

No. F6/DFS/MS/GH/SZ/2018/ 535

Dated: 28/3/18

FIRE SAFETY CERTIFICATE

Road, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus five upper floors, using basement as hall, ground floor as reception & office, first floor use by tenant (running a restaurant), second, third & fourth floor each having 06 guest rooms respectively (total 18 guest rooms) and fifth floor is sealed by owner, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/210 dated 11.02.2015. The premises was re-inspected by the officer concerned of this department on 16/03/2018 in presence of Sh. Amarpreet Singh Chadha, proprietor, and found that the guest house is running at basement, ground plus five upper floors, using basement as hall, ground floor as reception & office, first floor as office and vacant hall, second, third & fourth floor each having 06 guest rooms respectively (total 18 guest rooms) and fifth floor is sealed & owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on _____at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Amarpreet Singh Chadha (Owner), M/s. Deluxe Otani Inn, 6/85, WEA, Padam Singh Road, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Guest House Deluxe Otani Inn, 6/85, WEA, Padam Singh Road, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

Details of previous NOC

: F.6/DFS/MS/GH/2015/SZ/210 dated 11.02.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 16.03.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Amarpreet Singh Chadha, Owner

9. Year of Construction

: Before 1991

10. Applicant's letter No.

: Form 'J' dated nil

The said guest house is comprised of basement, ground plus five upper floors.

S. No.	Minimum Standards prevention and fire safe		Fire safety arrangements as per letter dt. 11.02.2015	Provided at site	Remarks MR/NMR
1	Access to building				201200000
	Road width		06 mts	Provided	MR
	Gate width			Directly accessible	MR
	Width of internal ro	oad /	N/A	N/A	N/A
2	Number, Width, Type &	Arrangement	t of Exits		
	a. Number of staircases		_ "		-
	A CONTRACTOR OF THE CONTRACTOR	Upper Floors		01	MR
	Basements			02	MR
	b. Width of staircases			-	- ,
	• Upper Floors			1.03 mts	MR being old case
	• Basements		Old Case Old Case	0.99 & 0.96 mt.	MR being old case
		. Protection of exits		-	*-
	• Fire check door			N/A	N/A
		 Pressurization No. of continuous staircases to 	N/A N/A	N/A	N/A
	e. No. of continuous		01	01	MR
	g. Width of Corridor		1.0 mt.	1.11 mts.	MR
	h. Door Size		Old case	→ 0.81 mts	MR being old case
3	Compartmentation.				
	Fire check door	N/A	N/A	N/A	
	Sealing of electrics	al shafts	N/A	Sealed	
	Fire Rating of shaft door		N/A	N/A	N/A
	Water Curtain		N/A	N/A	N/A
	• Fire Dampers		N/A	N/A	N/A
4	Smoke Management Sys	stem			J. Benefit
4	Smoke Management Sys			11	

	Basements	30 a/c per hour	Exhaust fan	MR			
	• Upper floors	12 a/c per hour	Natural Ventilation	MR			
5	Fire Extinguishers						
	 Total numbers 	16	Provided	MR			
	 Types 	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	 Total numbers on each floor 	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	7 Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 62 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper FloorSprinkler above false ceiling	N/A	N/A	N/A			
	Sprinkler doove raise centing	N/A	N/A	N/A			
11	Internal Hydrants	- P					
	Size of riser/down-comer	N/A	100 mm				
	Number of hydrants per floorHose Box	N/A	01 No.				
		N/A	01 No.				
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps Jockey Pump out put	N/A	N/A	N/A			
	ramp out put	N/A	N/A	N/A			
	pump nead	N/A	N/A	N/A			
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A			
A STATE OF	Standby Fullip Head	A	- " - " - " - " - " - " - " - " - " - "				

				Wal		
	>	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	>	Pump House Access	N/A	N/A	N/A	
2 ,-		Terrace level	"			
	•		450 LPM	450 LPM	MR	
		Head of the pump	30 mts	30 mts	MR	
		Power Supply	Required	Provided	MR	
	<u> </u>		Required	Provided	MR	
14	Captiv	e Water Storage for fire fighting.		4		
	•	Underground tank capacity	N/A	N/A	N/A	
	>	Draw-off connection	N/A	N/A	N/A	
	>	Fire service inlet	N/A	Provided		
	>	Access to tank	N/A	N/A	N/A	
	•	Overhead Tank capacity	Old Case	5000 lts	MR being old case	
15	Exit Si	gnage.	Required	Provided	MR	
16		on of Lifts.		0		
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	N/A	N/A	
	•	Communication In lift Car	Required	Provided	MR	
	•	Fireman's Grounding Switch	Required	Provided	MR	
	•	Lift Signage	Required	Provided	MR	
17	Standl	y power supply	Required	Provided	MR	
18	Standay power supply					
	>	Total Area	N/A	N/A	N/A	
	>	Location	N/A	N/A	N/A	
19	Fire C	o <mark>ntr</mark> ol Room				
		Detector System Panel	N/A	N/A	N/A	
		Flow Switch Panel	N/A	N/A	N/A	
	•	PA System Panel	N/A	N/A	N/A	
	•	Battery backup	Required	Provided	MR	
	•	Building Floor Plans	N/A	N/A	N/A	
20	_	Fire Protection Systems for	N/A	N/A	N/A	
	Protec	tion of special Risks, if any:				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/210 dated 11.02.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

166/DOBW

m. Scell FTM.

South (South) m. scell le 27/3