GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001 Dated: 28 03 12018

No. F6/DFS/MS/GH/SZ/2018/SS 2

FIRE SAFETY CERTIFICATE

Certified that M/s. Guest House Yug Villa located at 7A/14, WEA, Channa Market, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus three upper floors, using basement as hall/storage, ground floor as reception, lobby, office & 02 guest rooms, first, second & third floor each having 05 guest rooms respectively (total 17 guest rooms) and a pantry for staffs on the terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/142 dated 02.02.2015. The premises was re-inspected by the officer concerned of this department on 16/03/2018 in presence of Sh. Raman Kapoor, proprietor and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 28/03/2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 2803 2018 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Raman Kapoor, proprietor, M/s. Guest House Yug Villa, 7A/14, WEA, Channa Market, Karol Bagh, New Delhi- 110005

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Guest House Yug Villa 7A/14, WEA, Channa Mkt, Karol Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/142 dated 02.02.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 16-03-2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Sh. Raman Kapoor (Owner)

9. Year of Construction

: 2009-2010

10. Applicant's letter No.

: Form 'J' dated nil

The said guest house is comprised of basement, ground plus three upper floors.

	<u> </u>	to the prised of baseme		ce upper moors.	
S.		Vinimum Standards on fire vention and fire safety U/R 33	Fire safety arrangements as per letter dt. 20.11.2014	Provided at site	Remarks MR/NMR
1	Acces	s to building			
	•	Road width	06 mts	Provided	MR
	•	Gate width		Directly accessible	MR
	•	Width of internal road	N/A	N/A	N/A
2	Numb	er, Width, Type & Arrangeme	ent of Exits		
		aber of staircases	-	_	
	•	Upper Floors	01	01	MR
	•	Basements	02	02	MR
	b. Wid	t <mark>h of staircases</mark>	-	-	-
	•	Upper Floors	Old Case	1.26 mts	MR
	•	Basements	Old Case	1.24, 0.90 mts	MR being old case
	c. Prote	ection of exits	_	-	-
	•	Fire check door	N/A	N/A	N/A
		Pressurization	N/A	N/A	N/A
	e. No. terrace	of continuous staircases to	01	01	MR
		h of Corridor	N/A	N/A	N/A
2	h. Door		Old case	0.79 mts	MR being old case
3	Compa	rtmentation.		1	
		Fire check door	N/A	N/A	N/A
		Sealing of electrical shafts	Required	Sealed	MR
	1	Fire Rating of shaft door	N/A	N/A	N/A
		Water Curtain	N/A	N/A	N/A
	• 1	Fire Dampers	N/A	N/A	N/A
4	Smoke]	Management System.			1
		Basements	30 a/c per hour	Exhaust fan provided	I MP

	Total numbers	12	Provided	Mk			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
-	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming	system.					
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 82.5 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
7.1	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
Α.	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	· N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A			
	Standby Pump HeadAuto Starting/ Manual stopping	N/A	N/A	N/A			
	Pump House Access	N/A	N/A	N/A			
	Terrace level	N/A	N/A	N/A			
	101100 10101	1 - V					

	Discharge of pump	450 LPM	450 LPM	MR		
	➤ Head of the pump	30 mts	30 mts each	MR		
	> Power Supply	Required	Provided	MR		
	➤ Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for fire fightin	g.				
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
Ŷ	> Fire service inlet	N/A	Provided			
	> Access to tank	N/A	Provided			
	Overhead Tank capacity	5,000 lts	6,000 lts	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room		÷	-		
38	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/142 dated 02.02.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

243/2016 20103/2016

2000

M.K.CHATTOPADHYAY