GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 6 20

Dated: 6/9/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Crest Inn located at 4/27, WEA, Saraswati Marg, Karol Bagh, New Delhi- 110005, comprised of basement, ground plus four upper floors, using basement as hall / storage, ground floor as reception, hall & pantry, first, second & third floor each having 08 guest rooms respectively, fourth floor having 07 guest rooms (total 31 guest rooms) and the terrace floor is sealed the owner, was granted FSC by this department vide F6/DFS/MS/GH/2015/SZ/414 dated 23.03.2015. The premises was re-inspected by the officer concerned of this department on 26/03/2018 in presence of Sh. Jitendera Verma, general manager, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 6/4/18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 6/4/18 at New Delhi by.

6/4. (VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- 1. Sh. Manoj Kumar (Owner), M/s. Hotel Crest Inn, 4/27, WEA, Saraswati Marg, Karol Bagh, New Delhi- 110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Crest Inn, 4/27, WEA, Saraswati Marg,

Karol Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/414 dated 23.03.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 26.03.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Jitender Verma, General Manager : Before 2001

9. Year of Construction 10. Applicant's letter No.

: 1275/Addl. C.P/Lic(H) dated New Delhi the 22.02.2018

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 23.03.2015	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	Gate width		Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-		-		
	Upper Floors	01	01	MR		
	Basements	02	02	MR		
	b. Width of staircases	-	=	_		
	• Upper Floors	Old Case	1.27 mts	MR being old case		
	Basements	Old Case	1.43, 1.27 mts	MR being old case		
	c. Protection of exits	-	-	-		
	• Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	01	01	MR		
	g. Width of Corridor	1.0 mt.	1.16 mts.	MR		
	h. Door Size	Old case	0.80 mts	MR being old case		
3	Compartmentation.					
	• Fire check door	N/A	N/A	N/A		
	• Sealing of electrical shafts	N/A	Sealed			
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					

St. Co. Co.	Basements	30 a/c per hour	Exhaust fan	MR			
	Upper floors	12 a/c per hour	provided				
_			Natural Ventilation	MR			
5	Fire Extinguishers						
	• Total numbers	15	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
6	IS marking First Aid Hora Books	ISI marked	Provided	MR			
0	First-Aid Hose Reels.	0.1	D				
	Total numbers on each floor Levels of the second like th	01 30 m	Provided	MR			
	Length of hose reel hoseNozzle diameter	5 mm	Provided	MR			
7			Provided	MR			
/	7 Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	• Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 125 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.		8 H				
	• Basement	N/A	Provided	Area less than 200 sq. mts.			
	• Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants	•					
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.	1.					
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.			7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7			
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	, 11/11	11//1				

		M/20					
	Auto Starting/ Manual stopping	, N/A	N/A	N/A			
	Pump House Access	N/A	N/A	N/A			
	Terrace level						
	Discharge of pump	450 LPM	450 LPM	MR			
	Head of the pump	30 mts	30 mts	MR			
	> Power Supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.			2			
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	> Fire service inlet	N/A	Provided				
	> Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	Old case	5000 lts	MR being old case			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.			8			
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for	N/A	N/A	N/A			
	Protection of special Risks, if any:	,	<u> </u>				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/414 dated 23.03.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

FTM.

m.sell We 2/4.

F.T. letter is put up for Sign.

289/20/84