GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 62/

Dated:

6/4/18

FIRE SAFETY CERTIFICATE

Issued on 6/4/18 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- 1. Sh. Jagdish Chander Suri (Owner), M/s. Hotel Swisston Palace, 17A/18, WEA, Karol Bagh, New Delhi- 110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Swisston Palace, 17A/18, WEA, Karol

Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/371 dated 17.03.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 26.03.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

: Sh. K.K. Walia, Liaison manager

from the building side 9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 1348/Addl. C.P/Lic(H) dated New Delhi the 26.02.2018

The said guest house is comprised of basement, ground plus four upper floors.

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | Fire safety arrangements as per letter dt. 17.03.2015 | Provided at site | Remarks MR/NMR | | |
|-----------|---|--|---------------------|-------------------|--|--|
| 1 | Access to building | | | | | |
| | • Road width | 06 mts | Provided | MR | | |
| | Gate width | | Directly accessible | MR | | |
| | Width of internal road | N/A | N/A | N/A | | |
| 2 | Number, Width, Type & Arrangement | t of Exits | | | | |
| | a. Number of staircases | - | - | - | | |
| | Upper Floors | 01 | 01 | MR | | |
| | Basements | 01 | 01 | MR being old case | | |
| | b. Width of staircases | - | - | - | | |
| | Upper Floors | Old Case | 1.25 mts | MR being old case | | |
| | Basements | Old Case | 1.15 mts | MR being old case | | |
| | c. Protection of exits | - | | - | | |
| | Fire check door | N/A | N/A | N/A | | |
| | Pressurization | N/A | N/A | N/A | | |
| | e. No. of continuous staircases to | 01 | 01 | MR | | |
| | terrace g. Width of Corridor | 1.0 mt. | 1.18 mts. | MR | | |
| | h. Door Size | Old case | 0.80 mts | MR being old case | | |
| 3 | Compartmentation. | | | | | |
| | Fire check door | N/A | N/A | N/A | | |
| | Sealing of electrical shafts | N/A | Sealed | | | |
| | • Fire Rating of shaft door | N/A | N/A | N/A | | |
| | Water Curtain | N/A | N/A | N/A | | |
| | Fire Dampers | N/A | N/A | N/A | | |
| 4 | Smoke Management System. | | | 1 | | |

| | a Hanor flagge | 12 0/2 0001 | provided | IVII |
|----|--|---|---------------------|------|
| | Upper floors | 12 a/c per hour | Natural Ventilation | MR |
| 5 | Fire Extinguishers | | | |
| | Total numbers | 16 | Provided | MR |
| | • Types | CO ₂ , ABC, WCO ₂ | Provided | MR |
| | IS marking | ISI marked | Provided | MR |
| 6 | First-Aid Hose Reels. | | | |
| | Total numbers on each floor | 01 | Provided | MR |
| | Length of hose reel hose | 30 m | Provided | MR |
| | Nozzle diameter | 5 mm | Provided | MR |
| 7 | Automatic fire detection and alarming | system. | | |
| | Type of detectors | N/A | N/A | N/A |
| | Location of Main Panel | N/A | N/A | N/A |
| | Location of Repeater Panel | N/A | N/A | N/A |
| | Alternate source of power | Required | D.G. set 82.5 KVA | MR |
| | Hooters' Location | N/A | N/A | N/A |
| 8 | MOEFA | Required | Provided | MR |
| 9 | Public Address System. | Required | Provided | MR |
| 10 | Automatic Sprinkler System. | | | |
| | Basement | Required | Provided | MR |
| | Upper Floor | N/A | N/A | N/A |
| | Sprinkler above false ceiling | N/A | N/A | N/A |
| 11 | Internal Hydrants | | | |
| | Size of riser/down-comer | N/A | N/A | N/A |
| | Number of hydrants per floor | N/A | N/A | |
| | Hose Box | N/A | | N/A |
| | | 11/21 | N/A | N/A |
| 12 | Yard Hydrants. | | | |
| | Total number of hydrants | N/A | N/A | N/A |
| 12 | Hose Box | N/A | N/A | N/A |
| 13 | Pumping Arrangements. | | • | |
| | Ground Level | | | |
| | Discharge of main PumpHead of Main pump | N/A | N/A | N/A |
| | Head of Main pumpNumber of main pumps | N/A | N/A | N/A |
| | Jockey Pump out put | N/A | N/A | N/A |
| | Jockey pump head | N/A | N/A | N/A |
| | Standby Pump out put | N/A | N/A | N/A |
| | Standby Pump Head | N/A | N/A | N/A |
| | | N/A | N/A | N/A |

No.

| , | Auto Starting/ Manual stopping | N/A | N/A | N/A | | | |
|--------------|--|----------|----------|------------------|--|--|--|
| 1 | > Pump House Access | N/A | N/A | N/A | | | |
| | Terrace level | | | | | | |
| | Discharge of pump | 450 LPM | 450 LPM | MR | | | |
| | Head of the pump | 30 mts | 30 mts | MR | | | |
| | > Power Supply | Required | Provided | MR | | | |
| | Auto Starting of pump | Required | Provided | MR | | | |
| 4 | Captive Water Storage for fire fighting. | | | | | | |
| | Underground tank capacity | N/A | N/A | N/A | | | |
| | > Draw-off connection | N/A | N/A | N/A | | | |
| | Fire service inlet | N/A | N/A | N/A | | | |
| | Access to tank | N/A | N/A | N/A | | | |
| | Overhead Tank capacity | Old case | 5000 lts | MR being old cas | | | |
| 5 | Exit Signage. | Required | Provided | MR | | | |
| 5 | Provision of Lifts. | | | | | | |
| 18 | Pressurization of Lift Shaft | N/A | N/A | N/A | | | |
| · · | Pressurization of Lift lobby | N/A | N/A | N/A | | | |
| Spine : A | Communication In lift Car | Required | Provided | MR | | | |
| | Fireman's Grounding Switch | Required | Provided | MR | | | |
| ~ | Lift Signage | Required | Provided | MR | | | |
| 7 | Standby power supply | Required | Provided | MR | | | |
| 8 | Refuge Area. | | | | | | |
| | > Total Area | N/A | N/A | N/A | | | |
| | > Location | N/A | N/A | N/A | | | |
| 9 | Fire Control Room | | | | | | |
| | Detector System Panel | N/A | N/A | N/A | | | |
| - | Flow Switch Panel | N/A | N/A | N/A | | | |
| | PA System Panel | N/A | N/A | N/A | | | |
| | Battery backup | Required | Provided | MR | | | |
| | Building Floor Plans | N/A | N/A | N/A | | | |
| | | | | | | | |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/371 dated 17.03.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

Miscelle Weight who for Sign.

F. T. letter is put up for Sign.