GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2018/ No 2 631

Dated :- 9-1-4-1-8-

FIRE SAFETY CERTIFICATE

Certified that the M/s Garam Dharam Dhaba (A Unite of Veeru Foods Pvt. Ltd.) located at M-16, Ground & Mezzanine floor, Outer Circle, Connaught Place, New Delhi comprises of Ground + Mezzanine + 02 Upper floor owned/occupied by M/s Garam Dharam Dhaba was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/1308 dated 21/07/15. The premises was re-inspected by the officer concerned of this department on 03/04/18 in the presence of Mr. Ravi Ram (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assemblys Building, Group – D at Ground & Mezzanine floor with effect from – P for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 9-1-4-12----at New Delhi by.

(Vipin Kental) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

2. The Manager,

M/s Garam Dharam Dhaba (A Unite of Veeru Foods Pvt. Ltd.),

M-16, Ground & Mezzanine floor, Outer Circle, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building M/s Garam Dharam Dhaba (A Unite of Veeru Foods Pvt. Ltd.)

at M-16, Ground & Mezzanine floor, Outer Circle,

Connaught Place, New Delhi 2. Type of occupancy:-Assembly Building Group-D Gr. + Mezzanine + 02 upper floors

Restaurant at Ground + Mezzanine floor

3. Type of case:-

4. Details of previous FSC:-F6/DFS/MS/EH/2015/NDZ/1308 dated

21/07/15

5. Fire safety directives No.-N/A 6. Date of inspection:-

03/04/18 Sh. Manoj Kumar Sharma (ADO/CC)

7. Name of the inspecting officer:-

8. Name & designation of officer from the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Ravi Ram (Manager)

Old Heritage Bldg.

Nil diary dated 16/03/2018

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR			
1.	Access to Building						
	1) Road width	09 mtr	13 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases						
	1. Upper floors	02 No.	02 No.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase		*				
	1. Upper floors	1.25 mtr. & 0.90 mtr.	1.50 mtr. (Iron) 0.90 to 1.15 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	N/A	N/A	N/A			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	N/A	N/A	N/A			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	02 mtr.	02 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Exhaust fan	MR			
5.	Fire Extinguishers						
	1) Total numbers	06 Nos.	06 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	Provided	MR			

6.	First-Aid Hose Reel						
	1) Total number of eachfloor	01		01		M	
	2) Length of hose reel hose		mtr.	-	mtr.	M	
	3) Nozzle diameter		mm	-	mm	M	R
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A		N/			/A
	2) Location of main panel	N/A		N/			/A
	3) Location of repeater panel			N/A		N/A N/A	
	4) Alternate source of power	N/		N/			
	5) Hooter's Location	N/A		N/A		N/A	
8.	MOEFA	_	quired	-	ovided	1000000	R
9.	Public Address System	N/.	A	N/	/A	N	/A
10.	Automatic Sprinkler Syster	n	×				
	1) Basement	N/.		N			/A
	2) Upper floors	N/.		-	ovided		/A
	3) Sprinkler above false	N/.	A	N	/A	N	/A
	ceiling						
11.	Internal Hydrants			1.0			
	1) Size of riser/down-comer		0 mm	_	00 mm		IR IR
	2) Number of hydrants per	01		01		IV.	IR.
	floor	0.1		0.1	1	N/	IR
	3) Hose box	01		01	L-	IV.	IK
12.	Yard Hydrants	1 3 1/	' A	NI	/A	N	/A
	1) Total number of hydrants	N/	-	-			/A
	2) Hose box	N/	A	11	/A	114	//
13.	Pumping Arrangement						
	1) Ground level		> T / A		NI/A	- 0	N/A
	a) Discharge of main		N/A		N/A		IN/A
	pump		N/A		N/A		N/A
	b) Head of main pum				N/A		N/A
	c) Number of main p		N/A N/A		N/A		N/A
	d) Jockey pump out p		N/A N/A		N/A		N/A
	e) Jockey pump head		N/A		N/A		N/A
	f) Stand by pump ou		N/A		N/A		N/A
	g) Stand by pump he h) Auto starting/Man		N/A		N/A		N/A
	h) Auto starting/Man stopping	iual	1 1/11		1 3/4 1		
	2) Terrace level						
	a) Discharge of pum	n	450 LPM		450 LPM		MR
	b) Head of pump	۲	30 mtr.		30 mtr.		MR
	c) Power supply		Required		Provided		MR
	d) Auto starting of pu	umn	Required		Provided		MR
14.	Captive Water Storage	for Fi	A 70				
14.	1) Under ground tank	k	N/A	7	N/A		N/A
	capacity						
	a) Draw-off connect	ion	N/A		N/A		N/A
	b) Fire service inlet		Required		Provided		MR
	c) Access to tank		N/A		N/A		N/A
	d) Over head tank capacity	1			10,000 ltr.		MR

En

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any: ABC & Co2	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DF\$/MS/EH/2015/NDZ/1308 dated 21/07/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Derolyoz)

(CEP M. SCELL MET)

F.T. Little is pert up for ing.