GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 6 90

Dated: 12/9/18

FIRE SAFETY CERTIFICATE

Issued -- 12-4-4-at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1428/Addl. C.P/Lic. (H) dated 07/03/2018.
- 2. The Manager, Centra Inn Guest House at 2503-A, Nalwa Street, Chuna Mandi, Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

| INSPECTION REPOR |
|------------------|
|------------------|

Centra Inn Guest House at 2503-A, Nalwa 1. Name & address of the building

Street, Chuna Mandi, Pahar Ganj, New Delhi

Residential, Sub Division-A-1 2. Type of occupancy:-

Ground + 04 Upper floors (total 24 guest rooms)
Ground floor (Reception + office), 1st floor to 3rd floor (08 guest rooms at each floor) and 4th floor

(staff rooms + open terrace)

3. Type of case:-Renewal

No. F6/DFS/MS/GH/2015/NDZ/1484 dated 4. Details of previous FSC:-

17/08/15.

5. Fire safety directives No.-N/A

30/03/18 6. Date of inspection:-Sh. Manoj Kumar Sharma (ADO/CC)

7. Name of the inspecting officer:-

From the building side:-

9. Year of construction:-

8. Name & designation of officer

Mr. Gagan Talwar (Owner)

Old

1428/Addl. C.P/Lic. (H) dated 07/03/2018. 10. Applicant's letter No:-

| | | | | Old Case | |
|-------|--|--|------------------|-------------------|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR | |
| 1. | Access to Building | | | | |
| | 1) Road width | 06 mtr. | 06 mtr. | MR | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arr | | | | |
| | A. Number of staircases | , | | | |
| | 1. Upper floors | 01 Nos. | 01 Nos. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | 1.25 mtr. | 1.25 mtr. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous | 01 | 01 | MR | |
| | staircase to terrace | | 1 | | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 01 mtr. | 01 mtr. | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | 30 ACPH | N/A | N/A | |
| | 2) Upper floors | 12 ACPH | Natural | MR | |
| 5. | Fire Extinguishers | # d | | | |
| | 1) Total numbers | 10 Nos. | 10 Nos. | MR | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | |

| | 3) ISI marking | Required | Provided | MR |
|-----|-------------------------------|-------------|----------|----------------|
| 6. | First-Aid Hose Reel | rtequirea | Tiovided | IVIIX |
| | 1) Total number of eachfloor | 01 | 01 | MR |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR |
| 7. | Automatic Fire Detection & | | | IVIK |
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| 10. | Automatic Sprinkler System | required | Tiovided | IVIK |
| 100 | 1) Basement | N/A | N/A | N/A |
| | 2) Upper floors | N/A | N/A | N/A N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A N/A |
| | ceiling | 14/11 | 17/71 | IN/A |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| | floor | | | |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | Pumping Arrangement | | . • | |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | | | |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | | | |
| | 2) Terrace level | | | and the second |
| | a) Discharge of pump | 180 LPM | 180 LPM | MR |
| | b) Head of pump | 30 mtr. | 30 mtr. | MR |
| | c) Power supply | Required | Provided | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 4. | Captive Water Storage for Fi | re Fighting | | |
| | 1) Under ground tank | N/A | N/A | N/A |
| | capacity | <u> </u> | | |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |

| | c) Access to tank | N/A | N/A | N/A |
|-----|---|-----------|-----------|-----|
| | d) Over head tank capacity | 2500 ltr. | 2500 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| 4 | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | ·MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syste Risk, if any: | N/A | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1484 dated 17/08/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

496/cfo NM

5/4. 19/4.

C.F.F.

M. Scell 4/4.

F. J. Letter is put up for logn pl