GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 844

Dated: 25 04/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Blue Sapphire, located at 3351-54, Christen Colony, Bank Street, Karol Bagh, New Delhi- 110005, comprised of basement, ground plus four upper floors, using basement as nail, ground floor as reception, office, hall, shops & staff pantry, first floor having 09 guest rooms & 01 store room, second floor having 05 guest rooms & 01 store room and third floor having 09 guest rooms & 01 store room (total 23 guest rooms) and one staff room on terrace floor, was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2015/NDZ/148 dated 02.02.2015. The premises was re-inspected by the officer concerned of this department on 16/04/2018 in presence of Mr. Naresh Kumar (manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 25 04 18 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Suman Anand (Owner), M/s. Blue Sapphire, 3351-54, Christen Colony, Bank Street, Karol Bagh, New Delhi- 110005.

2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

: M/s. Blue Sapphire, 3351-54, Christen Colony, Bank Street, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2015/NDZ/148 dated 02.02.2015.

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 16.04.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Mr. Naresh Kumar (manager)

9. Year of Construction

: Before 2002

10. Applicant's letter No.

: 1323/Addl. C.P./Lic (H) dated New Delhi the 23.02.2018

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 02.02.2015	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	06 mts	Provided	MR	
	• Gate width	4.5 mts	Directly accessible	MR	
	Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	-	-	-	
	Upper Floors	Old Case	01	MR being old case	
	Basements	Old Case	01	MR being old case	
	b. Width of staircases	-	-	-	
	Upper Floors	1.25 mts	1.07-1.19 mts	MR being old case	
	Basements	1.25 mts	1.14 mts	MR being old case	
	c. Protection of exits	-	- 1	-	
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	e. No. of continuous staircases to	01	01	MR	
	g. Width of Corridor	Old case	2.0 mts	MR	
	h. Door Size	Old case	0.87 mts	MR being old case	
3	Compartmentation.		4		
	Fire check door	N/A	N/A	N/A	
	Sealing of electrical shafts	N/A	Sealed	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	• Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.				
	Basements	30 a/c per hour	Exhaust Fan provided	MR	
	Upper floor	12 a/c per hour	Natural Ventilation	MR	

T				-		
5	Fire Extinguishers					
	Total numbers	12	Provided	MR		
,	• Types	CO ₂ , ABC, WCO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
7	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	Required	D.G. set 45 KVA	MR		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
•	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	\$			
			N/A	N/A		
12	Yard Hydrants.					
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level		<u> </u>			
	Discharge of main Pump	N/A	N/A	N/A		
	> Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head	N/A		N/A		
	> Auto Starting/ Manual stopping	ng	N/A	N/A		
	 Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A	N/A N/A N/A	N N		

6	First-Aid Hose Reels.				
	Total numbers on each floor	01	Provided	MR	
	Length of hose reel hose	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming sy	stem.			
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	Required	D.G. set 45 KVA	MR	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.				
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.				
	Ground Level		<u> </u>		
	Discharge of main Pump	N/A	N/A	N/A	
	➤ Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	> Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level				
	Discharge of pump	450 LPM	Provided	MR	
	➤ Head of the pump	30 mts	Provided	MR	
		u u	1		

1	Power Supply	Required	Provided	MR		
	Auto Starting of pump	N/A	N/A	N/A		
14	Captive Water Storage for fire fighting.					
, -	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	old case	5000 lts	MR, old cas		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
ERV	Flow Switch Panel	N/A	N/A	N/A		
100	PA System Panel	N/A	N/A	N/A		
8	Battery backup	Required	Provided	MR		
9	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/NDZ/148 dated 02.02.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

131/Do(Sw) clt-19.04.18

Name Di

Name M.K.CHATTOPADHYAY
Div. Officer (South West)