GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 800

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Grand President located at 17A/8, WEA, Karol Bagh, New Delhi- 110005, comprised of basement, ground plus four upper floors, using basement as hall/storage, ground floor as reception, office & hall, first & second floor each having 07 guest rooms and third floor having 06 guest rooms (total 20 guest rooms) and a pantry for staff on fourth floor, was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2015/SZ/491 dated 07.04.2015. The premises was re-inspected by the officer concerned of this department on 16/04/2018 in presence of Mr. Chetan Bhandari (owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23/04/20/B for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 23/04/2018 at New Delhi by.

23/4 (VIPEN KENTAL) CHIEF FIRE OFFICER

Dated: 23/04/2018

Copy to:-

1. Sh. Chetan Bhandari (Owner), M/s. Hotel Grand President, 17A/8, WEA, Karol Bagh, New 23, Delhi- 110005.

2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

Name & address of the building

: M/s. Grand President guest house, 17A/8, WEA, Karol Bagh, New Delhi.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

: F.6/DFS/MS/GH/2015/SZ/491dated 07.04.2015.

4. Details of previous NOC 5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 16.04.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

: Sh. Chetan Bhandari, owner

from the building side 9. Year of Construction

: Before 2007

10. Applicant's letter No.

: 1588/Addl. C.P./Lic (H) dated New Delhi the 21.03.2018

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 07.04.2015	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	06 mts	Provided	MR	
	• Gate width	4.5 mts	Directly accessible	MR	
	• Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangement	of Exits			
	a. Number of staircases	-	-	-	
	• Upper Floors	Old Case	01	MR being old case	
	• Basements	02	02	MR	
	b. Width of staircases	-	-		
	• Upper Floors	1.25 mts	1.25 mts	MR	
	Basements	1.25 mts	1.13, 1.08 mts	MR being old case	
	c. Protection of exits	-	-	-	
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	e. No. of continuous staircases to	01	01	MR	
	terrace	Old case	1.42 mts	MR	
	g. Width of Corridor	Old case	0.80 mts	MR being old case	
	h. Door Size	Old case	0.00 III.5		
3	Compartmentation.	N/A	N/A	N/A	
	Fire check door			N/A	
	• Sealing of electrical shafts	N/A	Sealed		
	• Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	• Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.		Exhaust Fan provided MD		
	Basements	30 a/c per hour	Exhaust Fall provided	MIK	
27342	• Upper floor	12 a/c per hour	Natural Ventilation	MR	

	Total numbers	12	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 125 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	12 Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	> Discharge of main Pump	N/A	N/A	N/A			
	➤ Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	> Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	Auto Starting/ Manual stoppin	ng N/A	N/A	N/A			
	> Pump House Access	N/A	N/A	N/A			
	Terrace level						

	> Power Supply	Required	Provided	MR			
1	> Auto Starting of pump	N/A	N/A	N/A			
14	Captive Water Storage for fire fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	Provided				
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	Old case	6000 lts	MR, old cas			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.	•	a a				
7	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
RE SE	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
1411	Battery backup	Required	Provided	MR			
7	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/491 dated 07.04.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

416/DOCCO) 04-19/04/18

Name M.K.CHA TOPADHYAY
Div. Officer (South West)

Land