GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/NDZ/2018/ 857

Dated:-

27/04/18

FIRE SAFETY CERTIFICATE

Certified that the Hindustan Times Building located at 18-20, K.G. Marg, New Delhi comprised of Basement + Ground + 17 Upper floors owned/occupied by Hindustan Times was granted FSC by this department vide letter No. F6/DFS/MS/NDZ/2015/359 dated 16/03/2015. The premises was re-inspected by the officer concerned of this department on 04/04/18 in the presence of Sh. N.C. Gautam (DGM fire & safety) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Business Building, with effect from 27 1/13--for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

Sh. N.C. Gautam, DGM fire & safety, Hindustan Times Building, 18-20, K.G. Marg, New Delhi

Condition for the validity of fire safety certificate

- 1. at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

N/15

INSPECTION REPORT

1. Name & address of the building: Hindustan Times Building

18 & 20 K.G. Marg, New Delhi.

2. Type of occupancy

: Business Building

B + Gr. + 17 upper floor

3. Type of case:-

: New Case

4. Details of previous FSC

: F6/DFS/MS/NDZ/2015/359 dated

16/03/15.

5. Fire safety directives No.

: N/A

6. Date of inspection:-

04/04/18

7. Name of the inspecting officer

: Sh. M.K. Sharma ADO/CC

8. Name & designation of officer From the building side

: Sh. N.C. Gautam (DGM fire & safety)

9. Year of construction

: Prior to 1974

10. Applicant's letter No

: Nil Dated 20/03/2018

10.	Applicant's letter No	. MII Dated	20103	72010	Ole	d Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Pro	ovided at site	1000	marks R/NMR	
1.	Access to Building						
	1) Road width	13 mtr.	30	Mtr.	Ml		
	2) Gate width	06 mtr.	06	mtr.	M	R	
	3)Width of internal road	06 mtr.	06	mtr.	M	R	
2.	Number, Width Type & Arrangement of Exits						
2.	A. Number of staircases						
	1. Upper floors	02 Nos.	02	Nos.	MR		
	2. Basements	01 Nos.	01	Nos.	M	R	
	B. Width of staircase						
	1. Upper floors	1.5 mtr.		3 mtr. each	MR		
	2. Basements	1.5 mtr.	1.8	3 mtr. & ramp	MR		
	C. Protection of exits	-					
	1. Fire check door	Required		rovided	MR		
	2. Pressurization	NA	N.		NA		
	D. No. of continuous	02	02	2	02	2	
	staircase to terrace				NI		
	E. Width of corridor	NA		NA		NA MR	
	F. Door size	1.0 mtr.	1.	1.0 mtr.		IK	
3.	Compartmentation					(D)	
	1) Fire check door	Required		Provided		1R	
	2) Sealing of electrical shafts	Required	-	Provided		MR	
	3) Fire rating of shaft door	Required		rovided		IR	
	4) Water curtain	NA	N			IA (P)	
N N	5) Fire Dampers	Required	P	Provided		1R	
4.	Smoke Management System	an contr		D '1 1		MD	
	1) Basements	30 ACPH		Provided		MR MR	
	2) Upper floors	12 ACPH	-	Natural		IVIK	
5.	Fire Extinguishers		120		MR		
	1) Total numbers	101	,	120 ABC CO2		-	
	2) Types	ABC, CO2		ABC, CO2 Provided		MR MR	
	3) ISI marking	Required		rrovided		IVIN	
6.	First-Aid Hose Reel	102		02	-	MR	
	1)Total number	02		30 m		MR	
	2) Length of hose reel hose	30 m		5 mm		MR	
	3) Nozzle diameter	5 mm		J IIIII		IVII	

7.	Automatic Fire Detection & A	Jarming System		
	1) Type of detectors	Required	Drovidad	1
	2) Location of main panel	At Gr. floor	Provided	MR
	3) Location of repeater panel	Floor wise	Provided	MR
	4) Alternate source of power	7	Provided	MR
	5) Hooter's Location	Required	Provided	MR
8.	MOEFA	Each floor	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automotic Sprinklan S	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement	Required	Provided	MR
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false	Required	Provided	MR
11.	ceiling			
11.	Internal Hydrants			
	1) Size of riser/down-comer	150 MM	150 MM	MR
	2) Number of hydrants per	02	02	MR
	Basement			
10	3) Hose box each floor	02	02	MR
12.	Yard Hydrants			
	1) Total number of hydrants	Required	Provided	MR
	2) Hose box	Required	Provided	MR
				14117
13.	Pumping Arrangement	Common		
	1) Ground level			
	a) Discharge of main	2850 LPM	2850 LPM	MD
	pump		2030 LI WI	MR
	b) Head of main pump	126 mtr.	126 mtr.	MR
	c) Number of main	02	02	
	pump		02	MR
	d) Jockey pump out put	900 LPM	900 LPM	MD
	e) Jockey pump head	126 mtr.		MR
	f) Stand by pump	4500 LPM	126 mtr.	MR
	output	TOU LIVI	4500 LPM	·MR
	g) Stand by pump head	126 mtr.	126	
	h) Auto starting/Manual		126 mtr.	MR
	stopping	Required	Provided	MR
	2) Terrace level			
		NIA		
	8 - 1	NA	NA	NA
	, PP	NA	NA	NA
	c) Power supply	NA	NA	NA
	d) Auto starting of	NA	NA	NA
1	pump Continu Water St. C. Fi			
4.	Captive Water Storage for Fire			
	1) Under ground tank	2,00,000 ltr.	2,00,000 ltr.	MR
	capacity			
	a) Draw-off connection	Required *	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacit	y 25,000 litr.	25,000 litr.	MR
			,	
· .	Exit Signage.	Required	Provided	MR
),	Provision of Lifts.		1.071404	IVII
	a) Pressurization of lift	Daguina 1	D 1 1	
	shaft	Required	Provided	MR
	b) Pressurization of lift	Required	Provided	
		RAGILIPAN	I Daniel I	MR

	lobby			
	c) Communication in lift	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	NA	NA	NA
	Total area location	NA	NA	NA
19.	Fire Control Room			- N
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	NA	NA	NA
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	O. Special Fire Protection System for Protection of special Risk, if any:			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2018/1108 dated 19/03/2018 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/2015/NDZ/359 dated 16/03/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DCFO/NDZ

M-scell FT 161.

F.T letter in Jon

(NDZ) miscell