GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/95

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Gold Souk located at 7A/35, WEA, Channa Market, Karol Bagh, New Delhi- 110005, comprised of basement, stilt, ground plus three upper floors, using basement as storage, stilt floor as parking and reception, ground floor having 04 guest rooms, first floor having 05 guest rooms, second having 04 guest rooms and third floor having 05 guest room (total 18 guest rooms) and a pantry for staff in temporary shed on terrace floor, was issued FSC by this department vide letter No. F.6/DFS/MS/2015/SZ/595 dated 23.04.2015. The guest house building was re-inspected by the officer concerned of this department on 10/04/2018 in the presence of Sh. Rahul Kumar (manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 27 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 2704 2018 at New Delhi by.

(VIPEN KENTAL)
CHIEF FIRE OFFICER

Copy to:-

- 1. Shri Vikas Kumar (Owner), M/s. Hotel Gold Souk, 7A/35, WEA, Channa Market, Karol Bagh, New Delhi- 110005.
- 2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of UBBL-16.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

: M/s. Hotel Gold Souk, 7A/35, WEA, Channa Market, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/2015/SZ/595 dated 23.04.2015.

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 10.04.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Sh. Rahul Kumar, manager

9. Year of Construction

: Before 2010

10. Applicant's letter No.

: 83-87/Addl. C.P./Lic (H) dated New Delhi the 18.01.2018

The said guest house is comprised of basement, stilt, ground plus three upper floors.

S. No.		inimum Standards on fire ention and fire safety U/R 33	Fire safety arrangements as per letter dt. 23.04.2015	Provided at site	Remarks MR/NMR
1	Access	to building		Desided	
	•	Road width	06 mts	Provided	MR
		Gate width	4.5 mts	Provided	MR
		Width of internal road	N/A	N/A	N/A
2		er, Width, Type & Arrangement	of Exits		
		nber of staircases	-		-
			01	01	MR
	•	Upper Floors	02	02	MR
	•	Basements	-	-	-
	b. Wi	dth of staircases	1.25	1.48 - 1.55 mts	MR
	•	Upper Floors	1.25 mts	1.31, 1.20 mts	MR
	•	Basements	1.25 mts	1.51, 1.20 mes	
	c. Pro	tection of exits	- DI/A	N/A	N/A
	, •	Fire check door	N/A	N/A	N/A
	•	Pressurization	N/A	01	MR
	e. N	o. of continuous staircases to	01		MR being old case
		idth of Corridor	Old case	1.21 mts	MR being old case
	_	oor Size	Old case	0.86 mts	MR being old case
3		partmentation.		- 10	
3		Fire check door	N/A	N/A	N/A
	and the second s	Sealing of electrical shafts	N/A	Sealed	
	And the second second	Fire Rating of shaft door	N/A	N/A	N/A
	and a received	Water Curtain	N/A	N/A	N/A
		Fire Dampers	N/A	N/A	N/A
4	Sm	oke Management System.	30 a/c per hour	Exhaust fan provided	MR
		BasementsUpper floors	12 a/c per hour		MR

	Total numbers	20	Provided	MR		
7 2 1 2	• Types	CO ₂ , ABC, WCO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
12	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming	: 1				
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	Required	D.G. set 125 KVA	MR		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	N/A	Provided	Area is less than 200 sq. mts.		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
11	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
12	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.		-			
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	> Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	> Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head	N/A	N/A	N/A		
	> Auto Starting/ Manual stoppi	ing	DT/A	N/A		
	> Pump House Access	N/A	N/A	N/A		
	Terrace level	N/A	N/A	IVAX		

	1	fred of the pump	30 mts	Provided	MR			
-		Power Supply	Required	Provided	MR			
		Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.							
	•	Underground tank capacity	N/A	N/A	N/A			
	>	Draw-off connection	N/A	N/A	N/A			
	>	Fire service inlet	N/A	N/A	N/A			
	>	Access to tank	N/A	N/A	N/A			
	•	Overhead Tank capacity	5000 lts	5000 lts	MR			
15	Exit S	ignage.	Required	Provided	MR			
16	Provision of Lifts.							
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	Required	Provided	MR			
	•	Fireman's Grounding Switch	N/A	N/A	Old lift			
	•	Lift Signage	Required	Provided	MR			
17	Stand	by power supply	Required	Provided	MR			
18	Refuge Area.							
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19	Fire Control Room							
		Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Battery backup	N/A	N/A	N/A			
	,	Building Floor Plans	N/A	N/A	N/A			
20		al Fire Protection Systems for tion of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/2015/SZ/595 dated 23.04.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

12/04/20/8 12/04/20/8

DCFO (SZ)

Rang 16/4

FT/O.

Name M.K.CHATTOPADHYAY
Div. Officer (South West)