## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 738

## FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Lucky Inn located at 12A/12, WEA, Karol Bagh, New Delhi110005, comprised of basement, ground plus three upper floors, using basement as hall/storage, ground floor as reception & 09 guest rooms, first, second & third floor each having 11 guest rooms respectively (total 42 guest rooms) was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2015/SZ/468 dated 31.03.2015. The premises was re-inspected by the officer concerned of this department on 12/04/2018 in presence of Sh. Sanjay Kumar (manager), and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23/04/2016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 23/04/2018 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Dated: 23/04/2018

## Copy to:-

- 1. Sh. Parveen Manchanda (Owner), M/s. Hotel Lucky Inn, 12A/12, WEA, Karol Bagh, New Delhi-110005.
- 2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

## Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

1. Name & address of the building : M/s. Hotel Lucky Inn, 12A/12, WEA, Karol Bagh, New

Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2015/SZ/468 dated 31.03.2015.

5. Fire Safety directives letter No : Nil

6. Date of inspection : 12.04.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side : Mr. Parveen Manchanda, Owner

9. Year of Construction : Before 1990

10. Applicant's letter No. : 1582/Addl. C.P./Lic (H) dated New Delhi the 21.03.2018

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 31.03.2015	Provided at site	Remarks MR/NMR		
1	Access to building					
	• Road width	06 mts	Provided	MR		
	Gate width		Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement	of Exits				
	a. Number of staircases	2		-		
	Upper Floors	02	02	MR		
	Basements	02	02	MR		
	b. Width of staircases	-	-	- ·		
	• Upper Floors	1.25 mts	1.20, 0.90 mts	MR being old case		
2	Basements	1.25 mts	1.11, 0.92 mts	MR being old case		
	c. Protection of exits	-	i <del>-</del>	-		
	• Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	e. No. of continuous staircases to	01	02	MR		
	terrace	Old case	1.05 mts	MR being old case		
	g. Width of Corridor	Old case	0.80 mts	MR being old case		
	h. Door Size		_			
3	• Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	Sealed	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4						
	Smoke Management System.  • Basements	30 a/c per hour	Exhaust Fan provided	MR		
	Upper floors	12 a/c per hour	Natural Ventilation	MR		

5	Fire Extinguishers						
	Total numbers	10	Provided	MR 💗			
	• Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	02	Provided	MR			
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
\	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 62 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
11	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.	5					
12	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	➤ Head of Main pump	N/A	N/A	N/A			
	> Number of main pumps	N/A	N/A	N/A			
	> Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	> Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	Auto Starting/ Manual stopp		N/A	N/A			
	> Pump House Access	N/A	N/A	N/A			

		14/30					
-	> Power Supply	Required	Provided	MR			
PX.	> Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	Provided				
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	old case	5000 lts	MR, old case			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room			*			
SER	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
W-10	• PA System Panel	N/A	N/A	N/A			
8	Battery backup	Required	Provided	MR			
ire On	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/468 dated 31.03.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

13/4/18 1402/cfo22

derf

Name M.K.CHATTOPADHYAY
Div. Officer (South West)