T any

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/EH/2018/ 855

Dated 27 04/2018

FIRE SAFETY CERTIFICATE

Center Shivaji Palace, Raja Garden, New Delhi – 110027. was issued FSC vide Letter No. F6/DFS/MS/EH/2015/271 dated 26-02-2015 and FSC to mall vide letter no. F6/DFS/MS/2017/773 dated 30-05-2017. The premises was re inspected by the officers concerned of this department on 10-04-2018 in the presence of Mr. Prabhdeep Singh (Owner) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D with effect from 27/01/2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 27,04 2018.. at New Delhi by.

(Atul Garg) Chief Fire Officer Delhi Fire Service.

Copy to:

- 1. The Manager, Castle 24, TF 01, City Square Mall, Plot No -7-8, Distt Center Shivaji Palace, Raja Garden, New Delhi 27.
- 2. The Dy Health Officer, NDMC, West Zone, Rajori Garden, New Delhi 110027

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Restaurant Castle 24, TF-01, City Square Mall, Plot No -7-8, Distt Center Shivaji Palace, Raja Garden, New Delhi – 27.

2. Type of Occupancy

: Assembly

3. Type of Case : Renewal (Situated in Mall already issued NOC vide letter no. F6/DFS/MS/2017/773 dated 30-05-2017)

4. Details of previous NOC: Letter No. F6/DFS/MS/EH/2015/271 dated 26-02-15

5. Fire Safety directives Letter No.: FSC Issued to the mall

6. Date of inspection

: 10-04-2018

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

from the building side

: Mr. Prabhdeep Singh (Owner)

9. Year of Construction

: 2006

10. Applicant's letter No.

: Nil Dated 26-02-2018

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requireme	nts	Provided at site	1	narks NMR
1.	Access of building (Mall)					121
	 Road width 	30 m		Provided	MR	
	Gate width	6 m		Provided	MR	
enterentional	 Width of internal road 	6 m		Provided	MR	
2.	Number, width, Type & Arrange	gements of exits				
	a. Number of staircases					
	 Upper floors 	6 Provided NA NA 1.5 mtr & 117cm, 121cm, 12 1.25 mtr 149cm, 123cm, 148cm		Provided	MR NA	
	Basements			NA		
	b. Width of staircases					
	• Upper floors			ócm,	MR (Being old	
	 Basements 	NA	NA			case) NA
	c. Protection of exits					INA
	• Fire check door			NA	NA	
	• Pressurization	NA		NA	NA	
in anticipo actual constituents	d. No of continuous staircase to terrace	NA		NA	NA	
	e. Width Of Corridor f. Door Size	NA		NA	NA	
direction in the control of	f. Door Size	Two Exit		2x111cm		(Old case)

Fire check door Sealing of electrical	NA	NA	NA	
	NIA			
shafts	NA	NA	NA	
Fire Rating of shaft door	NA	NA	NA .	
Water Curtain	NA	NA	NA	
	NA	NA	NA	
	NA	NA	NA	
Upper floors	12 a/c per hour	Provided	MR	
Fire Extinguishers	P			
 Total numbers 			MR	
• Types			MR	
IS marking	ISI marked	Provided	MR	
First – Aid Hose Reels				
Total numbers on each floor	1	Provided	MR	
	30 m	Provided	MR	
	5 mm	Provided	MR	
		Provided	MR	
• 1			MR	
 Location of Repeater 	NA	NA	NA	
Alternate source of	Required	Provided	MR	
Hooters' Location	Required	Provided	MR	
MOEFA	Required	Provided	MR	
Public Address System	NA	Provided	NA	
Automatic Sprinkler System				
	NA	NA	NA	
	Required	Provided	MR	
 Sprinkler above false 	Required	Provided	MR	
	the mall			
Size of riser/down-	150 mm	Provided	MR	
Number of hydrants per	Required	Provided	MR	
Hose Box	Required	Provided	MR	
Yard Hydrants				
Total number of hydrants	NA	NA	NA	
Hose Box	NA	NA	NA	
	Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarm Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System Automatic Sprinkler System Basements Upper Floor Sprinkler above false ceiling Internal Hydrants: Common witl Size of riser/downcomer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants	Smoke managements System Basements Upper floors Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Required MOEFA Required MOEFA Required Basements Upper Floor Sprinkler System Basements Upper Floor Sprinkler above false ceiling Internal Hydrants: Common with the mall Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants	Smoke managements System Basements Upper floors Total numbers on each floor Length of hose reel hose Nozzle diameter Total numbers on each floor Length of hose reel hose Nozzle diameter Total numbers on each floor Length of hose reel hose Nozzle diameter Total numbers on each floor Length of hose reel hose Nozzle diameter Total numbers on each floor Length of hose reel hose Nozzle diameter Total number of hydrants	

13	B. Pumping Arrangements: Com	non with the ma	11			
	Ground Level	with the ma				
	 Discharge of main pum 	p NA	2850 lpm	NIA	_	
	> Head of main pump	NA	60 m	NA		
Number of main pu			1	NA		
	Jockey pump out put	NA	180 lpm	NA		
	Jockey pump head	NA	60 m	NA		
	Standby Pump out put	NA		NA		
	Standby Pump Head	NA	2850 lpm 60 m	NA		
	Auto Staring/Manual	NA		NA		
	stopping	INA	Required	NA		
	Pump House Access	NA	D 1	77.1		
	 Terrace level 	IVA	Required	NA		
	Discharge of pump	900 lpm	TN			
		900 lpm	The capacities of Pumps		MR	
			provided at GF are at			
	Head of the pump	40 m	higher side			
	Power supply		Do		MR	
dissert	Auto starting of pump	Required	Do		MR	
14.		Required	Do	• • •	MR	
1	Captive water Storage for fire fig	gnting: Common				
	 Under ground tank capacity 	NA	1,00,000	NA		
	> Draw off connection	27.4	litres			
	Fire service inlet	NA	Provided	NA		
	Access to tank	Required	Provided	MR		
		NA	Provided	NA		
1	 Overhead Tank capacity 	10, 000 litres	30, 000	MR		
			Litres			
15	Evit Ciana		Provided			
16.	Exit Signage Provision of Lifts	Required	Provided	MR		
10.		1		-		
	1 1005 at 12 at 1011 Of Lift	NA	NA	NA		
	Shaft		*			
	Pressurization of lift	NA	NA	NA		
	lobby		9			
	Communication in lift	NA	NA	NA		
	Car		-			
	Fireman's Grounding	NA	NA '	NA		
	Switch					
	Lift Signage	NA	NA	NA		
7.	Standby power supply	Daguinad				
8.	Refuge Area	Required	Provided	MR		
	Total area	NIA				
	Location	NA	NA	NA		
	The state of the s	NA	NA	NA	1	
9			**			
9.	Fire control room	214				
9.	Detector system panel	NA	NA	NA		
9.	Detector system panelFlow Switch Panel	NA	NA	NA NA		
9.	 Detector system panel Flow Switch Panel PA System Panel 	NA NA				
9.	 Detector system panel Flow Switch Panel PA System Panel Battery backup 	NA	NA	NA		

20.	Special Fire Protection Systems for Protection of special Risks,	NA	NA	NA
	The fire protection system found functional at the time of instance of the deemed confire safety as required under F6/DFS/MS/EH/2015/271 dated a Service Rules 2010 is recommend. Signature of the Inspecting Office Name Designation Along the fire protection system found in the time of instance of the deemed confire safety as required under F6/DFS/MS/EH/2015/271 dated and the fire protection system for the fire protection system found in the time of instance of the deemed confirmation and the fire protection system found in the fire protection system found in the fire protection system for the fire protection for t	pection. Inpliance of minimum the rules the 26-02-2015 renewated.	m standards on NOC issued al under rule 3	n fire prevention and d vide letter no.
	Designation HW (w) P	I	Designation	
	Dopte fruitis à	\$14/108/		
	DISTO (2)	28/4/1		
	Cho west Stall	Leh Syn	s Da	uterf
	00 M			
	Spoken, rev	ized Wf		₩ N :
	CF3/602 S-1041	17		Toly