GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 934

Dated: 75/18

FIRE SAFETY CERTIFICATE

Certified that the Hotel New City Palace located at 726, Motar Market, Jama Masjid, Delhi-06 comprised of Ground + Mezzanine + 03 Upper floors, Ground floor (Commercial use), 1st floor (Post Office + staff room), 2nd floor (10 guest rooms + reception + office), 3rd floor (10 guest rooms) and terrace (01 room sealed), total 20guest rooms owned/occupied by Hotel New City Palace was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/579 dated 21/04/15. The premises was re-inspected by the officer concerned of this department on 08/04/18 in the presence of Mr. Sayed Azmat Ali (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- by to:
 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1575/Addl. C.P/Lic. (H) dated 20/03/2018.
- 2. The Manager,

Hotel New City Palace at 726, Motar Market, Jama Masjid, Delhi-06.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Hotel New City Palace at 726, Motar Market,

Jama Masjid, Delhi-06.

2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 20 Guest rooms) Ground floor (Commercial use), 1st floor (Post Office + staff room), 2nd floor (10 guest rooms + reception + office), 3rd floor (10 guest rooms) and terrace (01 room sealed)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/NDZ/579 dated

24/04/15. 5. Fire safety directives No.-N/A

6. Date of inspection:-08/04/18

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Manoj Kumar Sharma (ADO/CC)

Mr. Sayed Azmat Ali (Owner)

Old

1575/Addl. C.P/Lic. (H) dated 20/03/2018.

S.No.	Minimum Standards on fire	Requirement/		Old Case	
	Prevention and fire safety U/R 33	Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	12 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Ar	rangement of l	Exits	14/74	
	A. Number of staircases		2		
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase			1071	
	1. Upper floors	0.80 mtr.	0.98 mtr.	MR	
,	2. Basements	N/A	N/A	N/A	
	C. Protection of exits	×			
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	01	01	MR	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	0.80 mtr.	0.80 mtr.	MR	
•	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
	Smoke Management System				
-	1) Basements	30 ACPH	N/A	N/A	
-	2) Upper floors	12 ACPH	N/A	N/A	

_	Fire Extinguishers			
5.	1) Total numbers	08 Nos.	08 Nos.	MR
		ABC & CO2	ABC & CO2	MR
	2) Types 3) ISI marking	Required	Provided	MR
	3) 1SI marking	required		
6.	First-Aid Hose Reel 1) Total number of eachfloor	01	2 nd & 3 rd floor	MR
	1) Total number of eachitoor	30 mtr.	30 mtr.	MR
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter Automatic Fire Detection &			
7.		N/A	N/A	N/A
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	COLUMN TO THE PARTY OF THE PART	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	riovided	IVIIX
10.	Automatic Sprinkler System	>1/A	N/A	N/A
	1) Basement	N/A		N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	1 1/ / /
	ceiling			
11.	Internal Hydrants	1	> 1/A	N/A
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	IN/A
	floor		21/4	N/A
	3) Hose box	N/A	N/A	IN/A
12.	Yard Hydrants	N/A		
	1) Total number of hydrants	N/A	N/A	
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			27/4
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum	p N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu	it N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manua		N/A	N/A
	stopping			
	2) Terrace level		i	
	a) Discharge of pump	240 LPM	240 LPM	MR
	b) Head of pump	35 mtr.	35 mtr.	MR
	1	Required	Provided	MR
		A.	Provided	MR
	d) Auto starting of pum	P		
		1		

4.	Captive Water Storage for F	ire righting	N/A	N/A
	1) Under ground tank	N/A	IN/A	18/73
-	capacity	DI/A	N/A	N/A
	a) Draw-off connection	N/A		N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A 2500 ltr.	N/A
	d) Over head tank	2500 ltr.	2500 Itr.	IN/A
	capacity	D : 1	Provided	MR
15.	Exit Signage.	Required	Provided	IVIIX
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift- lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided(DG set 4KVA)	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/579 dated 21/04/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

5-24/ch/m Dero (NDZ) / 16/4, 14/5.

CF. M. Sall FTM.

13/4.