GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 892

Dated:03/05/18

FIRE SAFETY CERTIFICATE

Certified that the Al-Haseeb Guest House located at 384, Bazar Matia Mahal, Jama Masjid, Delhi comprised of Ground + 03 Upper floors, Ground floor (Commercial use), 1st floor (02 guest rooms + Reception), 2nd floor (02 guest rooms), 3rd floor (02 guest rooms), total 06 guest rooms owned/occupied by Al-Haseeb Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/578 dated 21/04/15. The premises was re-inspected by the officer concerned of this department on 14/04/18 in the presence of Mr. Md. Zaheer (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 1st floor - 02 guest rooms + Reception, 2nd floor 02 guest rooms, 3rd floor 02 guest rooms, total 06 guest rooms only with effect from 43 45 - 42 - --- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -03-05-118---at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

9

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1644/Addl.C.P/Lic.(H) dated 37/03/18.
- 2. The Manager,

Al-Haseeb Guest House at 384, Bazar Matia Mahal, Jama Masjid, Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION	REPORT
II OI LOIT	A CADA

Al-Haseeb Guest House at 384, Bazar 1. Name & address of the building

Matia Mahal, Jama Masjid, Delhi

Residential, Sub Division-A-1 2. Type of occupancy:-

Ground + 03 Upper floors (total 06 guest rooms)
Ground floor (Commercial use), 1st floor (02 guest rooms + Reception), 2nd floor (02 guest rooms), 3rd floor

(02 guest rooms).

3. Type of case:-

4. Details of previous FSC:-

Renewal No. F6/DFS/MS/GH/2015/NDZ/578 dated

21/04/15.

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

N/A 14/04/18

Sh. Manoj Kumar Sharma (ADO/CC)

Mr. Md. Zaheer (Manager)

Old

1644/Addl.C.P/Lic.(H) dated 37/03/18.

10.	Applicant's letter 140.			Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	8.0 mtr. (approx)	MR	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2	Number, Width Type & Arra	angement of Ex	its		
2.	A. Number of staircases	8		•	
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	0.84 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace			27/4	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	01 mtr.	01 mtr.	MR	
3.	Compartmentation				
-	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
-10	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers			MD	
	1) Total numbers	06 Nos.	06 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	

1) 10001	Required	Provided	
1) Total number of eachfloor			
1) 10001	N/A	N/A	N/A
	N/A	N/A	N/A
-)8	N/A	N/A	N/A
Automatic Fire Detection & A			
	N/A	N/A	N/A
	AND STATE OF THE PARTY OF THE P		N/A
			N/A
			N/A
			N/A
/			N/A
			N/A
	N/A	IN/A	IN/ A
	21/4	DI/A	NI/A
,			N/A
			N/A
2 -	N/A	N/A	N/A
	27/4	27/4	D.T./ A
			N/A
	N/A	N/A	N/A
		2.7/1	77/4
	N/A	N/A	N/A
			N/A
1	N/A	N/A	N/A
Pumping Arrangement			
			N/A
a) Discharge of main	N/A	N/A	N/A
pump			
b) Head of main pump	N/A	N/A	N/A
c) Number of main pump	N/A	N/A	N/A
d) Jockey pump out put	N/A	N/A	N/A
	N/A	N/A	N/A
f) Stand by pump output	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
		•	
	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
		N/A	N/A
Cantive Water Storage for F			
		N/A	N/A
a) Draw-off connection	N/A	N/A	N/A
			N/A
	a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System N/A Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box N/A Yard Hydrants 1) Total number of hydrants 1) Ground level A) Discharge of main pump b) Head of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump N/A Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A	2) Location of main panel N/A N/A 3) Location of repeater panel N/A N/A 4) Alternate source of power N/A N/A 5) Hooter's Location N/A N/A MOEFA N/A N/A Public Address System N/A N/A Automatic Sprinkler System 1) Basement N/A N/A 2) Upper floors N/A N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A N/A 2) Number of hydrants per floor 3) Hose box N/A N/A Yard Hydrants 1) Total number of hydrants N/A N/A 2) Hose box N/A N/A Pumping Arrangement 1) Ground level N/A N/A a) Discharge of main pump N/A N/A c) Number of main pump N/A N/A d) Jockey pump head N/A N/A f) Stand by pump head N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump N/A N/A d) Jouer supply N/A N/A c) Power supply N/A N/A d) Auto starting of pump N/A N/A Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A N/A N/A N/A N/A N/A N/A

m

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	N/A	N/A	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any:	em for Protect	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. safety F6/DFS/MS/GH/2015/NDZ/578 dated 21/04/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ M.

CF. NPL

CF. M. SCELL FTM.

1/315. CF.D. M. SCELL 14914.

FTM.

FTM.

FTM.

FTM.

FTM.

FTM.

FTM.

FTM.