GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 9 6 2

FIRE SAFETY CERTIFICATE

Issued on 9/5/8 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Dated: 9/5/18

Copy to:-

- 1. Sh. Kuldeep Sobti (Owner), M/s. Hotel Akshay Palace, 26B, Pusa Road, Karol Bagh, New Delhi- 110005.
- 2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

: M/s. Hotel Akshay Palace 26B, Pusa Road, Karol Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2014/SZ/1462 dated 25.11.2014.

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 23.04.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Sh. Sallumudin, manager

9. Year of Construction

: 1988

10. Applicant's letter No.

: Form "J" dated 01.03.2018

The said guest house is comprised of basement, ground, mezzanine plus three upper floors.

S.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 25.11.2014	Provided at site	Remarks MR/NMR
	Access to building		Provided	MD
1	Road width	06 mts		MR
		4.5 mts	Directly accessible	MR
	Gate width Width of internal road	N/A	N/A	N/A
		t of Exits		, , , , , , , , , , , , , , , , , , ,
2	Number, Width, Type & Arrangement	-	- *	- 1
	a. Number of staircases	02	02	MR
	• Upper Floors	Old case	02	MR being old case
157	Basements	Old case	-	-
	b. Width of staircases	-	1.25 mts,1.0 mts	MR being old case
	Upper Floors	1.25 mts	1.0 mts each	MR being old case
	Basements	1.25 mts	-	-
	c. Protection of exits	-	NT/A	N/A
	Fire check door	N/A	N/A	N/A
	 Pressurization 	N/A	N/A	MR
	e. No. of continuous staircases to terrace	01	01 1.30 mts	MR
	g. Width of Corridor	Old case	0.85 mts	MR being old case
	h. Door Size	Old case	0.63 1113	
3	Compartmentation.		70	N/A
	Fire check door	N/A	N/A	IN/A
	Sealing of electrical shafts	N/A	Sealed	
	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	• Fire Dampers	N/A	N/A	N/A
		11/12		
4		30 a/c per hou	Exhaust fan provided	MR
1	Basements	12 a/c per hou		
	Upper floors	12 a/c per not	Natural Ventilation	1711

5	Fire Extinguishers							
	Total numbers	15	Provided	MR				
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6	First-Aid Hose Reels.							
,	Total numbers on each floor	01	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7 Automatic fire detection and alarming system.								
	Type of detectors	N/A	N/A	N/A				
	 Location of Main Panel 	N/A	N/A	N/A				
	Location of Repeater Panel	N/A	N/A	N/A				
	Alternate source of power	Required	D.G. set 62 KVA	MR				
	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
	Basement	Required	Provided	MR				
	Upper Floor	N/A	N/A	N/A				
	Sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants	2						
11	Size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
12	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.							
75	Ground Level							
	Discharge of main Pump	N/A	N/A	N/A				
	Head of Main pump	N/A	N/A	N/A				
	Number of main pumps	N/A	N/A	N/A				
	Jockey Pump out put	N/A	N/A	N/A				
	> Jockey pump head	N/A	N/A	N/A				
	Standby Pump out put	N/A	N/A	N/A				
	Standby Pump Head	N/A	N/A	N/A				
	Auto Starting/ Manual stoppPump House Access	N/A	N/A	N/A				
	> Pump House Access	N/A	N/A	N/A				

A	2							
DE		Head of the pump	30 mts	Provided	MR			
dr.		Power Supply	Required	Provided	MR			
0		Auto Starting of pump	Required	Provided	MR			
14	Captiv	ve Water Storage for fire fighting	5.					
	•	Underground tank capacity	N/A	N/A	N/A			
	>	Draw-off connection	N/A	N/A	N/A			
	>	Fire service inlet	N/A	N/A	N/A			
	>	Access to tank	N/A	N/A	N/A			
	•	Overhead Tank capacity	Old case	5000 lts	MR, Old case			
15	Exit S	ignage.	Required	Provided	MR			
16		sion of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	Required	Provided	MR			
		Fireman's Grounding Switch	N/A	N/A	Old lift			
	•	Lift Signage	Required	Provided	MR			
17	Stand	by power supply	Required	Provided	MR			
18	Refuge Area.							
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19	Fire Control Room							
		Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Battery backup	Required	Provided	MR			
		Building Floor Plans	N/A	N/A	N/A			
20	Speci	al Fire Protection Systems for	N/A	N/A	N/A			
	Prote	ction of special Risks, if any:						

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/1462 dated 25.11.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.



Pry 14/2018