GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. p6/208/ars/school (2018/w2/98)

Dated: 10/5 /2018

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**,

Issued on 10/5/18 at New Delhi by

Chief Fire Officer Ph: 011-23414250

Copy to:

- 1. The Principal, Govt. Girls Middle School, Sector-24, Rohini, Delhi-110085
- 2. The Director of Education, Old Secretariat, Delhi

INSPECTION REPORT

1. Name & address of the building: Govt. Girls Middle School, Sector-24, Rohini, Delhi-110085

2. Type of Occupancy

: Education

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/School/2015/WZ/138 dated 30/01/2015

5. Fire Safety directives letter No

: Director of Education dated 01/03/2011

(G+1)

6. Date of inspection

: 27/04/2018

7. Name of the Inspecting Officers

: ADO (RN)

8. Name and designation of officers

from the building side

: Sh. Vedpal (Principal)

9. Year of Construction

: 2014

10. Applicant's letter No.

: GGMS/S-24/R/407 dated 05/04/2018

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	DOE Requirement	Provided at site	Remarks MR/NMR
	Access to building			
	Road width	06 mtr	Provided	M/R
	Gate width	06 mtr	Provided	M/R
	Width of internal road	N.A.	N.A.	N.A.
	Number, Width, Type & Arrangement of	of Exits		
	a. Number of staircases			w 8
	Upper Floors	01	02	M/R
	Basements	N.A.	N.A.	N.A.
	b. Width of staircases			4
	Upper Floors	1.5 mtr	1.40 mtr each	M/R
	• Basements	N.A.	N.A.	N.A.
	c. Protection of exits			
	Fire check door	N.A.	N.A.	N.A.
	• Pressurization	N.A.	N.A.	N.A.
	d. No. of continuous staircases to terrace	N.A.	N.A.	N.A.
	e. Width of Corridor	N.A.	N.A.	N.A.
	f. Door Size	1 mtr	1.10 mtr Double door	M/R

3	Compartmentation		NT 4	NT A		
	• Fire check door	N.A.	N.A.	N.A.		
	 Sealing of electrical shafts 	N.A.	N.A.	N.A.		
	• Fire Rating of shaft door	N.A.	N.A.	N.A.		
	Water Curtain	N.A.	N.A.	N.A.		
	• Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	• Basements	30 a/c per hour	N.A.	N.A.		
	 Upper floors 	12 a/c per hour	N.A.	N.A.		
5	Fire Extinguishers					
	Total numbers	07	09	M.R		
	• Types	ISI marked	ABC	M.R		
	IS marking	131 marked	Yes	M.R		
6	First-Aid Hose Reels.					
	Total numbers on each floor		N.A.	N.A.		
	 Length of hose reel hose 	30 m	N.A.	N.A.		
	Nozzle diameter	5 mm	N.A.	N.A.		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	N.A.	N.A.		
	 Location of Main Panel 	N.A.	N.A.	N.A.		
	 Location of Repeater Panel 	N.A.	N.A.	N.A.		
	Alternate source of power	N.A.	N.A.	N.A.		
	Hooters' Location	N.A.	N.A.	N.A.		
8	MOEFA	N.A.	N.A.	N.A.		
9	Public Address System.	N.A.	N.A.	N.A.		
10	Automatic Sprinkler System.					
	Basement	N.A.	N.A.	N.A.		
	Upper Floor	N.A.	N.A.	N.A.		
	 Sprinkler above false ceiling 	N.A.	N.A.	N.A.		
11	Internal Hydrants					
	Size of riser/down-comer	N.A.	N.A.	N.A.		
	Number of hydrants per floor	N.A.	N.A.	N.A.		
	Hose Box	N.A.	N.A.	N.A.		

	And the second s			
12	Yard Hydrants.			\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Ne d	Total number of hydrants	N.A.	N.A.	N.A.
	Hose Box	N.A.	N.A.	N.A.
13	Pumping Arrangements.		*	
	Ground Level			
	Discharge of main Pump	N.A.	N.A.	N.A.
	Head of Main pump	N.A.	N.A.	N.A.
	Number of main pumps	N.A.	N.A.	N.A.
	Jockey Pump out put	N.A.	N.A.	N.A.
	Jockey pump head	N.A.	N.A.	N.A.
	> Standby Pump out put	N.A.	N.A.	N.A.
	Standby Pump Head	N.A.	N.A.	N.A.
	> Auto Starting / Manual	N.A.	N.A.	N.A.
	stopping	N.A.	N.A.	N.A.
	> Pump House Access			
	Terrace level	N.A.	N.A.	N.A.
	Discharge of pumpHead of the pump	N.A.	N.A.	N.A.
		N.A.	N.A.	N.A.
	Power SupplyAuto Starting of pump	N.A.	N.A.	N.A.
			11.7 %	11.74.
14	 Captive Water Storage for fire fighting Underground tank capacity 	N.A.	N.A.	N.A.
	Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A.
			<u> </u>	
	Overhead Tank capacity	N.A.	N.A.	N.A.
15	Exit Signage.	N.A.	N.A.	N.A.
16	Provision of Lifts. • Pressurization of Lift Shaft	N.A.	N.A.	N.A.
	 Pressurization of Lift Shaft Pressurization of Lift lobby 	N.A.	N.A.	N.A.
	Communication In lift Car	N.A.	N.A.	N.A.
	Fireman's Grounding Switch	N.A.	N.A.	N.A.
	• Lift Signage	N.A.	N.A.	N.A.

17	Standby power supply	N.A.	N.A.	N.A.
18	Refuge Area.			
	> Total Area	N.A.	N.A.	N.A.
	> Location	N.A.	N.A.	N.A.
19	Fire Control Room			
	Detector System Panel	N.A.	N.A.	N.A.
	• Flow Switch Panel	N.A.	N.A.	N.A.
	PA System Panel	N.A.	N.A.	N.A.
	Batter backup	N.A.	N.A.	N.A.
	Building Floor Plans	N.A.	N.A.	N.A.
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.A.	N.A.	N.A.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/School/2015/WZ/138 dated 30/01/2015 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Rajesh Kumar

Designation: Asstt. Divisional Officer

Of west 15/18

Any RN

As approved,

for PI

ettel el pr

9/5

142/9/5/14

MM