## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/ Dfs/ans/school(2018/M02/950

Dated: 8/5/18

## FIRE SAFETY CERTIFICATE

(Vipin Kental)
Chief Fire Officer

To,

The Principal,
Govt Girls Sr. Sec School, Lalita Park, (Ramesh Park) Delhi-92

Copy to:-

The Joint Director of Education, (Land & Estate)
 Directorate of Education, Lucknow Road, Delhi-54.

1. Name & address of the building : Govt Girls Sr. Sec School at Lalita Park, (Ramesh

Park) Delhi-92.

2. Building is comprised of

: G+1 Upper floor

Type of Occupancy

: Educational

4. Type of Case

: Renewal

5. Details of Previous FSC

: F.6/DFS/MS/School/2014/NDZ/1327 Dated-

22/10/14

6. Fire Safety Circular No.

: F.16/Estate/CC/FS/2011/3298 to 3398dt

01.03.2011

7. Date of Inspection

: 11/04/18

8. Name of the Inspecting officers: ADO R.K.Yadav

9. Name and designation of

Officer from the building side

: Mrs Anuradha Saxena (Principal)

10. Year of Construction

: 1985 & 2013

11. Applicant's letter No

: G.G.L.P./1137 Dated 02/03/18

	N 0	Minimum Standards on fire prevention and fire safety U/R33	Requirement	Provided at Site	Remarks			
	1	Access to building						
		Road width	06 m	06 m	MR			
		Gate width	4.5 m	5.2 m	MR			
		<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A			
	2	Number, Width, Type and Arrangement of Exits						
		a. Number of Staircases						
		Upper Floor	07 no.	07 no.	MR			
		Basement	N/A	N/A	N/A			
		B. Width of Staircases	107	14//	19/7			
		Upper Floor	1.5 m	1.5 m each	MR			
		Basement	N/A	N/A	N/A			
		c. Protection of exits						
		Fire check door	N/A	N/A	N/A			
		Pressurization	N/A	N/A	N/A			
		d. No. of continuous staircases to terrace	N/A	N/A	N/A			
		e. Width of Corridor	1.5 M	1.5 M	MR			
		f. Door Size	1.0 M	1.0 M	MR			
3	3	Compartmentation.						
		Fire check door	N/A	N/A	N/A			
		<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A			
		<ul> <li>Fire rating of shaft door</li> </ul>	N/A	N/A	N/A			
		Water curtain	™ N/A	N/A	N/A			
		<ul> <li>Fire Dampers</li> </ul>	N/A	N/A	N/A			
4	-	Smoke Management System.						
		Basement	N/A	N/A	N/A			
		Upper floor  Fire Extinguishers	N/A	N/A	N/A			
5		/ x2 B						
		Total numbers	15 Nos.	15 Nos.	MR			
-	-	• Types	ABC & Co2	ABC & Co2	MR			
		ISI marking	ISI marked	ISI marked	MR			

6	First-aid-Hose Reels.							
	Total numbers of each floor	N/A	N/A	N/A				
	<ul> <li>Length of hose reel hose</li> </ul>	N/A	N/A	N/A				
	Nozzle diameter	2 200						
		N/A	N/A	N/A				
7	Automatic fire detection and alarming system.							
4.~~	Type of detectors	N/A	N/A	N/A				
	Location of main panel	N/A	N/A	N/A				
	<ul> <li>Location of repeater panel</li> </ul>	N/A	N/A	N/A				
	Alternate source of power	N/A	N/A	N/A				
	Hooter's location	N/A	N/A	N/A				
8	MOEFA	N/A	Provided	MR				
9	Public address System.	N/A	Provided	MR				
10	Automatic Sprinkler System.		. 1011404	1011				
	Basement	N/A	N/A	N/A				
r	upper floor	N/A	N/A	N/A				
	sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants		1					
	size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
/	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
( *	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.	N/A	N/A	N/A				
· ·	Ground Level		1	1 417 1				
	Discharge of main Pump	N/A	N/A	N/A				
<u></u>	Head of Main Pump	N/A	N/A	N/A				
20 1. 15 1.4 10 1.4	Number of main pumps	N/A	N/A	N/A				
	Jockey pump out put	N/A	N/A	N/A				
	Jockey pump head	N/A	N/A	N/A				
	Standby pump out put	N/A	N/A	N/A				
	Standby pump Head	N/A	N/A	N/A				
12	Auto Starting /Manual	N/A	N/A	N/A				
	stopping							
	> Pump House Access	N/A	N/A	N/A				
12.	Terrace Level     Discharge of numb	N1/A	NI/A	K1/A				
	<ul><li>Discharge of pump</li><li>Head of the Pump</li></ul>	N/A	N/A	N/A				
	<ul><li>Head of the Pump</li><li>Power supply</li></ul>	N/A N/A	N/A N/A	N/A				
	F Tower Supply	IN/A	IN/A	N/A				
	Auto Starting of pump	N/A	N/A	N/A				
1	Captive Water Storage for Fire							
	Fighting.							
	Underground tank capacity	N/A	N/A	N/A				
	> Draw-off connection	N/A	N/A	N/A				
	Fire service inlet	N/A	N/A	N/A				
	> Access to tank	N/A	N/A	N/A				
-	Overhead Tank capacity      This Company	N/A	N/A	N/A				
5	Exit Signage.	N/A	N/A	N/A				

	61.66	N/A	N/A	N/A
16	Provision of Lifts.	N/A	N/A	N/A
	Pressurization of Lift Shaft	N/A	N/A	N/A
	<ul> <li>Pressurization of Lift lobby</li> </ul>	and the same of th	N/A	N/A
	<ul> <li>Communication in lift car</li> </ul>	N/A	N/A	N/A
	<ul> <li>Firemen's grounding switch</li> </ul>	N/A		N/A
	Lift Signage	N/A	N/A	
4 -7	Standby power supply	N/A	N/A	N/A
17		N/A	N/A	N/A
18	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
	<ul> <li>Detector system panel</li> </ul>		N/A	N/A
	<ul> <li>Flow switch panel</li> </ul>	N/A		N/A
	PA system panel	N/A	N/A	
1		N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans		N/A	N/A
20	Special Fire Protection systems for	N/A	14//	
	protection of special Risks, if any:	1 11 11	ro tostad/chec	ked and found

The fire protection systems provided in the building were tested/checked and found

functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The FSC issued vide letter no. F.6/DFS/MS/School/2014/NDZ/1327 Dated-22/10/14 renew under the circular no. F.16/Estate/CC/Fire safety/2011/3298 to 3398 dated 01.03.11 is recommended.

Signature of the InspectingOfficer

Name:-R.K.Yadav Designation:-ADO (LN)

DO(ED)

CFP- M. SCELL METY.

On, FT Letter is put up for sugar, pl.

msour le