GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2018/ MD2 | 1012

Dated : 10/5/18-

FIRE SAFETY CERTIFICATE

Certified that the HYBRID (A Unit of Hybrid Hospitally LLP) located at 54, Gr. Floor, Janpath, Connaught Place, New Delhi comprises of Two Block – A- Basement + Ground + 03 Upper floor and Block-B Ground + 1st floor, Restaurant running at B-Block, Ground floor only owned/occupied by HYBRID (A Unit of Hybrid Hospitally LLP) was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/263 dated 26/02/15. The premises was re-inspected by the officer concerned of this department on 24/04/18 in the presence of Mr. Rajesh (General Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building, Group-D of Sub-Division D-5 Restaurant at Ground floor (B-Block) only with effect from by Group-D of Sub-Division D-5 Restaurant at Ground floor (B-Block) under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --{--}-{-----at New Delhi by.

(Vipin Kental)
Chief Fire officer
Delhi Fire Service

of c

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

2. The Manager, HYBRID (A Unit of

HYBRID (A Unit of Hybrid Hospitally LLP),

54, Gr. Floor, Janpath, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1-13

	INS	SPEC	TION	REP	ORT
--	-----	------	------	-----	-----

1. Name & address of the building HYBRID (A Unit of Hybrid Hospitally LLP)

54, Gr. Floor, Janpath, Connaught Place, New Delhi

2. Type of occupancy:- Assembly Building Group-D

Two Block – A- Basement + Ground + 03 Upper floor and Block-B Ground + 1st floor, Restaurant running at

B-Block, Ground floor only

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/EH/2015/NDZ/263 dated

22/02/15

5. Fire safety directives No.- N/A

6. Date of inspection:- 24/04/18

7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

from the building side:- Mr. Rajesh (General Manager)

9. Year of construction:- Old Heritage Bldg.

10. Applicant's letter No:- Nil diary dated 19/02/2018

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	09 mtr	12 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of Ex	kits			
	A. Number of staircases					
	1. Upper floors	02 No.	04 No.	MR		
	2. Basements	01	01	MR		
	B. Width of staircase		7			
	1. Upper floors	1.5 mtr. & 1.0 mtr.	1.52 mtr., 1.20 mtr., 1.0 mtr. & 0.80 mtr. 0.90 mtr.	MR		
	2. Basements	01 mtr.	01 mtr.	MR		
	C. Protection of exits	N/A	N/A	N/A		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	03	MR		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	02 mtr.	02 mtr. & 1.8 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
×	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	12 Nos.	15 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		

6.	First-Aid Hose Reel						
0.	1) Total number of eachfloor 02			02		M	
	2) Length of hose reel hose	30 n	ntr.	30	mtr.	M	
	3) Nozzle diameter	05 r	nm	05	mm	M	R
7.	Automatic Fire Detection &	Aları	ming Syste	em		,	
1.	1) Type of detectors	Req	uired	Pro	ovided	M	
	2) Location of main panel	N/A		N/A	4	N	
	3) Location of repeater panel	N/A	1	N/1	A	N	
	4) Alternate source of power	N/A	1	N/A	A		/A
	5) Hooter's Location	N/A	1	N/A	A	N.	/A
8.	MOEFA	N/A	1	N/A	A		/A
9.	Public Address System	N/A		N/	A	N	/A
2014	Automatic Sprinkler System						
10.	1) Basement	Red	quired	Pro	ovided	N	IR
	2) Ground floors	N/A		N/			/A
	3) Sprinkler above false	N/A		N/		N	/A
	ceiling			1,112		7	
11.	Internal Hydrants						
11.	1) Size of riser/down-comer	100) mm	10	00 mm	N	IR
	2) Number of hydrants per	02		02		N	IR
	floor						
	3) Hose box	02	02			MR	
12.	Yard Hydrants						
12.	1) Total number of hydrants	Cotal number of hydrants N/		N/A			I/A
	2) Hose box	N/	A	N	/A	N	I/A
13.	Pumping Arrangement				-		
15.	1) Ground level		,				
	a) Discharge of main		N/A	N/A	N/A		N/A
	pump						
	b) Head of main pum	р	N/A		N/A		N/A
	c) Number of main p	ump	N/A		N/A		N/A
	d) Jockey pump out p		N/A	artematical participation of the second	N/A		N/A
	e) Jockey pump head		N/A		N/A		N/A
-	f) Stand by pump ou		N/A		N/A		N/A
		Stand by pump head			N/A		N/A
	h) Auto starting/Man		N/A		N/A		N/A
	stopping						
	2) Terrace level				. 11		
	a) Discharge of pump		450 LPM		450, 280 L	PM	MR
	b) Head of pump		30 mtr. 30 mtr.			MR	
	c) Power supply		Required	1	Provided		MR
	d) Auto starting of p	ump	Required	d	Provided		MR
14.	Captive Water Storage for Fi		ire Fightin	ıg			
	Under ground tank		N/A		N/A		N/A
	capacity	capacity					7711
					N/A		N/A
<u>~</u>	b) Fire service inlet				N/A		N/A
	c) Access to tank		N/A		N/A		N/A
	d) Over head tank capacity		10,000 lt	r	10,000 ltr.		MR

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			1111
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	Provided	N/A
18.	Refuge Area	N/A	N/A	N/A
2	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any: ABC & Co2			MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2015/NDZ/263 dated 26/02/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma Designation :- ADO (CC)

Dy. CFO (NDZ)

M.