GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 1006

Dated :- 10/5/18

FIRE SAFETY CERTIFICATE

Certified that the Richmood Inn Guest House at 9597-9603, Desh Raj Bhatia Marg, Multani Dhanda, Pahar Ganj New Delhi comprised of Ground + 04 Upper floors, Ground floor (reception + 01 office), 1st floor (09 guest rooms), 2nd floor (10 guest rooms), 3rd floor (10 guest rooms), 4th floor (staff kitchen + D.G set), total 29 guest rooms owned/occupied by Richmood Inn Guest House was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/714 dated 11/05/15. The premise was re-inspected by the officer concerned of this department on 09/04/18 in the presence of Mr. Karan (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 29 guest rooms only with effect from - 10/15/1-5------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - (1) - (1) ---- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1491/Joint/C.P./Lic. (H) dated 16/03/18.
- 2. The Manager, Richmood Inn Guest House at 9597-9603, Desh Raj Bhatia Marg, Multani Dhanda, Pahar Ganj New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

N/22

	INICI	DECTION DEDC	DT			
1		PECTION REPO		0507 0602		
1.	Name & address of the building Richmood Inn Gurdt House at 9597-9603.					
	Desh Raj Bhatia Marg, Multani Dhanda, Pahar Ganj New Delhi. Gr. + 04 Upper floors (total 29 Guest rooms Ground floor (reception + 01 office), 1 st floor (09 guest rooms), 2 nd floor (10 guest rooms), 3 rd flo (10 guest rooms), 4 th floor (staff kitchen + D.G set)					
	. Type of case:-	Renewal				
4	. Details of previous NOC:-	No. F6/DF	S/MS/GH/2015/NI	DZ/714 dated		
		11/05/15.				
5.	Fire safety directives No	N/A				
	6. Date of inspection:- 09/04/18					
	Name of the inspecting officer		Kumar Sharma (Al	DO/CC)		
8.	8	•				
	the building side:-	Sh. Karan	(Manager)			
	Year of construction:-	2008				
10	. Applicant's letter No:-	1491/Addl. C.F	P/Lic.(H) dated 16/03	/18		
				Old Case		
.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
	Prevention and fire safety	Existing fire	12	MR/NMR		
	U/R 33	safety				
		arrangements				
•	Access to Building					
	1) Road width	N/A	09 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of Ex	kits			
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	1.25 mtr.	1.22 to 1.25	MR		
			Mtr.			
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits			1		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization					
	2. Flessurization	IN/A	N/A	I N/A		
		N/A 01	N/A 01	N/A MR		
	D. No. of continuous	01	N/A 01	MR		
	D. No. of continuous staircase to terrace	01	01	MR		
	D. No. of continuous staircase to terrace E. Width of corridor	01 N/A	01 N/A	MR N/A		
-	D. No. of continuous staircase to terrace E. Width of corridor F. Door size	01	01	MR		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation	01 N/A 01 mtr.	01 N/A 01 mtr.	MR N/A MR		
2	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door	N/A 01 mtr.	01 N/A 01 mtr.	MR N/A MR N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts	01 N/A 01 mtr. N/A N/A	01 N/A 01 mtr. N/A N/A	MR N/A MR N/A N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door	N/A 01 mtr. N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A	MR N/A MR N/A N/A N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain	N/A 01 mtr. N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A N/A N/A	MR N/A MR N/A N/A N/A N/A N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers	N/A 01 mtr. N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A	MR N/A MR N/A N/A N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers Smoke Management System	N/A 01 mtr. N/A N/A N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A N/A N/A N/A N/A	MR N/A MR N/A N/A N/A N/A N/A N/A		
	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers Smoke Management System 1) Basements	N/A 01 mtr. N/A N/A N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A N/A N/A N/A N/A	MR N/A MR N/A N/A N/A N/A N/A N/A		
•	D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers Smoke Management System	N/A 01 mtr. N/A N/A N/A N/A N/A N/A	N/A 01 mtr. N/A N/A N/A N/A N/A N/A N/A	MR N/A MR N/A N/A N/A N/A N/A N/A		

5.	Fire Extinguishers			
	1) Total numbers	08	08	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
_	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	27/4	220	
10	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	27/1	127/1	
	1) Total number of hydrants	N/A	N/A	N/A
12	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	27/4	27/	
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	NI/A
	c) Number of main pump	N/A N/A	N/A N/A	N/A
	d) Jockey pump out put	N/A N/A	N/A N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	IN/A	IN/A	N/A
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for Fi		TTOVIGEG	IVIN
17.	1) Under ground tank	N/A	N/A	N/A
	capacity	1 1/ 1/1	1 1 1 / / 1	1N/A
	capacity			

1 100

	a) Draw-off connection	N/A	N/A	N/A
_	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	25000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	NA		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/714 dated 11/05/2010 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DCFO/NDZ