GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ / 01

FIRE SAFETY CERTIFICATE

Certified that the Saya Dx. Guest House located at 2213, Chauna Mandi, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 guest rooms + reception + office), 1st floor to 3rd floor (07 guest rooms at each floor), 4th floor (03 guest rooms + 01 staff room + staff kitchen), total 25 guest rooms owned/occupied by Saya Dx. Guest House was granted **FSC** by this department No.F6/DFS/MS/GH/2015/NDZ/674 dated 01/05/15. The premise was re-inspected by the officer concerned of this department on 19/04/18 in the presence of Mr. Arun (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 25 guest of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 10-15-18---at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1644/Joint/C.P./Lic. (H) dated 03/04/18.
- The Manager,
 Saya Dx. Guest House at 2213, Chauna Mandi, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub-rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		PECTION REPO					
1.	Name & address of the building Saya Dx. Guest House at 2213, Chauna						
_	Mandi, Pahar Ganj, New Delhi						
2.	Type of occupancy:- Residential, Sub Division-A-1						
			er floors (total 25 Gu				
	Ground floor (01 guest rooms + reception + office), 1 st floor to 3 rd floor (07 guest rooms at each floor),						
		4 th floor (03 gu	est rooms + 01 staff room	n + staff kitchen			
	Type of case:-	Renewal					
4.	Details of previous FSC:- No. F6/DFS/MS/GH/2015/NDZ/674 dated						
		01/05/15.					
	Fire safety directives No	N/A					
	5. Date of inspection:- 19/04/18						
	Name of the inspecting officer		Kumar Sharma (A	DO/CC)			
	Name & designation of officer						
	the building side:-	Mr. Arun (Manager)				
	Year of construction:-	1990	M. AD 1 . 102	10.4.12.0.1.0			
10.	Applicant's letter No:-	1644/Joint C.P	P./Lic. (H) dated 03				
CNI	M:-:	Requirement/	D ' 1 - 1 - 4 - '4 -	Old Case			
S.No.	Minimum Standards on fire	Existing fire safety	Provided at site	Remarks			
	Prevention and fire safety U/R 33	arrangements		MR/NMR			
1.	Access to Building	-					
1.	1) Road width	N/A	09 mtr.	MR			
			100000 10000000000000000000000000000000				
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase	L		1.			
	1. Upper floors	0.80 mtr.	1.10 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits		*				
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	01	MR			
	staircase to terrace	27/					
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1.0 mtr.	1.0 mtr.	MR			
3.	Compartmentation	1					
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
	Smoke Management System						
4.	Smoke Management System						
4.	1) Basements	30 ACPH	N/A	N/A			
4.		30 ACPH 12 a/c per	N/A Natural	N/A MR			

5.	Fire Extinguishers	,			
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel	required	Tiovided	IVIIX	
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection &	Alarming Syst	om .	IVIK	
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A N/A	
	3) Location of repeater panel	N/A	N/A	N/A N/A	
	4) Alternate source of power	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A	
3.	MOEFA	N/A		N/A	
) <u>.</u>	Public Address System		N/A	N/A	
0.	Automatic Sprinkler System	Required	Provided	MR	
	1) Basement		27/4		
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling	N/A	N/A	N/A	
11.	Internal Hydrants				
1.	1) Size of riser/down-comer	N T/A	27/1		
		N/A	N/A	N/A	
	2) Number of hydrants per floor	N/A	N/A	N/A	
	3) Hose box	> T / A	27/1		
2.	,	N/A	N/A	N/A	
4.	Yard Hydrants				
	 Total number of hydrants Hose box 	N/A	N/A	N/A	
3.		N/A	N/A	N/A	
·	Pumping Arrangement				
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump		8		
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual stopping	N/A	N/A	N/A	
	2) Terrace level	8			
	a) Discharge of pump	450 LPM	450 LPM	MR	
	b) Head of pump	30 mtr.	30 mtr.	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump	Required	Provided	MR	

14.	Captive Water Storage for	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			IVIIC
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17,	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	m for Protect	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/674 dated 01/05/18 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

5-541cf-112-

Defo(No)