GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2018/ / いって

Dated :- 1-0/5/18-

FIRE SAFETY CERTIFICATE

Certified that the Zomozzat Restaurant located at 52 Janpath, Connaught Place, New Delhi comprises of Ground + 03 Upper floor, Restaurant running at Groung floor owned/occupied by Zomozzat Restaurant was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/1409 dated 14/11/14. The premises was re-inspected by the officer concerned of this department on 24/04/18 in the presence of Mr. Shailesh Kumar (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Business Building, Restaurant running at Ground floor only with effect from 10 for 10 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ----lof-s---at New Delhi by.

(Vipin Kental) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department. Palika Kendra, New Delhi.

2. The Manager,

Zomozzat Restaurant at 52 Janpath. Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

| | n IODE | COTION DEDOD | T | | | |
|---------------|--|-----------------------------------|-------------------------|-------------------|--|--|
| | | ECTION REPOR | | noth | | |
| 1. | Name & address of the building | | estaurant at 52 Jan | ipain, | | |
| | | Connaught Place, New Delhi | | | | |
| 2. | Type of occupancy:- | Assembly Bu | uilding Group-D | in a st Cr. Floor | | |
| | | | floors, restaurant runn | ing at Gr. Floor | | |
| | Type of case:- | Renewal | OH 2014 AND 7/14 | 00 datad | | |
| 4. | Details of previous FSC:- | | GH/2014/NDZ/14 | 09 dated | | |
| | | 14/11/14 | | | | |
| 5. | Fire safety directives No | N/A | | | | |
| | Date of inspection:- | 24/04/18 | | 0/00 | | |
| | Name of the inspecting officer: | - Sh. Manoj K | umar Sharma (AD | 0/00) | | |
| 8. | Name & designation of officer | 100 | | | | |
| | from the building side:- | | ailesh Kumar (Mar | iager) | | |
| 9. | Year of construction:- | Old Heritage | | | | |
| 10. | Applicant's letter No:- | | ed 05/04/2018 | | | |
| S.No. | Minimum Standards on fire | Requirement/ | Provided at site | Remarks | | |
| | Prevention and fire safety U/R 33 | Existing fire safety arrangements | | MR/NMR | | |
| | Agges to Ruilding | arrangements | | | | |
| . • | Access to Building | 00 | 16 mts | MR | | |
| | 1) Road width | 09 mtr | 16 mtr. | N/A | | |
| | 2) Gate width | N/A | N/A | | | |
| | 3) Width of internal road | N/A | N/A | N/A | | |
|) | Number, Width Type & Arra | angement of Ex | its | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | N/A | N/A | N/A | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | B. Width of staircase | | | | | |
| | 1. Upper floors | 1.5 mtr. | 1.30 mtr. | MR | | |
| | 1. Opper moors | | Existing | 27/1 | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | C. Protection of exits | N/A | N/A | N/A | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous | N/A | N/A | N/A | | |
| | staircase to terrace | | | N ₂ | | |
| | E. Width of corridor | N/A | N/A | N/A | | |
| | F. Door size | 02 mtr. | 02 mtr. | MR | | |
| 2 | | OZ III. | | | | |
| 3. | Compartmentation | NI/A | N/A | N/A | | |
| | 1) Fire check door | N/A | | N/A | | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A N/A | | |
| | 3) Fire rating of shaft door | N/A | N/A | | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| St. Committee | 5) Fire Dampers | N/A | N/A | N/A | | |
| 4. | Smoke Management System | | T = 24 | 1211 | | |
| | 1) Basements | 30 ACPH | N/A | N/A | | |
| | 2) Upper floors | 12 ACPH | Natural | MR | | |
| 5. | Fire Extinguishers | • | , | | | |
| | 1) Total numbers | 12 Nos. | 12 Nos. | MR | | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | | |
| | 3) ISI marking | Required | Provided | MR | | |
| | 0) 101 1111110 | 1 | | | | |
| 6 | First-Aid Hose Reel | | | | | |
| 6. | First-Aid Hose Reel 1) Total number of eachfloor | 02 | 02 | MR | | |

| | 3) Nozzle diameter | 05 | mm | 05 mm | | (D | |
|-----|------------------------------|--------------|------------|--------------|--|-----------|--|
| 7. | Automatic Fire Detection & | | | tom | IV | 1R | |
| | 1) Type of detectors | | equired | Provided | I N | 1R | |
| | | | : floor | Gr. floor | | 1R | |
| | | | A | N/A | | | |
| | 4) Alternate source of power | | quired | Provided | | N/A MR | |
| | 5) Hooter's Location | N/ | | N/A | | N/A | |
| 8. | MOEFA | | | Provided | 3 | | |
| 9. | Public Address System | Required N/A | | N/A | | MR N/A | |
| 10. | Automatic Sprinkler System | | Λ | IN/A | - | / A | |
| 101 | | | A | N/A | N | /A | |
| | 2) Ground floors | N/ | | Provided | | /A /A | |
| | 3) Sprinkler above false | N/ | | N/A | | /A /A | |
| | ceiling | 1 4/1 | 1 | IN/A | | /A | |
| 11. | Internal Hydrants | | | | | | |
| | 1) Size of riser/down-comer | Re | quired | Provided | M | R | |
| | 2) Number of hydrants per | | quired | Provided | | R | |
| | floor | 1 | Janoa | Tiovided | 17/1 | .10 | |
| | 3) Hose box | Red | quired | Provided | M | R | |
| 12. | Yard Hydrants | 1 100 | 1 | Tiorided | 141 | 11 | |
| | 1) Total number of hydrants | N/A | 4 | N/A | N | /A | |
| | 2) Hose box | N/A | | N/A | N | | |
| 13. | Pumping Arrangement | | | | 1 // | | |
| | 1) Ground level | | | | | | |
| | a) Discharge of main | | N/A | N/A | | N/A | |
| | pump | | | 1 1/2.2 | | 1 1/11 | |
| | b) Head of main pump | | N/A | N/A | | N/A | |
| | c) Number of main pump | | N/A | N/A | | N/A | |
| | d) Jockey pump out put | | N/A | N/A | - | N/A | |
| | e) Jockey pump head | | N/A | N/A | _ | N/A | |
| | f) Stand by pump outpu | | N/A | N/A | | N/A | |
| | g) Stand by pump head | | N/A | N/A | | N/A | |
| | h) Auto starting/Manua | | N/A | N/A | and the same of th | N/A | |
| | stopping | | | | - | A 1/ / B | |
| | 2) Terrace level | | | | | | |
| | a) Discharge of pump | | 450 LPM | 450, 180 LPN | 1 | MR | |
| | b) Head of pump | | 30 mtr. | 30 mtr. | - 1 | MR | |
| | c) Power supply | | Required | Provided | | MR | |
| | d) Auto starting of pum | р | Required | Provided | - 1 | MR | |
| 14. | Captive Water Storage for | | | | | | |
| | 1) Under ground tank | | J/A | N/A | | N/A | |
| | capacity | | | | | | |
| | a) Draw-off connection | | J/A | N/A | | N/A | |
| | b) Fire service inlet | | J/A | N/A | | N/A | |
| | | | I/A | N/A | - | N/A | |
| | d) Over head tank capacity | 1 | 0,000 ltr. | 10,000 ltr. | | MR | |
| 15. | Exit Signage. | R | equired | Provided | | MR | |
| 16. | Provision of Lifts. | | | | | | |
| | a) Pressurization of lift | N | I/A | N/A | | V/A | |
| | , | | | 1 1/1 1 | | 1/ [] | |

| | shaft | | | |
|-----|--|----------|----------|-----|
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| 1= | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| D | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syste Risk, if any: ABC & Co2 | MR | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/EH/2018/398 dated 30/01/2018 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2014/NDZ/1409 dated 11/04/14 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma Designation :- ADO (CC)

Dy. CFO (NDZ)

MOFO NOT