GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1642

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Taj Princess located at 15A/25, W.E.A, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus five upper floors, using basement as hall/storage, ground floor as reception, office, lobby & 01 guest room, first, second & third floor each having 08 guest rooms respectively, fourth floor having 05 rooms and 01 hall for personal use (total 25 guest rooms), fifth floor is sealed by the owner, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1055 dated 19.06.2015. The premises was re-inspected by the officer concerned of this department on 02/07/2018 in presence of Sh. Sandeep Bhat, general manager of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 16/7/18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on ______ at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- 1. Sh. Sunil Anand (owner), M/s. Hotel Taj Princess, 15A/25, W.E.A, Karol Bagh, New Delhi-110005.
- 2. The Additional C.P. (Lic.), Police Station Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

: M/s. Hotel Taj Princess, 15A/25, W.E.A, Karol Bagh, 1. Name & address of the building New Delhi- 110005.

2. Type of Occupancy : Lodging House

: Renewal 3. Type of Case

: F6/DFS/MS/GH/2015/SZ/1055 dated 19.06.2015 4. Details of previous NOC

5. Fire Safety directives letter No : Nil

6. Date of inspection : 02.07.2018

: M.K. Chattopadhyay, DO(South West) 7. Name of the Inspecting Officers

8. Name and designation of officers

: Sh. Sandeep Bhat, general manager from the building side

9. Year of Construction : 1998

: 3604/Addl. C.P/Lic (H) dated New Delhi the 25.05.2018 10. Applicant's letter No.

The said guest house is comprised of basement, ground plus five upper floors.

S. No.		Ainimum Standards on fire vention and fire safety U/R 33	Fire safety requirements as pel letter dt. 19.06.2015	Provided at site	Remarks MR/NMR		
1	Acces	Access to building					
	•	Road width	06 mts	Provided	MR		
	•	Gate width	Required	Directly accessible from the road	MR		
	•	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits						
	a. Nur	mber of staircases	-	-	-		
	•	Upper Floors	Old Case	01	MR being old case		
	•	Basements	Old Case	01	MR being old case		
	b. Wie	dth of staircases	-	-	-		
	•	Upper Floors	Old case	1.31 mts	MR being old case		
	•	Basements	Old case	1.42 mts each	MR being old case		
	c. Pro	tection of exits	-	-	_		
	•	Fire check door	Required	Provided	MR		
	•	Pressurization	N/A	N/A	N/A		
	e. No.	of continuous staircases to terrace	01	01	MR		
	g. Wi	dth of Corridor	Old case	1.20 mts	MR		
	h. Do	or Size	Old case	0.80 mts	MR being old case		
3	Comp	partmentation.					
	•	Fire check door	N/A	N/A	N/A		
	•	Sealing of electrical shafts	N/A	N/A	N/A		
	•	Fire Rating of shaft door	N/A	N/A	N/A		
	•	Water Curtain	N/A	N/A	N/A		
	•	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.						
		Basements	30 a/c per hou	r Exhaust fan provided	MR		
		Upper floors	12 a/c per hou	r Natural Vantilation	MP		

	Total numbers	15	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming	system.					
	Type of detectors	N/A	Smoke				
	Location of Main Panel	N/A	N/A	N/A			
	 Location of Repeater Panel 	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 65 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	N/A	Provided				
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	75 mm				
	 Number of hydrants per floor 	N/A	01 No.				
	Hose Box	N/A	01 No.				
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	> Head of Main pump		N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	> Auto Starting/ Manual stopp	ping N/A	N/A	N/A			
	> Pump House Access	N/A	N/A	N/A			
	Terrace level		,				
	Discharge of pump	450 LPM x		MR			
	> Head of the pump	30 mts e	2 11 1	MR			
	> Power Supply	Requir	red Provided	MR			

-

	ı						
+	Captive Water Storage for fire fighting.						
7	•	Underground tank capacity	N/A	N/A	N/A		
	- >	Draw-off connection	N/A	N/A	N/A		
	>	Fire service inlet	N/A	Provided	MR		
	>	Access to tank	N/A	N/A	N/A		
	•	Overhead Tank capacity	10000 lts	Provided	MR		
15	Exit S	ignage.	Required	Provided	MR		
16	Provision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A		
	•	Pressurization of Lift lobby	N/A	N/A	N/A		
	•	Communication In lift Car	Required	Provided	MR		
	•	Fireman's Grounding Switch	Required	Provided	MR		
	•	Lift Signage	Required	Provided	MR		
17	Stand	by power supply	Required	Provided	MR		
18	Refuge Area.						
	>	Total Area	N/A	N/A	N/A		
	>	Location	N/A	N/A	N/A		
19	Fire Control Room						
		Detector System Panel	N/A	N/A	N/A		
		Flow Switch Panel	N/A	N/A	N/A		
		PA System Panel	N/A	N/A	N/A		
		Battery backup	Required	Provided	MR		
		Building Floor Plans	N/A	N/A	N/A		
20		al Fire Protection Systems for ction of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/1055 dated 19.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K. CHATTOPADHYAY Div. Officer (South West)

DCFO (8Z)

2014

FIN