GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1625.

Dated: 13/7/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel M.S. Regency located at 15A/23, W.E.A, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus four upper floors, using basement as hall/storage, ground floor as reception, office, first, second & third floor each having 08 guest rooms respectively, (total 24 guest rooms), and a pantry for staff on fourth floor, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1056 dated 19.06.2015. The premises was re-inspected by the officer concerned of this department on 02/07/2018 in presence of Sh. Manoj Upadhyay, manager of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 13/7/13 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on $\frac{13}{7}$ at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICEI

Copy to:-

- 1. Sh. Ankur Madan (owner), M/s. Hotel M.S. Regency, 15A/23, W.E.A, Karol Bagh, New Delhi-110005.
- 2. The Additional C.P. (Lic.), Police Station Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel M.S. Regency, 15A/23, W.E.A, Karol Bagh,

New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/1056 dated 19.06.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 02.07.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Manoj Upadhyay, manager

9. Year of Construction

: Before 2005

10. Applicant's letter No.

: 3648/Addl. C.P/Lic (H) dated New Delhi the 25.05.2018

The said guest house is comprised of basement, ground plus four upper floors.

S. No.		nimum Standards on fire	Fire safety requirements as pe letter dt. 19.06.2015		Remarks MR/NMR		
1	Access to building						
	•	Road width	06 mts	Provided	MR		
	•	Gate width	Required	Directly accessible from the road	MR		
	•	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits						
	a. Num	ber of staircases	-	-	- "		
	•	Upper Floors	Old Case	01	MR being old case		
		Basements	Old Case	01	MR being old case		
	b. Widt	h of staircases	-	-	-		
	•	Upper Floors	Old case	1.30 mts	MR being old case		
		Basements	Old case	1.21 mts	MR being old case		
	c. Prote	ection of exits	-	-	_		
		Fire check door	N/A	N/A	N/A		
		Pressurization	N/A	N/A	N/A		
		of continuous staircases to terrace	01	01	MR		
	g. Wid	th of Corridor	Old case	1.20 mts	· MR		
	h. Doo		Old case	0.87 mts	MR being old case		
3	Compa	artmentation.					
	•	Fire check door	N/A	N/A	N/A		
	•	Sealing of electrical shafts	N/A	N/A	N/A		
	•	Fire Rating of shaft door	N/A	N/A	N/A		
	•	Water Curtain	N/A	N/A	N/A		
	•	Fire Dampers	N/A	N/A	N/A		
4	Smoke	Management System.	1				
	•	Basements	30 a/c per hou	Exhaust fan provided	MR		

-	Total numbers	- 15	Provided	≥R			
,	• Types	CO ₂ , ABC	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	7 Automatic fire detection and alarming system.						
	• Type of detectors	N/A	Smoke				
	 Location of Main Panel 	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set (125 KVA)	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
n.	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants		11/11	1 1 1 1 1			
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12							
	 Total number of hydrants 	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.		-	2.17.2.2			
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	Auto Starting/ Manual stopping	g N/A	N/A	N/A			
	Pump House Access	N/A	N/A	N/A			
	Terrace level Discharge of nump						
7 - 4	= seminge of pump	450 LPM	Provided	MR			
		30 mts	Provided	MR			
	Power SupplyAuto Starting of nump	Required	Provided	MR			

14	Ca	Captive Water Storage for fire fighting.						
		Underground tank capacity	N/A	N/A	N/A			
B ₂₁		Draw-off connection	N/A	N/A	N/A			
		Fire service inlet	N/A	Provided	N/A			
	11	Access to tank	N/A	N/A	N/A			
, ,		Overhead Tank capacity	5000 lts	6000 lts Provided	MR			
15	Exi	t Signage.	Required	Provided	MR			
16	Pro	Provision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	Required	Provided	MR			
	•	Fireman's Grounding Switch	Required	Provided	MR			
	•	Lift Signage	Required	Provided	MR			
17	Star	ndby power supply	Required	Provided	MR			
18	Ref	Refuge Area.						
		Total Area	N/A	N/A	N/A			
)	Location	N/A	N/A	N/A			
19	Fire	Control Room						
		Detector System Panel	N/A	N/A	N/A			
FIR	ESEA	Flow Switch Panel	N/A	N/A	N/A			
01	H OHI	PA System Panel	N/A	N/A	N/A			
Deta. Dialy	717	Battery backup	N/A	Provided	N/A			
ber	Tro. CA	Building Floor Plans	N/A	N/A	N/A			
20	Prote	ial Fire Protection Systems for ection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/1056 dated 19.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K. CHATTOPADHYAY

Div. Officer (South West)