GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018//626

Dated: /3/9/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Ramanujam Lodging House located at 12/4, W.E.A, Karol Bagh, New Delhi- 110005 comprised of ground plus two upper floors, using ground floor as reception & 10 guest rooms, first floor having 10 guest rooms and second floor having 03 guest rooms (total 23 guest rooms) was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1295 dated 21.07.2015. The premises was re-inspected by the officer concerned of this department on 02.07.2018 in presence of Sh. Ravi, manager of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 13/7/18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 13/7/8 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Ramanujam Lodging House, 12/4, W.E.A, Karol

Bagh, New Delhi- 05

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2015/SZ/1295 dated 21.07.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 02-07-2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Ravi, manager

9. Year of Construction

: Before 1987

10. Applicant's letter No.

: letter no nil Dated 21.06.2018

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 21.07.2015	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	Provided	MR
	Gate width	4.5 mts	Directly accessible from road	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangemen	t of Exits		
	a. Number of staircases	-	-	_
	Upper Floors	01	01	MR
	Basements	N/A	N/A	N/A
	b. Width of staircases	-	-	-
	Upper Floors	Old case	1.10 mts.	MR being old case
	Basements	N/A	N/A	N/A
	c. Protection of exits	-	-	-
	Fire check door	N/A	N/A	N/A
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	Old case	1.60 mts	MR
	h. Door Size	Old case	0.85 mts	MR being old case
	Compartmentation.			and the second s
	Fire check door	N/A	N/A	N/A
	Sealing of electrical shafts	N/A	Sealed	
	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A

	• Basements	30 a/c per hour	N/A	N/A		
	• Upper floors	12 a/c per hour	Natural Ventilation	MR		
5	Fire Extinguishers					
ile -	• Total numbers	10	Provided	MR		
	Types	CO ₂ , ABC, WCO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	 Total numbers on each floor 	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	 Location of Main Panel 	N/A	N/A	N/A		
	 Location of Repeater Panel 	N/A	N/A	N/A		
	Alternate source of power	Required	D.G. set 200 KVA	A MR		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	 Basement 	N/A	N/A	N/A		
	• Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	• Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.		14			
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.			- kg, 		
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	➤ Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	NI/A		

1	Auto Starting/ Manual	N/A	N/A	14/22
	stopping	N/A	N/A	N/A
	> Pump House Access			
	Terrace level	450 LPM	Provided	MR
	Discharge of pump	30 mts	Provided	MR
	> Head of the pump		Provided	MR
	Power Supply	Required	Provided	MR
	> Auto Starting of pump	Required		
	Captive Water Storage for fire fighting	g.	N/A	N/A
	 Underground tank capacity 	N/A		N/A
	> Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	> Access to tank	N/A	N/A	MR being old
-	Overhead Tank capacity	Old case	3,000 lts	case
		Required	Provided	MR
5	Exit Signage.		,	
6	Provision of Lifts.	N/A	N/A	N/A
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	 Fireman's Grounding Switch 	N/A	N/A	N/A
	• Lift Signage		Provided (25 KVA)	MR
17	Standby power supply	Required		
18	Refuge Area.	N/A	N/A	N/A
	> Total Area		N/A	N/A
	> Location	N/A	14/71	
19	Fire Control Room	N/A	N/A	N/A
	Detector System Panel		N/A	N/A
-	Flow Switch Panel	N/A	N/A	N/A
100	PA System Panel	N/A	14/17	100
a	Battery backup	Required	Provided	MR N/A
F1026	A CONTRACTOR OF THE PARTY OF TH	N/A	N/A	N/A
	Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any:		N/A	N/A

The fire protection systems provided in the building were checked and found functional at the

In view the deemed compliance of the minimum standards on fire prevention and fire safety time of inspection. measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/1295 dated 21.07.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended. department vide letter No.

shortcomings pointed the All F6/DFS/MS/GH/2018/SZ/2418 dated 01.06.2018

DFA is put up for approval & signature please.

TTOPADHYAY Divisional Officer (South West)