GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ | 6 6 3

Dated: --11-7-11-8-

FIRE SAFETY CERTIFICATE

Certified that the Aslam Guest House located at 501, Gali Matia Mahal, Jama Masjid, Delhi comprised of Ground (Commercial use), 1st floor (08 guest rooms + reception), 2nd floor (08 guest rooms) and 3rd floor (09 guest rooms), total 25 guest rooms owned/occupied by Aslam Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1041 dated 19/06/15. The premise was re-inspected by the officer concerned of this department on 01/07/18 in the presence of Sh. Naushed Alam (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 for 25 guest rooms at 1st to 3rd floor only with effect from -------for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -1-1-18-----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service of com

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter no. 3812/Addl. C.P/Lic. (H) dated 31/05/2018.
- 2. The Manager,

Aslam Guest House at 501, Gali Matia Mahal, Jama Masiid, Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

T3 T				
INSPE	CTIO	NID	LDC	DT
		IIV K	HPL	111

1. Name & address of the building Aslam Guest House at 501, Gali Matia

Mahal, Jama Masjid, Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 25 Guest rooms) Ground (Commercial use), 1st floor (08 guest rooms + reception), 2nd floor (08 guest rooms) and 3rd floor

(09 guest rooms)

3. Type of case:-

4. Details of previous FSC:-

No. F6/DFS/MS/GH/2015/NDZ/1041 dated

19/06/15.

N/A

Renewal

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:- Sh.

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

01/07/18

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Naushad Alam (Manager)

Old

3812/Addl.C.P/Lic.(H) dated 31/05/2018.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety	Provided at site	Old Case Remarks
1.	Access to Building	arrangements		MR/NMR
đ	1) Road width	Dan 9 C 1	2.40	
	1) Road Width	Pss & Spl. area	2.43 mtr.	N/A
	2) Gate width	N/A	N/A	N/A
	3) Width of internal road	N/A	N/A	
2.	Number, Width Type & Ari		N/A	N/A
	A. Number of staircases	angement of E	XILS	
	1. Upper floors	01 Nos.	01 Nos.	1 10
	2. Basements	N/A	N/A	MR
	B. Width of staircase	IVA	IN/A	N/A
	1. Upper floors	1 mtr.	1.10 mtr.	MD
	2. Basements	N/A	N/A	MR
	C. Protection of exits	11111	IVA	N/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	
	F. Door size	1.25 mtr.	1.25 mtr.	N/A
3.	Compartmentation	1.25 IIII.	1.23 11111.	MR
	1) Fire check door	N/A	N/A	N/A
*****	2) Sealing of electrical shafts	N/A	N/A	N/A N/A
	3) Fire rating of shaft door	N/A	N/A	N/A N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A N/A
•	Smoke Management System	IN/A		
_	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural	MR
5.	Fire Extinguishers	IVIK		
	1) Total numbers	08 Nos.	08 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR

6.	3) ISI marking	Requi	red	Dungit	
0.	First-Aid Hose Reel		icu	Provided	M
	1) Total number of eachfl	oor 01		0.1	
	2) Length of hose reel has	se 30 mtr		01	M
7	3) NOZZIE diameton			30 mtr.	M
7.	Automatic Fire Detection 1) Type of detectors	a & Alarmin	or Cree	05 mm	M
	1) Type of detectors	N/A	ig sys	stem	
	2) Location of main panel	27/1		N/A	* N/A
	3) Location of repeater par	ol NI/A		N/A	N/A
	Alternate source of nove	er N/A		N/A	N/A
0	3) Hooter's Location	N/A		N/A	N/A
8.	MOEFA	N/A		N/A	N/A
9.	Public Address System	D	-1	N/A	N/A
10.	Automatic Sprinkler System	require	<u>a</u>	Provided	MR
	1) Dasement	N/A			
	2) Upper floors	N/A N/A		N/A	N/A
	3) Sprinkler above false	N/A N/A		N/A	N/A
1.1	ceiling	IN/A		N/A	N/A
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A		21/	
	2) Number of hydrants per	N/A		N/A	N/A
	Hoor	14/14		N/A	N/A
2	3) Hose box	N/A		21/4	
2.	Yard Hydrants	11/11		N/A	N/A
	1) Total number of hydrants	N/A		27/4	
	2) Hose box	N/A		N/A	N/A
3.	Pumping Arrangement	I V/ A		N/A	N/A
	1) Ground level	N/A			
	a) Discharge of main	N/A N/A		N/A	N/A
	pump	IN/A		N/A	N/A
	b) Head of main pump	NI/A		<u> </u>	
	c) Number of main pump	N/A		N/A	N/A
	d) Jockey pump out put			V/A	N/A
	e) Jockey pump head	N/A		V/A	N/A
	f) Stand by pump output	N/A		N/A	N/A
	g) Stand by pump head	N/A		J/A	N/A
	h) Auto starting/Manual	N/A		J/A	N/A
	stopping	N/A	N	I/A	N/A
	2) Terrace level				
	a) Discharge of pump	225 1 72 4			
	b) Head of pump	225 LPM	22	25 LPM	MR
	c) Power supply	30 mtr.) mtr.	MR
	d) Auto starting of pure	Required		ovided	MR
C	Captive Water Storage for Fir	Required	Pre	ovided	MR
	1) Under ground tank	e Fighting		-	
	capacity	N/A	N/	A	N/A
	a) Drave - CC	T/A		1	
	h) Fire con ! ! !	V/A	N/A		N/A
) = 110 Solvice iniet	V/A	N/A	1	N/A

hu

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide F6/DFS/MS/GH/2015/NDZ/1041 dated 19/06/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Office

Name: - M.K. Sharma

Designation: - ADO (CC)

Dy. CFO (NDZ)

CF.Q. m. scell FT.M.

CF.Q. m. scell 1577.

P.T. Letter is put wp for