GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/

Dated :-28/6/-18----

FIRE SAFETY CERTIFICATE

Certified that the M/s Shree Balaji Dx. Guest House located at 2204, Raj Guru Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (reception + staff rooms + shops), 1st floor to 2nd floor (07 guest rooms at each floor), 3rd floor (staff kitchen + DG set), total 14 guest rooms owned/occupied by M/s Shree Balaji Dx. Guest House was granted **FSC** by this department No.F6/DFS/MS/GH/2015/NDZ/1977 dated 04/11/15. The premises was re-inspected by the officer concerned of this department on 15/06/18 in the presence of Sh. Bhola Nath and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 14 guest rooms unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

M/s Shree Balaii Dy. Guest House at 2204. Pai Guru P.

M/s Shree Balaji Dx. Guest House at 2204, Raj Guru Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPEC	INSPECTION REPORT				
1.	Name & address of the building	M/s Shree Balaji Dx. Guest House at 2204,				
		Raj Guru Road, Pahar Ganj, New Delhi.				
2	Type of occupancy:-	Residential, Sub Division-A-1				
		Gr. + 03 Upper floors (total 14 Guest rooms)				
		Ground floor (reception + staff rooms + shops),				
		1 st floor to 2 nd floor (07 guest rooms at each floor),				
		3 rd floor (staff kitchen + DG set)				

3. Type of case:-

4. Details of previous FSC:-

No. F6/DFS/MS/GH/2015/NDZ/1977 dated

04/11/15. N/A

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer

From the building side:9. Year of construction:-

9. Year of construction:10. Applicant's letter No:-

15/06/18

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Bothla Nath

Nil dated 01/06/2018.

				Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr	angement of Ex	rits		
	A. Number of staircases			100	
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	1.20 Mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace		*		
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	01 mtr.	01 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Provided	MR	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	10	10	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	

	First-Aid Hose Reel	DI/A	01	N/A
	1) Total number of eachfloor	N/A	30 mtr.	N/A
	2) Length of hose reel hose	N/A	05 mm	N/A
	3) Nozzle diameter	N/A		14/14
7.	Automatic Fire Detection & A	Alarming S	N/A	N/A
	1) Type of detectors	N/A	N/A N/A	N/A
	2) Location of main panel	N/A	N/A N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A		N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	IN/A
10.	Automatic Sprinkler System		>T/A	N/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	1 1// 1
	ceiling			
11.	Internal Hydrants	77/4	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A N/A	N/A
	2) Number of hydrants per	N/A	IN/A	17/11
	floor	DT/A	N/A	N/A
	3) Hose box	N/A	IN/A	1 1// 1
12.	Yard Hydrants	NI/A	N/A	N/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	IN/A	1777
13.	Pumping Arrangement	27/4	N/A	N/A
	1) Ground level	N/A	N/A N/A	N/A
	a) Discharge of main	N/A	IN/A	1471
	pump	DT/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pun		N/A	N/A
	d) Jockey pump out put	N/A	N/A N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu		N/A N/A	N/A
	g) Stand by pump head		N/A N/A	N/A
	h) Auto starting/Manua	ıl N/A	11///	1 1111
	stopping			-
	2) Terrace level	NT/A	120 LPM	N/A
	a) Discharge of pump	N/A	30 mtr.	N/A
	b) Head of pump	N/A	Provided	N/A
	c) Power supply	N/A	Provided	N/A
	d) Auto starting of pun	np N/A		7.41.7
14.	Captive Water Storage fo	r Fire Figh	N/A	N/A
1.	1) Under ground tank	N/A	19/73	14/12
	capacity	NT/A	N/A	N/A
	a) Draw-off connection	n N/A	N/A N/A	N/A
	b) Fire service inlet	N/A	N/A N/A	N/A
	c) Access to tank	N/A	2500 ltr.	MR
	d) Over head tank	N/A	2500 III.	IVIIC
	capacity			

m

		Required	Provided	MR
15.	Exit Signage.	Tequitor		
16.	Provision of Lifts.	27/4	N/A	N/A
	a) Pressurization of lift	N/A	IN/A	
	shaft		N/A	N/A
	b) Pressurization of lift	N/A	IN/A	
	lobby		N/A	N/A
	c) Communication in	N/A	IN/A	
	lift car		N/A	N/A
	d) Fireman's switch	N/A	N/A N/A	N/A
	e) Lift signage	N/A	Provided	MR
17.	Stand by Power Supply	Required		N/A
18.	Refuge Area	N/A	N/A	
10.		N/A	N/A	N/A
	Total area location	137.2.2		
	G (I Doom	N/A	N/A	N/A
19.	Fire Control Room		N/A	N/A
	a) Detector system	N/A	14/77	
	panel	NI/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	14/73	
3		27/4	N/A	N/A
	e) Building floor plan	N/A		
20	Special Fire Protection Sy	stem for Prot	ection of special	MR
20.	Risk, if any: ABC & CO ₂			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1977 dated 04/11/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO(NDZ)

C.F.O. mscell we rep for signalius please.

C.F.O. mscell up for signalius please.

C.F.O. M. SCELL W266.

617/c6dm