GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 1509

Dated: 28/6/18-

FIRE SAFETY CERTIFICATE

Certified that the Lav Kush Deluxe Guest House located at 7784-7800, Arakashan Road, Ram Nagar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (reception), 1st floor to 2nd floor (11 guest rooms at each floor), 3rd floor (10 guest rooms), Terrace floor (Temporary staff room), total 32 guest rooms owned/occupied by Lav Kush Deluxe Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/747 dated 13/05/15. The premise was re-inspected by the officer concerned of this department on 18/06/18 in the presence of Mr. Rishabh Goel (Proprietor) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 32 guest 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager, Lav Kush Deluxe Guest House at 7784-7800, Arakashan Road, Ram Nagar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	N 31	Ö		B-62		
	INSP	ECTION REPOR				
1.	Name & address of the building		eluxe Guest House at			
			oad, Ram Nagar, Pal	nar Ganj,		
		New Delhi	a l D' ' ' A l			
2.	Type of occupancy:-	Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 32 Guest rooms)				
		Ground floor (1	reception), 1 st floor to	2 nd floor		
		(11 guest room	s at each floor), 3rd flo	or (10 guest		
			e floor (Temporary sta	ff room)		
	Type of case:-	Renewal				
4.	Details of previous FSC:-		No. F6/DFS/MS/GH/2015/747 dated			
_		13/05/15.				
	Fire safety directives No	N/A				
	Date of inspection:					
	Name of the inspecting officers		Lumai Sharma (AL	0/00)		
8.	Name & designation of officer From the building side:-	Mr Richahh	Goel (Proprietor)			
0	Year of construction:-	Old	Goer (Froprietor)			
	Applicant's letter No:-	Nil dated 11/06	/2018.			
10.	Applicant s letter 140.			Old Case		
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
0.1101	Prevention and fire safety	Existing fire safety arrangements		MR/NMR		
	U/R 33	arrangements				
1.	Access to Building					
	1) Road width	N/A	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Art	angement of Ex	its			
	A. Number of staircases) (D)		
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	1.05	1 20 4 - 1 20	MD		
	1. Upper floors	1.25 mtr.	1.20 to 1.30 mtr.	MR N/A		
	2. Basements	N/A	N/A	N/A		
	C Dustaction of oxita	1	1			

S.No.	Prevention and fire safety U/R 33	Existing fire safety arrangements	Flovided at site	MR/NMR
1.	Access to Building			
	1) Road width	N/A	06 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr	angement of Ex	its	
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	1.25 mtr.	1.20 to 1.30 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	01	01	MR
,	staircase to terrace			
	E. Width of corridor	1.25 mtr.	1.25 mtr.	MR
	F. Door size	1.0 mtr.	1.0 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 a/c per	Natural	MR
		hour	-	

5.	Fire Extinguishers		•	
	1) Total numbers	10 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided Provided	
6.	First-Aid Hose Reel	required	Tiovided	MR
	1) Total number of eachfloor	01	01	MD
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Syst	103 IIIII	MR
	1) Type of detectors	N/A	N/A	DI/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A N/A	N/A
8.	MOEFA			N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Provided	MR
±U.	1) Basement		27/4	
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	N/A	N/A	N/A
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	100	100	
		100 mm	100 mm	MR
	2) Number of hydrants per floor	01	01	MR
	3) Hose box	0.1	21	
12.		01	01	MR
14.	Yard Hydrants	21/4		
	1) Total number of hydrants 2) Hose box	N/A	N/A	N/A
3.		N/A	N/A	N/A
٥.	Pumping Arrangement	-	* 1	
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump		-	
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
		-		

hu

14.	Captive Water Storage for	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
7	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltr.	10,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	. N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	m for Protecti	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/747 dated 13/05/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Office

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

As approva, For letter is put up
please