FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No.F-6/DFS/MS/GH/2018/WZ/ 1494

Dated: 25 /06/2018

FIRE SAFETY CERTIFICATE

Certified that the Hotel Royal Mirage, Located at WZ – 107/ A-B, Rishi Nagar, Rani Bagh, Delhi – 110034 in a building comprised of Basement +Ground+ 3 Upper Floor was issued FSC vide this office letter noF-6/DFS/MS/GH/2014/WZ/1414 dated 18/11/2014. The premises was inspected by the officers concerned of this department on 14-06-2018 in the presence of Mr Gurpreet Singh Munna (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A of Sub Division - A 1 with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...25.1.6.4.3..... at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: 1. Hotel Royal Mirage, WZ - 107/ A-B, Rishi Nagar, Rani Bagh, Delhi

2. The Joint CP(Lic), 1st Floor, PS Defence colony, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per BBl 1983.
- 7. Tin Shed shall not be used for any activity.
- 8. All the passage & staircases will be kept free from any obstruction.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 10. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

Name & address of the building: Hotel Royal Mirage, Located at WZ - 107/ A-B, Rishi Nagar, Rani Bagh, Delhi – 110034.

1. Type of Occupancy: Residential (Guest House)(Basement+Ground+3 upper floors and Tin Shed at terrace)

2. Type of Case

: Renewal

3. Details of previous NOC

: F-6/DFS/MS/GH/2014/WZ/1414 Dated

18/11/2014

4. Fire Safety directives Letter No.: Nil

5. Date of inspection

:14-06-2018

6. Name of the Inspecting Officer: ADO (WP)

7. Name and designation of Officer

from the building side

: Mr.Gurpreet Singh Munna

8. Year of Construction

Applicant's letter No.

	9. Applicant's letter No.		:1	Vil dat	ed 28-05-2018	3		ж.	
S	33	BBL Requirem		ments	Provided a	Provided at site			
1.	Access of building								
	Road width	6	6 mtr NA NA		Provided	I N	(D		
	Gate width	N			On road		MR NA		
	 Width of internal road 	N			27.		MR		
2.	Number, width, Type & Arran	gem	ents of	exits			<i>3</i>		
		_		011105					
	a. Number of staircases				Λ.	- P	1_		
	• Upper floors	02			vided		The state of	MR	
	Basements	02			vided	i.		MR	
	b. Width of staircases							2722	
	• Upper floors	Required Required			15cm,99cm	MF	R(Old	case)	
	 Basements Protection of exits 			1.				case)	
	c. Protection of exits								
	Pressurization		NA		NA	NA			
	d. No of continuous	NA			NA	The second secon		NA	
	staircase to terrace	01	01		Provided	Provided		MR	
	e. Width Of Corridor f. Door Size		NA NA						
			1m		vided	idad		NA	
3.	Compartmentation	111	1	Trovided			M	R	
	 Fire check door 	NA			NA		NA		
	 Sealing of electrical shaf 		NA			NA NA		A	
	 Fire Rating of shaft door 		NA					NA	
	Water Curtain		NA		NA	NA			
1	• Fire Dampers		NA		NA .		NA		
4.	Smoke managements System				_		1112		
	Upper floors				Exhaust Fan		MF	MR	
					provided				
5.	Fire Extinguishers	12 a/c per		nour	NA	NA		NA	
٥.				y P					
	Total numbers	101	nos.		10	10		MR	

		And Hose Reels								
		 Total numbers on each 	h 1			Provided		1.00		
		floor				Tiovided		MR		
-		 Length of hose reel 	30	30mRequired		Provided		1.00		
	hose			3 omredaned		Flovided		MR		
	Nozzle diameter		5	5 mm		D '1 1				
	7.	7. Automatic fire detection and ala		ing grigters	- 1	Provided MR		MR		
		Type of detectors	N.	ang system			~			
• 10		 Location of Main 	IN.	A		Provided	N	A		
	Panel		NA		D :1 1		2			
						Provided	N.	A		
		 Location of Repeater Panel 	NA							
		 Alternate source of 	INA	<i>A</i>	1	Provided NA		A		
		power	NA							
-		Hooters' Location				Provided	NA			
S	3.	MOEFA		NA		rovided	NA			
_	_		Re	Required		rovided	MR			
		Public Address System	Re	Required		Provided MR				
1	0. 1	Automatic Sprinkler System				12	141			
	-	 Basements 	Red	quired	P	rovided	MI	5		
×		 Upper Floor 	NA			A	NA			
		 Sprinkler above false 	NA			A	NA			
_		ceiling					INA	`		
1	1. I	nternal Hydrants:								
1	-	 Size of riser/down-com 	ner .	er NA NA		Provided Provided				
		Number of hydrants per						NA		
		floor								
		 Hose Box 			60.46		NA			
12) 1/	112 112		NA	Pr	ovided	NA			
12	2. I	ard Hydrants					1111			
		 Total number of 	NA		N	4	NA			
-	3	hydrants					1 42 1			
10	7	Hose Box	NA	V.	NA	A	NA			
13	Pı	Pumping Arrangements:								
		 Ground Level 			-		4			
		 Discharge of main 	NA		NA		NA			
2.		pump			1		INA			
		Head of main pump	NA		NA		ŇA			
		Number of main	NA		NA		-			
		pumps	. *		1 12		NA	•		
	22	Jockey pump out put	NA		NA		NTA			
		Jockey pump head	NA		NA		NA			
	1	Standby Pump out put	NA		NA		NA			
		Standby Pump Head	NA		NA NA		NA NA			
		Auto Staring/Manual	NA							
		stopping	11/1		NA		NA			
		> Pump House Access	NA		NT A	TA				
- 1		• Terrace level	INA		NA	A NA				
		Discharge of	900 LPM		2 :					
		1	700 L	LIVI	2x450 LPM		MR			
		Head of the pump	40 m		Provided					
		Power supply				Market Area and Area	MR			
1		Auto starting of numer				rided	MR			
7			Requi	rea	Prov	rided	MR			
14.	Captive water Storage for fire fighting:									
		TT 4	NA		NA			NIA		
		capacity	- 14 1		INA		W = 1	NA		
		Draw off connection NA		NT A				271		
		V T	NA NA							
			NA NA			- 11/21				
			10.000		NA	A NA		NA		
		No.	V.VIV	HILES	rrow.	1100		100		

16.	Provision of Lifts						
	Pressurization of Lift Sh	NA		NA	NA		
	Pressurization of lift lob	ation of lift lobby			NA	NA	
	Communication in lift C	an's Grounding Switch			Provided	MR	
	Fireman's Grounding S				Provided	MR	
	Lift Signage		Required		Provided	MR	
17.	Standby power supply		Required		Provided	MR	
18.	Refuge Area				ž	in the second se	
	> Total area		NA		NA	NA	
	Location		NA		NA	NA	
19.	Fire control room						
	Detector system panel	NA		NA	Λ	NA	
	Flow Switch Panel	NA		NA		NA	
	PA System Panel	NA		NA		NA	
	Battery backup	NA		NA	Λ	NA	
	Building Floor Plans	NA	a a	NA		NA	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA		NA	λ	NA	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter no. F-6/DFS/MS/GH/2014/WZ/1414 Dated 18/11/2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Udaivir Singh Designation ADO/WP Signature of the Inspecting Officer

Name

Designation

1) 9/w /muler/14/6/18

TX. (90 6/2) - EK (90 W7)/5/06/P

40/Mb 312 64 1

letter

is polopeden