GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001.

No. F.6/DFS/MS/Cinema/2018/SZ/ / 4 95

Dated: 257 6/18

FIRE SAFETY CERTIFICATE

Certified that the **INOX Leisure Ltd.** (Audi 1 to 4), Plot No.-19, District Centre, Janak Puri, New Delhi-110058, comprised of basement, ground plus four upper floors, using ground floor as office, First floor 02 Audi, Second floor mechanical room/toilets, Third Floor 02 Audi & fourth floor mechanical room owned/ occupied by M/s Inox Leisure ltd. Earlier known as Satyam Cinema was issued NOC by this department vide letter no. F.6/DFS/MS/Cinema/2015/1173 dated 03.06.15 was re-inspected by the officers concerned of this department on 12.06.2018 in the presence of Sh. Pankaj Kanotra (G.M. Operations) and found that the owner/occupier have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises (Audi 01 to 04) is fit for occupancy class Group- D Assembly Building w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on at New Delhi.

(VIPIN KENTAL) CHIEF FIRE OFFICER

Copy to:-

 The Manager, INOX Leisure Ltd. (Audi 1 to4), Plot No.-19, District Centre, Janak Puri, New Delhi-110058.

2. The District Magistrate (West), Govt. of NCT of Delhi, Old Middle School Complex, Rampura, New Delhi-110035. Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	0.00	. Name & address of the building	NSPECTIC	N REPORT	7 110013	
-				eisure Ltd. (Aug	di 1 to4), Plot No19 8.	, District Centre Jan
		Type of Occupancy	: Group D	w Delhi-11005 (Assembly Bu	8.	, 541
		. Type of Case	: Renewal	(Assembly Bu	ilding)	
	4	- Details of Flevious Not	F (/DEG	MS/Cinoma/20	15/1170	
	5	Salety directives letter No.	F.6/MS/D	FS/RP/2002/C	015/1173 dated 03.06	.15
	6	Date of inspection	: 12.06.201	8	linema/992 dated 24.	06.2002
	0	Name of Inspecting Officer	DOME	Chattonadh	0 4 7 0	
	8.	Name and designation of officers	2.0. W.K	. Chattopadnya	ny & A.D.O. Sandeer	Duggal
	0	From the building side				
	9.	Year of Construction	: 2002	Kanotra (G.M	. Operations)	
	1(. Applicant's letter No.	Door	18/30175 dated	1.06.04.5	
		Using ground floor as office, First	floor 02 Aug	i Second d	106.04.2018	
S.	B.F.	Using ground floor as office, First Audi & fourth floor mechanical ro	oom	ii, Second 1100	r mechanical room/to	oilets, Third Floor 02
No.	IVIII	stanuards on fire provents.	on and fire	NBC/ BBL		
1.		3 9/1033	on and me		Provided at	Remarks
1.	Acc	ess to building		Requiremen	t site	MR/NMR
					DATE OF THE PARTY	
		Road width		A 222 11 (22	P	
	4	Gate width		Accessible (09 r 06 mtrs	12 111115	MR
		Width of internal road			Directly accessible	MR
2	PY			06 mtrs	from road 06 mtrs	MR
2.	Nun	ber, Width, Type & Arrangemen	t of Evita		00 mtrs	IVIIC
			LAILS			D.S. T. C. C.
	a. N	ımber of staircases				
	•	Upper Floors		The second	and the latest the second	
	•	Basements	·	04 No.'s	04 No.'s) (D
			21	01 No.+ 01 Ran	mp 01 No.+ 01	MR
	b. W	dth of staircases			Ramp	MR
	•	Upper Floor		T 15 2 1	Kallip	A second
		Basements		02 mtrs	2.07.2.10.0	
	<u>.</u>	Basements		02 111115	2.07, 2.12, 2.07	MR
			1 - 4 = 1	02 mtrs	& 2.04 mtrs S/Case 2.03 &	
	c. Pro	tection of exits		02 mus	Ramp 4.5 mtrs	MR
	0. 110				Teamp 4.5 mus	
		Fire check door		Required	D	
		Pressurization			Provided	MR
	d M			Required	Provided	MR
	u. No	of continuous staircases to	- I			
	ter	ace		Required	One	MR
	e. Wi	lth of Corridor		150 cms		
	6 -			0 01115	Opening in	MR
-	f. Do	or Size		150 cms	hall	**
	~	5118.30		150 CIIIS	180, 160 &	MR
	Compa	rtmentation •		3	160 cms	
	. •	Fire check door				
	•	Sealing of electrical shafts	-	Required	Provided	MR
		Fire Rating of shaft door		Required	Sealed	
		Water Curtain				MR
	•	Fire Dampers		N/A	N/A	N/A
				N/A	Provided	N/A
1	Smoke 1	Management System		Required	Provided	
				1 44	-1011404	MR
	•	Basements		Required	D	
_				required	Provided	MR
	• [Jpper floors	100	D		
				Required	Natural	« MR
F	Fire Ext	nguishers			Ventilation	
						The state of the s
		otal numbers		50 No.'s	Dravid 1	
		ypes	AB	C/CO ₂ /WCO ₂	Provided	MR
		marking	I	SI marked	Provided	MR
F	irst-Aid	Hose Reels		- Indiana	ISI marked	MR
						IVIK
	• 1	otal numbers on	*,>			
	• 1	otal numbers on ground floor ength of hose reel hose		03	Provided	
		TIPLI OT hose roal hose			Tiovided	MR

7.	Automatic fire detection and alarming system			
	• Type of detectors	Smoke & Heat	Provided	100
	Location of Main Panel	Required	G. Floor	MR
	Location of Repeater Panel	N/A		MR
	Alternate source of powerHooters' Location	Required	N/A	N/A
0		Required	Provided Provided Near exit	MR
8.	MOEFA	Required	Provided	MR MR
9.	Public Address System	Paguinal	7.11	
10.		Required	Provided	MR
10.	Automatic Sprinkler System			2
	Basement	Required	Provided	
* *	Ground Floor	Required	Provided	MR
11	Sprinkler above false ceiling	Required		MR
11.	Internal Hydrants	required	Provided	MR
	Size of riser/down-comer	150 mm	Provided	100
	 Number of hydrants 	03 No.'s	Provided	MR
1.5	Hose Box	03 No.'s		MR
12.	Yard Hydrants	55 110. 3	Provided	MR
	Total number of hydrants	T		
	Hose Box	Two	Provided	MR
13.	Pumping Arrangements	Two	Provided	MR
	Ground Level			
	Discharge of main Pump	2850 LPM	D	
	Head of Main pump	To the second se	Provided	MR
	Number of main pumps	60 mtrs	Provided	MR
	Jockey Pump out put	One	Provided	MR
	Jockey pump head	180 LPM	Provided	MR
	Standby Pump out put	60 mtrs	Provided	MR
	Standby Pump Head	2850 LPM	Provided	MR
	Water Curtain Pump	60 mtrs	Provided	
	➤ Auto Starting/Manual Stopping	Required	Provided	MR
		Required		MR
	Pump House Access	Required	Provided	MR
	Terrace level	Required	Provided	MR
	Discharge of pump	N/A	N/A	NI/A
	Head of the pump	N/A	N/A	N/A
	Power Supply Auto Starting of nump	N/A	N/A N/A	N/A N/A
	Auto Starting of pump	N/A	N/A	N/A N/A
4				
4.	 Captive Water Storage for fire fighting Underground tank capacity 			
	> Draw-off connection	100000 Ltrs	Provided	MR
1	Fire service inlet	Required	Provided	MR
i.	Access to tank	Required	Provided	MR
	Overhead Tank capacity	Required	Provided	MR
		10000 ltrs	45000 ltrs	MR
			Provided	IVIK
5.	Exit Signage.	Required	Provided	MR
5.	Provision of Lifts.			
	Pressurization of Lift Shaft	77/4		
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
		Required	Provided	MP

18. Refuge Area. N/A N/A N/A Total Area

		Location	N/A	N/A	N/A
÷					1.2
19.	Fire Co	ntrol Room		9-1	
	•	Detector System Panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans	N/A	N/A	N/A
	•		N/A	N/A	N/A
	•		N/A	N/A	N/A
	•		N/A	N/A	N/A
			N/A	N/A	N/A
20.		Fire Protection System for Protection of Risks, if any:	Manual CO ₂ Fire	Provided	MR
			Fighting System		
			for LT, HT Panel	r.	
	1		Modular type		
			DCP for AVH's	· ·	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F.6/DFS/MS/Cinema/2015/1173 dated 03.06.15 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: Building comprised of basement, ground floor plus four upper floors has already been issued FSC vide letter no. F.6/DFS/MS/2017/SZ/130 dated 02.02.2017.

Signature of Inspecting Officer

Name: - M.K. Chattopadhyay Designation: - Divisional Officer

Sandal 8 Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation:- Asstt. Divisional Officer

Dy. C.F.O. (South Zone) - leave