## FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/EH/2018/WZ/ / 4 2 )

Dated: 18 /06/2018

## **FIRE SAFETY CERTIFICATE**

Certified that the M/s Capital Grill (a unit of JPS Fine Dining LLP) located at A - 4, Ground Floor, Vishal Enclave, New Delhi in a building comprised of Basement + Ground + 3 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/EH/2015/WZ/561 Dated -21/04/2015. The premises was re inspected by the officers concerned of this department on 02-06-2018 in the presence of Mr. Anil Suri and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D (Ground Floor Only) with effect from  $\frac{18/06/18}{1800}$  for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 18/06/18 at New Delhi by.

Chief Fire Officer
Delhi Fire Service

## Copy to:

- 1. M/s Capital Grill (a unit of JPS Fine Dining LLP), A 4, Ground Floor, Vishal Enclave, New Delhi.
- 2. Dy. Health Officer, West Zone, SDMC, Public Health Department, Vishal Enclave, New Delhi. Following fire safety directives must be adhered to:-
- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. This NOC is valid for Ground Floor only.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per building bye laws.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

## **INSPECTION REPORT**

1. Name & address of the building: M/s Capital Grill (a unit of JPS Fine Dining LLP) located at A – 4, Ground Floor, Vishal Enclave, New Delhi.

2. Type of Occupancy : Assembly on ground floor only in a building comprised of Basement + G + 3 Upper Floors.

3. Type of Case : Renewal

4. Details of previous NOC: F6/DFS/MS/EH/2015/WZ/561 Dated -21/04/2015

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 02-06-2018

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

from the building side : Mr. Anil Suri

9. Year of Construction : 2014

10. Applicant's letter No. : Nil dated -06/04/2018

S	Minimum standards on fire	NBC	Provided at	Remarks	
No	prevention and fire safety U/R	Requirements	site	MR/NMR	
110	33	Requirements	Site	IVIIX/INIVIIX	
1.	Access of building				
	Road width	6 m	Provided	MR	
	Gate width	NA	On Road	NA	
	<ul> <li>Width of internal road</li> </ul>	NA	NA	NA	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases				
	<ul> <li>Upper floors</li> </ul>	NA	NA	NA	
	<ul> <li>Basements</li> </ul>	NA	NA	NA	
	b. Width of staircases	1			
	<ul> <li>Upper floors</li> </ul>	NA	NA	NA	
	<ul> <li>Basements</li> </ul>	NA	NA ·	NA	
	c. Protection of exits			8	
	<ul> <li>Fire check door</li> </ul>	NA	NA	NA	
	<ul> <li>Pressurization</li> </ul>	NA	NA	NA	
	d. No of continuous staircase to terrace	NA	NA	NA	
	e. Width Of Corridor	NA	NA	NA	
	f. Door Size	2m & 1m	2X204 cm,	MR	
			1X102cm		
			>		
		1 * _	3		

3.	Compartmentation	I					
	Fire check door	NA	NA	NA			
NZ.	<ul> <li>Sealing of electrical shafts</li> </ul>	NA	NA .	NA			
	Fire Rating of shaft door	NA	NA	NA			
	Water Curtain	NA	NA	NA			
	Fire Dampers	NA	NA	NA NA			
4.	Smoke managements System	1171	1421	1474			
	Basements	NA	NA	NA			
	Upper floors	12 a/c per hour	Provided	MR			
5.	Fire Extinguishers	· p · · · · · · · · ·	11011404	1711			
	Total numbers	04 nos.	Provided	MR			
	• Types	ABC & CO <sub>2</sub>	Provided	MR			
	• IS marking	ISI marked	Provided	MR			
6.	First – Aid Hose Reels		Trovided	IVIIC			
0.	Total numbers on each	1	Provided	MR			
	floor	1	Trovided	IVIK			
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7.	Automatic fire detection and alar	The Controller	Tiovided	IVIK			
/.		NR	Provided	ND			
	<ul><li>Type of detectors</li><li>Location of Main Panel</li></ul>	NR	Provided	NR			
		NR		NR NB			
	<ul> <li>Location of Repeater</li> <li>Panel</li> </ul>	INK	NR	NR			
	501 Section (#APA)	NR	Provided	NR			
	Alternate source of	INIX	Provided	INK			
	<ul><li>power</li><li>Hooters' Location</li></ul>	NR	Provided	NR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	NR	NR	NR			
		INIX	INIX	INK			
10.	Automatic Sprinkler System	Tara tara tara tara tara tara tara tara	T				
	• Basements	NR	NR	NR			
	<ul> <li>Upper Floor</li> </ul>	NR	Provided	MR			
	Sprinkler above false	NR	NR	NR			
	ceiling						
11.	Internal Hydrants:						
	<ul> <li>Size of riser/down-</li> </ul>	100 mm	Provided	MR			
	comer						
	<ul> <li>Number of hydrants per</li> </ul>	1	Provided	MR			
	floor						
	Hose Box	Required	Provided	MR			
12.	Yard Hydrants						
	<ul> <li>Total number of</li> </ul>	NA	NA	NA			
	hydrants		7	<u>.</u>			
	Hose Box	NA	NA	NA			
	1		* * 5 5				
	****			100			

D	imping Arrangements:		· ·	
Pu	0 111			NIA
	n: 1 - of main numn	NA	NA	NA
	1 6	NA	NA	NA
	C in mumps	NA	NA	NA
	t mit	NA	NA	NA
	<ul><li>Jockey pump out put</li><li>Jockey pump head</li></ul>	NA	NA	NA
	Standby Pump out put	NA	NA	NA
•	<ul> <li>Standby Pump Head</li> <li>Auto Staring/Manual stopping</li> <li>Pump House Access</li> </ul>	NA	NA	NA
		NA	NA	NA
		NA	NA	NA
	> Terrace level	450 1	Provided	MR
	Discharge of pump	450 lpm	Provided	MR
	> Head of the pump	40 m	Provided	MR
	> Power supply	Required	Provided	MR
1	> Auto starting of pump	Required	Flovided	11111
4.	Captive water Storage for fire fi	ghting:	NA	NA
-	<ul> <li>Under ground tank</li> </ul>	NA	INA	
	capacity	271	NA	NA
	Draw off connection	NA	NA NA	NA
	> Fire service inlet	NA	Provided	MR
	Access to tank	NA .	10000 litres	
	<ul> <li>Overhead Tank capacity</li> </ul>	y 10000 litres	Provided	1
			Provided	MR
5	Exit Signage	Required	Tiovided	
6.	Provision of Lifts	N. A.	NA	NA
	<ul><li>Pressurization of Lift</li></ul>	NA	INA	
	Shaft	271	NA	NA
	Pressurization of lift	NA	INA	
	lobby		NA	NA .
	Communication in lift	NA	INA	
	Car		NA -	NA '
	Fireman's Grounding	NA	INA	
	Switch		NA	NA
	Lift Signage	NA	Provided	MR
17.	Standby power supply	Required	Flovided	
18.			NA	NA
1	> Total area	NA	NA NA	NA
	> Location	NA	INA	1
19.	Fire control room		NA	NA
-	Detector system pane	1 NA	NA NA	NA
	Flow Switch Panel	NA		NA
	> PA System Panel	NA	NA	NA
	Battery backup	NA	NA	NA NA
	Building Floor Plans	NA	NA	INA
			1 1	

20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA*	NA	NA	
unct	The fire protection systems pro- ional at the time of inspection. In view of the deemed complian				
re 6/D ire S	safety as required under th FS/MS/EH/2015/WZ/561 Dated - Service Rules 2010 is recommende	e rules the -21/04/2015 re	NOC issued	vide letter no	
	Signature of the Inspecting Office				
			nature of the Ins	pecting Officer	
	Name Uda Vir & Designation ADO/W	Nar Nar	ne		
	Designation ADO/W	Des Des	signation		
			4		
	1 10 11	1			
	1 9 1 s mula	n/6/18			
	Dy CRO WY-EN	12			
	CFO (W2) M			. Iv	
	[3]	of Pls	as con		
		11			
	DOW pruher 141	16/18			
	AXOLAM			1 01	
	Six for lette	er 18	who toy	s for wh	ple.
	h \				18/8/18
	CASTOCIP				
	10/00/1				