GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. **F6/DFS/MS/SCHOOL/2018/** /427

Dated: /9/06/18

FIRE SAFETY CERTIFICATE

Certified that the H. S. Public School located at Plot No. 559, Kh.No. 54/16, Ashok Mohalla-II, Near Shiv Mandir, Nangloi, Delhi-110041, comprised of Ground + One Upper Floor only owned / occupied by H. S. Public School, has already been issued NOC / FSC by this department vide letter No. F6/DFS/MS/2013/School/719 dated 19/08/2013. The premises was reinspected by the officer concerned of this department on 12.06.2018 in the presence of Smt. Raj Rani (Principal) and observed that Fire prevention and fire safety arrangements provided in the premises, found in good working condition. The premises have therefore, deemed complied with the fire prevention and fire safety requirements in accordance with the Circular No. F6/Estate/CC/Fire/Safety/2011/3298-3398 dated 01/03/2011 and that the building / premises is fit for occupancy class Educational (Group B) with effect from19.1.6./1.8...for a period of 3 (three) years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

19 06 at New Delhi by.

CHIEF FIRE OFFICER

Copy to :-

- 1. Principal, H. S. Public School, Plot No. 559, Kh.No. 54/16, Ashok Mohalla-II, Near Shiv Mandir, Nangloi, Delhi-110041.
- 2. The Director of Education, GNCT of Delhi, Old Secretariat, Delhi-110054.

Conditions for the validity of Fire Safety Certificate:

- All the fire safety arrangement provided their in shall be maintained in good working 1. conditions at all times.
- Loss of life or property due to non functional fire safety measure shall be at the 2. responsibility of the management.
- The trained fire fighting staff should be available round the clock. 3.
- Any deviation with regard to the construction etc shall be verified by the concerned building 4. sanctioning agency.
- This certificate cannot be treated in any case for regularizations of unauthorized 5. construction.
- "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director 6. in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

The owner / occupier shall submit a declaration every year in form "K" provided in the first 7. schedule of Delhi Fire Service Rules 2010. The from is available WWW dfs Delhigayt nig in

N114 **INSPECTION REPORT**

1. Name & address of the building: H. S. Public School, Plot No. 559, Kh.No. 54/16, Ashok Mohalla-II, Near Shiv Mandir, Nangloi, Delhi-110041.

2. Type of Occupancy

: Educational

Ground + one upper floor

3. Type of Case

: Renewal

: F6/DFS/MS/2013/School/719 dated 19/08/2013

5. Fire Safety directives Letter No.: DOE Circular Dated 17/01/2005

6. Date of inspection

: 12/06/2018

7. Name of the Inspecting Officer: A. K.-Jaiswal (ADO JWP)

8. Name and designation of Officer

from the building side

4. Details of previous NOC

: Smt. Raj Rani.(Principal)

9. Year of Construction

Plot Area-600 Yard²

: 1996 Plot Area-400 Yard² 10. Applicant's letter No. : - Nil Dated 25/05/2018

S No	Minimum standards on fire prevention and fire safety	DOE. Circ. Dated 17/01/2005	Provided at site	Remarks MR/NMR		
110	U/R 33	Requirements	Site	TVII O I VIII O		
1.	Access of building					
	Road width	6 mtr	6 mtr	MR		
	Gate width	5 mtr	5 mtr	MR		
	Width of internal road	N/A	N/A	N/A		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases					
	Upper floors	2	2	MR		
	Basements	N/A	N/A	N/A		
	b. Width of staircases					
	Upper floors	1.50 mtr	1.40 mtr x 1 1.20 mtr x 1	MR		
	Basements	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No of continuous staircase to terrace	1	1	MR		
	e. Width Of Corridor	1.50 mtr	1.50 mtr	MR		
	f. Door Size	1.00 mtr	1.00 mtr	MR		
-3.	Compartmentation			*		
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	The state of the s	•	*		
4.	Smoke managements System					
	Basements	N/A	N/A	N/A		
	Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers			1		
	Total numbers	4	6	M/R		
	• Types	ISI marked ABC/CO ₂	Provided	M/R		
	IS marking	Required	Provided	M/R		
	Mg.					

0.	1 list – Ald Hose Reels						
	 Total numbers on 	1	1	MR			
-	each floor	4,110					
	 Length of hose reel 	30mtr	30mtr	MR			
	hose						
	Nozzle diameter	5 mm	5 mm	MR			
7.	Automatic fire detection and a	and the first and a first state of the first state					
	Type of detector	N/A	N/A	N/A			
	Location of Main	N/A	N/A	N/A			
	Panel	14/5	10/7	18/7			
	Location of Repeater	N/A	N/A	N/A			
	Panel	14/	17/4	N/A			
		NI/A	DI/A	01/0			
	Alternate source of	N/A	N/A	N/A			
	power						
	Hooters' Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	N/A	N/A	N/A			
10.	Automatic Sprinkler System						
	Basements	N/A	N/A	N/A			
	 Upper Floor 	N/A	N/A	N/A			
	 Sprinkler above false 	N/A	N/A	N/A			
	ceiling		*				
11.	Internal Hydrants		5				
	 Size of riser/down- 	N/A	N/A	N/A			
	comer			•			
	 Number of hydrants 	N/A	N/A	N/A			
	per floor						
	Hose Box	N/A	N/A	N/A			
12.	Yard Hydrants		1 . 7	1.7			
	Total number of	N/A	N/A	N/A			
	hydrants		14/73	13/75			
	Hose Box	N/A	N/A	N/A			
13.	Pumping Arrangements	14/74	14/7	IN/A			
	• Ground Level N/A						
	Discharge of main pump	N/A	N/A				
				D1/0			
	1 1	N/A	N/A	N/A			
	Number of main pumps Jockey pump out put	N/A	N/A	N/A			
	The state of the s	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
-	Standby Pump Head	N/A	N/A	N/A			
,	Auto Staring/Manual	N/A	N/A	N/A			
1	stopping Pump House Access	NI/A	NI/A	N1/A			
		N/A	N/A	N/A			
	Terrace level						
	Discharge of pump	450 LPM	450 LPM	MR			
	 Head of the pump 	40 MH	40 MH	MR			
3	Power supply	Required	Provided	MR			
,	Auto starting of pump	Required	Provided	MR			
14.	Captive water Storage for fire	fighting					
17.	Underground tank	N/A	N/A	N/A			
	capacity	IN/ A	IN/A	N/A			
	> Draw of connection	N/A	NI/A	NI/A			
	Fire service inlet		N/A	N/A			
\	Access to tank	N/A N/A	N/A	N/A			
	Overhead Tank	2,500 Ltr	N/A 2 500 Ltr	N/A			
		2,500 Ltf	2,500 Ltr	MR			
2 1	capacity						

	, , ,	110				
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of lift lobby	N/A	N/A	N/A		
	Communication in lift	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	➤ Lift Signage	N/A	N/A	N/A		
17.	Standby power supply	N/A	N/A	N/A		
18.	Refuge Area	N/A	N/A			
	Total area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19.	Fire control room					
	Detector system panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	N/A	N/A	N/A		

Note:-General requirements for schools as per Director of Education circular dated 17/01/2005.

- 1. Escape route:- Clear
- 2. LPG cylinders in laboratories :- Nil
- 3. Electric wiring:- Conduit Wiring MCB and ELCB......
 Electric circuit- MCB Provided
- 4. Electric meter board / switch board panel.:-Not Under the staircase
- 5. Basement use as per BBL 1983 :- N/A
- 6. Emergency telephone no. board :- Displayed
- 7. Generator set: :- at the terrace

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2013/School/719 dated 19/08/2013 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

D. Q. (W)

Signature of the Inspecting Officer Name : Ashok Kumar Jaiswal

Designation : A.D.O. (Jwala Puri)

Pr. CFO (WZ) - E/L

CFO WZ LL ALOO N FT

[06] A FTIV E.T. is fout up bor segn- Sl.