## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1466

Dated: 22/6/18

## **FIRE SAFETY CERTIFICATE**

Certified that M/s. Hotel Kochar Continental located at 59/28,New Rohtak Road, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus four upper floors, using basement as hall/storage, ground floor as reception, office and one guest room, first, second & third floor each having 06 guest rooms and two rooms for personal use respectively, (total 19 guest rooms) and a pantry for staff with one staff room in temporary shed on fourth floor was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/NDZ/957 dated 09.06.2015. The premises was reinspected by the officer concerned of this department on 12/06/2018 in presence of Mr. Hari Singh Kochar (Owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 22/6/14 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 22 16 118 at New Delhi by.

(VIPEN KENTAL)
CHIEF FIRE OFFICER

## Copy to:-

- 1. Mr. Hari Singh Kochar (Owner), M/s. Hotel Kochar Continental 59/28,New Rohtak Road, Karol Bagh, New Delhi- 110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

## Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s. Hotel Kochar Continental 59/28, New Rohtak Road,

Karol Bagh, New Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2015/NDZ/957 dated 09.06.2015

5. Fire Safety directives letter No : Nil

6. Date of inspection : 12.06.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side : Sh. Hari Singh Kochar, owner

9. Year of Construction : 2006-07

10. Applicant's letter No. : Form 'J' dated nil

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 09.06.2015	Provided at site	Remarks MR/NMR				
1	Access to building							
3	Road width	06 mts	Provided	MR				
	Gate width	4.5 mts	Provided	MR				
	Width of internal road	N/A	N/A	N/A				
2	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases	_		-				
	Upper Floors	01	01	MR				
	Basements	01	01	MR being old case				
	b. Width of staircases	-		<del>-</del>				
	Upper Floors	Old Case	1.25 mts	MR being old case				
	Basements	Old Case	1.50 mts	MR being old case				
	c. Protection of exits	-	-	<u>-</u>				
	Fire check door	N/A	N/A	N/A				
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A				
	e. No. of continuous staircases to terrace	01	01	MR				
	g. Width of Corridor	1.0 mt	1.25 mts.	MR				
	h. Door Size	Old case	0.86 mts	MR being old case				
3	Compartmentation.							
	Fire check door	N/A	N/A	N/A				
	Sealing of electrical shafts	N/A	N/A	N/A				
	Fire Rating of shaft door	N/A	N/A	N/A				
	Water Curtain	N/A	N/A	N/A				
	Fire Dampers	N/A	N/A	N/A				
4	Smoke Management System.	ı						
a =	Basements	30 a/c per hour	Exhaust fan provided	MR				
	Upper floors	12 a/c per hour	Natural Ventilation	MR				
			1					

	Total numbers	15	Provided	MR		
	Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.	TTOVICCO				
	Total numbers on each floor	01	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	Required	D.G. set 62.5 KVA	MR		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.	1 - 20,1400				
	Basement	Required	Provided	MR		
## F	• Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants	,				
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A		N/A		
12	N/A					
12	Yard Hydrants.  • Total number of hydrants			g 31		
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	N/A	N/A	N/A		
13		N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level     Discharge of main Pump					
		N/A	N/A	N/A		
	pump	N/A	N/A	N/A		
	- thine of of main painps	N/A	N/A	N/A		
	ramp out put	N/A	N/A	N/A		
	panip nead	N/A	N/A	N/A		
	amp out put	N/A	N/A	N/A		
	surracy rump ricad	N/A	N/A	N/A		
	starting, ivialidal stopping	N/A	N/A	N/A		
	Tump House Heeess	N/A	N/A	N/A		
	Terrace level					

1	> He	ad of the pump	30 mts	30 mts each	MR			
	> Por	wer Supply	Required	Provided	MR			
	> Au	to Starting of pump	Required	Provided	MR			
14	Captive Water	·	, , , , , , , , , , , , , , , , , , , ,					
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>		N/A	N/A	N/A			
			N/A	N/A	N/A			
			N/A	N/A	N/A			
			N/A	N/A	N/A			
-			Old Case	5,000 lts	MR, old case			
15	Exit Signage.	Exit Signage.		Provided	MR			
16	Provision of L	vision of Lifts.						
10	• Pressur	ization of Lift Shaft	N/A	N/A	N/A			
	• Pressur	ization of Lift lobby	N/A	N/A	N/A			
	• Commi	unication In lift Car	Required	Provided	MR			
	• Firema	n's Grounding Switch	Required	Provided	MR			
	Lift Sig	nage	Required	Provided	MR			
17	Standby powe	Standby power supply		Provided	MR			
18	Refuge Area.							
	> Total A	rea	N/A	N/A	N/A			
	> Location		N/A	N/A	N/A			
19		ire Control Room						
IRE SE	• Detec	tor System Panel	N/A	N/A	N/A			
M	• Detec	Switch Panel	N/A	N/A	N/A			
5/6//	DA C	ystem Panel	N/A	N/A	N/A			
1032	Batter	ry backup	N/A	N/A	N/A			
Fire C		ing Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:		N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/NDZ/957 dated 09.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

670/DOCSW) 14.06.2018

Name M.K.CHATTOPADHYAY
Div. Officer (South West)

RAM