GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1438

Dated: 20 06 2018

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Star Palace located at 15A/17, WEA, Karol Bagh, New Delhi110005 comprised of basement, ground plus three upper floors, using basement as storage, ground floor as reception & shops, first & second each having 10 guest rooms respectively, third floor having 09 guest rooms (total 29 guest rooms) and two staff rooms with pantry on terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2014/SZ/1063 dated 22.08.2014. The premises was re-inspected by the officer concerned of this department on 11/06/2018 in presence of Sh. Subham, manager, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 2006 2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 20 06 2018 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Director, M/s. Hotel Star Palace, 15A/17, WEA, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s. Hotel Star Palace, 15A/17, WEA, Karol Bagh,

New Delhi- 110005

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2014/SZ/1063 dated 22.08.2014

5. Fire Safety directives letter No : Nil

6. Date of inspection : 11.06.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Sh. Subham, manager 9. Year of Construction : 1990-91

10. Applicant's letter No. : nil dated 17.05.2018

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	pr	Minimum Standards on fire evention and fire safety U/R 33	Fire safety arrangements as per letter di 22.08.2014		Remarks MR/NMR		
1	Access to building						
	•	Road width	06 mts	Provided	MR		
	•	Gate width	4.5 mts	Provided	MR		
	•	Width of internal road	N/A	N/A	N/A		
2	Numl	ber, Width, Type & Arrangem	ent of Exits	1071	IN/A		
	a. Nu	mber of staircases	-				
	•	Upper Floors	01	01	MR		
	•	Basements	01	01	MR being old case		
	b. Wic	Ith of staircases	- 01	-	with being old case		
	•	Upper Floors	OHC	1.25 mts	MD		
	•	Basements	Old Case	1.25 mts	MR being old case		
	c. Protection of exits		Old Case	1.25 IIIIS	MR being old case		
	•	Fire check door	-	4	<u> </u>		
	•	Pressurization	N/A	N/A	N/A		
	1	of continuous staircases to terrace	N/A	N/A	N/A		
		th of Corridor	01	01	MR		
- 1	h. Door		1.5 mts	1.5 mts.	MR		
		ertmentation.	Old case	0.79 mts	MR being old case		
				6			
		Fire check door	N/A	N/A	N/A		
		Sealing of electrical shafts	N/A	N/A	N/A		
	- 1	Fire Rating of shaft door	N/A	N/A	N/A		
		Water Curtain	N/A	N/A	N/A		
		Fire Dampers	N/A	N/A	N/A		
S	moke l	Management System.			A 11/4 %		
		Basements Inner flagge	30 a/c per hour	Exhaust fan provided	MR		
		Jpper floors	12 a/c per hour	Natural Ventilation	MR		

3	THE Extinguishers						
	Total numbers	15	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming						
•	Type of detectors	N/A	N/A	N/A			
8	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 62.5 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	• Basement	Required	Provided	MR			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants	2					
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	Auto Starting/ Manual stopping	ng N/A	N/A	N/A			
	Pump House Access	N/A	N/A	N/A			
	Terrace level	3 a 18					

26	Discharge of pump	450 LPM	450 LPM	MR			
S	Head of the pump	30 mts	30 mts each	MR			
	> Power Supply	Required	Provided	MR			
9	Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	 Underground tank capacity 	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inletAccess to tank	N/A	N/A	N/A			
		N/A	N/A 🌤	N/A			
	Overhead Tank capacity	Old Case	5,000 lts	MR, old case			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.		2. 2.				
	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
E SEA	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
5/6/10	PA System Panel	N/A	N/A	N/A			
1029	Battery backup	N/A	N/A	N/A			
Fire	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Note: All the shortcomings pointed out by this department vide letter No. F6/DFS/MS/GH/2018/SZ/1934 dated 10.05.2018 have been complied with by the guest house management.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/SZ/1063 dated 22.08.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

689/00/80

Name M.K. CHATTOPA DHYA Y