GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/Assembly/(UG)/SZ/2018/1461

Dated: 22/06/18

FIRE SAFETY CERTIFICATE

Certified that the INA Underground Metro Station of Line-7, comprising of Three Levels (Lower Concourse. Interchange/Platform Level & Concourse/Ground Level) was inspected by the officer concerned of this department on 13/06/2018 in the presence of Mr. Rajeev Saxena[Dy. CE (E&M)] and found that the said Metro Stationbuilding have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the premises is fit for occupancy class "Group D-7Assembly building" with effect from 22/06/18-2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 22/06/18 at New Delhi by.

(Vipin Kental) Chief Fire Officer Tel: 011-23412225

Copy to:-

- 1. The Sh. A. K. Singh, Executive Director/Electrical, Near Malviya Nagar Metro Station, Press Enclave Road, New Delhi-110017
- 2. Director Works, Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi-110001

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in/wps/wem/connect/doit/fire/FIRE/Home/Forms
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form** 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

INSPECTION REPORT 1. Name & address of the building : INA Underground Metro Station of Line-7 2. Type of Occupancy : Assembly- Group-"D" 3. Type of Case : New 4. Details of Previous NOC : NA 5. Fire Safety directives letter No : F6/DFS/MS/2013/2524 dated 12/11/2013 6. Date of inspection : 13/06/2018 7. Name of Inspecting Officer : A. K. Malik 8. Name and designation of officer from the building side : Mr. Rajeev Saxena [Dy. CE (E & M)] 9. Year of Construction : 2018 [Lower Concourse + Interchange/Platform Level + Concourse/Ground Level] 10. Applicant's letter No. : Form 'I' & outdoor diary no. 8006 dated 28/05/2018 S. No. Minimum Standards on fire prevention NFPA Provided at site Remarks and fire safety U/R 33 Requirement MR/NMR 1. Access to building Road width Required 10m MR Gate width NA 6m NA Width of internal road Approachable Abut on Road MR 2. Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors NA--NA--NA-1. Lower Concourse MR to Interchange Level (50%)- 1 Nos + 4 Escalator capacity of 2. Lower Concourse Basements Provided Escalators is to Platform - 3 Nos + counted for 4 Escalator evacuation in Platform NFPA) Concourse -3 Nos + 4 Escalator 4. Interchange Level to Ground Level Nos + 2 Escalator b. Width of staircases Upper Floor -NA--NA--NA-1. $3.2m + 1m \times 4$ MR Nos (Based on 2. 2.05m, 1.2m & 1.12m & 0.91m evacuation $1m + 1m \times 4 Nos$ Basements (maintenance calculation 3. 2m, 2m & 1m + staircase) submitted by 1m x 4 Nos DMRC as per $4.2.67m + 1m \times 2$ NFPA) Nos c. Protection of exits Fire check door Required Provided MR Required in Fireman Pressurization Staircase & Provided. MR Emergency Staircase d. No. of continuous staircases to terrace -NA--NA--NAe. Width of Corridor -NA--NA--NAf. Door Size 0.91m lm MR 3. Compartmentation Fire check door Required Provided MR Sealing of electrical shafts Required Provided MR Fire Rating of shaft door 30minute & 3 Hours Provided MR Water Curtain -NA--NA--NA-Fire Damners

	Basements	Required	Provided	MR
	• Upper floors	-NA-	-NA-	-NA-
5.	Fire Extinguishers			
	 Total numbers 	108 No's	108 No's	MR
	Types	ABC/W.CO2/CO2	32/08/68	MR
	 IS marking 	ISI marked	Yes	MR
6.	First-Aid Hose Reels	· · · · · · · · · · · · · · · · · · ·	1 03	IVIIC
	Total numbers on each floor	l No. in ancillary building, 09 Nos at		
	 Length of hose reel hose 	Concourse, 08 Nos at each Platform & 04 Nos at Interchange Level	Provided	MR
	Nozzle diameter	. 36m	Provided	MR
		6mm	Provided	MR
7.	Automatic fire detection and alarming s	system		1711(
	• Type of detectors	Smoke & Heat	Provided	MR
THE PARTY OF THE P	 Location of Main Panel 	Station Control Room	Provided	MR
	 Location of Repeater Panel 	Required	Fireman Staircase	MR
	 Alternate source of power 	Required	Provided	MR
	 Hooters' Location 	* All Area	Provided	
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	rrovided	MR
		Required in		
	 Basement 	following rooms:-		
			Provided	MR
		mess, store, security, locker		
	 Ground & Above Floor 	The second of the second of		
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants	-NA-	-NA-	-NA-
	Size of riser/down-comer	150		
	of tisel/down-comer	150mm 1 No. in ancillary	Provided	MR
		building. 09 Nos at	Provided	MR
	Number of hydrants per floor	Concourse, 08 Nos at each Platform & 04 Nos at Interchange Level		IVIIX
	Hose Box	l No. in ancillary building, 09 Nos at Concourse, 08 Nos at each Platform & 04 Nos	Provided	MR
		at Interchange Level		
12.	Yard Hydrants			
	 Total number of hydrants 	1 Nos	Provided	MR
	Hose Box	1 Nos at ancillary building & 1 Nos at	Provided	MR
13.	Pumping Arrangements	each tunnel portal		
	Ground Level			
	Discharge of main Pump	2020 1 124		
	➤ Head of Main pump	2839 LPM	Provided	MR
	Todd of Main pump	75m for Hydrant & 56m for Sprinkler	Provided	MR
	Number of main pumps	Two	Provided	MR
	 Jockey Pump out put 	2 x 189 LPM	Provided	MR .
	Jockey pump head	75m for Hydrant &	Provided	MR
	Standby Pump out put	56m for Sprinkler		
		2 x 2839 LPM(electric)	Provided	MR
	> Standby Pump Head	75m for Hydrant &	Provided	MR
	Auto Starting/Manual Stopping	56m for Sprinkler		

Γ		ound Metro Station of Line-7				
	Pump House Access	Required	Provided	MR		
	Terrace level					
	Discharge of pump	-NA-	-NA-	-NA-		
	Head of the pump	-NA-	-NA-	-NA-		
	Power Supply .	-NA-	-NA-	-NA-		
14.	Auto Starting of pump	-NA-	-NA-	-NA-		
17.	Captive Water Storage for fire fighting	g		and the same of th		
	 Underground tank capacity 	-NA-	-NA-	-NA-		
	 Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 	Required	Provided	MR		
		Required	Provided	MR		
		Required	Provided	MR		
15.		2 x 1,00,000 Lts	Provided	MR		
	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.			E E		
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	-NA-	-NA-	-NA-		
		-NA-	-NA-	'-NA-		
		Required	Provided	MR		
		Required	Provided	MR		
1.00		Required	Provided	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.					
	Total Area	-NA-	-NA-	N. A.		
	Location	-NA-	-NA-	-NA-		
19.	Fire Control Room	: 177	-NA-	-NA-		
20.	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 	Required in SCR	Provided	MR		
		Required	Provided			
		Required		MR		
			Provided	MR		
		Required	Provided	MR		
		Required .	Provided	MR		
<i>₩</i> () •		Clean Agent flooding system for	Provided local			
	Special Fire Protection System for Protection of special Risks, if any:	Electrical Panels & Transformer	application with NOVEC 1230	MR		
Th	e fire protection systems and it is	1 tailstorner	1230			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the above compliance of the minimum standards of fire prevention and fire safety measures as required under the rule 35 of the Delhi Fire Service Rules 2010, Fire Safety Certificate is recommended under rule 35(3).

Accordingly form "II" in shape of DFA is put up for approval under rule 35(4).

Signature of Inspecting Officer Name: A. K. Malik

Designation: DO (SD)

14/06/18 Dy. CFO (8%)