FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

F6/DFS/MS/2018/WZ/School/1447

Dated: 20 /06/2018

FIRE SAFETY CERTIFICATE

Certified that the Modern Public School, Located at BM – Block, Shalimar Bagh Delhi- 110088. comprised of Ground + 02 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2015/WZ/774 Dated- 15-05-2015 The premises was re inspected by the officer concerned of this department on 02-05-2018 in the presence of Sh. Ashish (Caretaker) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance DOE Circular No- 3298-3398 Dated-01/03/2011 and that the premises is fit for occupancy class "Educational" Group B(Except Temporary shed at terrace & Ground Floor) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... go lo. 6./1. g.... at New Delhi by.

Chief Fire Officer,
Delhi Fire Service

Copy to:

No.

- 1. The Principal, Modern Public School, BM Block, Shalimar Bagh Delhi- 110088.
- 2. Director of Education, Old Secretariat, Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Temporary shed at terrace and Ground Floor shall not be used for any purpose.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Modern Public School, Located at BM – Block, Shalimar Bagh Delhi- 110088.

2. Type of Occupancy: Educational (Ground + 2 Upper Floor) Except Temporary shed at terrace & Ground Floor)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2015/WZ/774 Dated- 15-05-2015

5. Fire Safety directives Letter No.: Cr.No- 3298-3398 Dated-01/03/2011

6. Date of inspection

: 02-5-2018

7. Name of the Inspecting Officer: Udaivir singh, ADO (WP)

No. of Students=2636 No. of class rooms=62

8. Name and designation of Officer

Plot area=2 acres

Covered area=54408sqf

from the building side :Sh. Ashish (Caretaker)

9. Year of Construction

: 1971

10. Applicant's letter No.

: MPS/2018/4222 Dated-25/04/2018

S No	Minimum standards on fire prevention and fire safety U/R 33	Cr.No. 3298- 3398 Dated- 01/03/2011	Provided at site	Remarks MR/NMR			
1.	Access of building		1				
	 Road width 	Accessible Provided > 09m		MR			
	 Gate width 	Accessible	Provided 370cm	MR			
	 Width of internal road 	NA	NA	NA			
2.	Number, width, Type & Arrangements of exits						
Section 2	a. Number of staircases						
	 Upper floors 	2	2 Provided	MR			
	 Basements 	NA	NA	NA			
	b. Width of staircases						
	 Upper floors 	2x1.5m	Provided	MR			
	• Basements	NA	NA	NA			
	c. Protection of exits						
	Fire check door	NA NA		NA			
	 Pressurization d. No of continuous 	NA	NA	NA			
	staircase to terrace e. Width Of Corridor f. Door Size	2	2 Provided				
		1.5m	210cm Provided	MR			
		1m 100cm		MR			

3.	Compartmentation							
	Fire check door	N	ΙA		NA	NA		
	 Sealing of electrical shafts 		NA NA				NA	
					NA	NA		
	 Fire Rating of shaft do 	0 40	A		NA	NA NA		
	Water Curtain		A		NA	NA NA		
	Fire Dampers	1,			1471	INA		
4.	Smoke managements System							
	Basements	N			NA	NA	•	
	• Upper floors	N	A		NA	NA		
5.	Fire Extinguishers							
	 Total numbers 		onos.		25 Provided	MR		
	• Types		BC & CO ₂		Provided	MR		
	IS marking	IS	SI marked		Provided	MR		
6.	First – Aid Hose Reels							
	Total numbers on each	02	2		Provided	MR		
	floor	30)m		Provided	MR		
	 Length of hose reel hos 	se 5n	nm		Provided	MR		
	 Nozzle diameter 							
7.	Automatic fire detection and alarming system							
	Type of detectors		NA		NA		NA	
	 Location of Main Panel 		NA		NA		NA	
	 Location of Repeater Pa 	anel	el NA		NA		NA	
	Alternate source of pow		NA	1	NA		NA	
	Hooters' Location		NA]	VA		NA	
8.	MOEFA		Required	+	Provided		MR	
9.	Public Address System		Required	_	Provided			
10.	Automatic Sprinkler System Required Provided MR							
	Basements	NA		NA	A		NA	
	 Upper Floor 	NA	A N		NA		NA	
	 Sprinkler above false ceiling 	NA		NA	NA		NA	
11.	Internal Hydrants:							
	Size of riser/down- comer		100 mm		Provided		ИR	
	 Number of hydrants per 	floor	02		Provided		ΛR	
	 Hose Box 		02		Provided	N	/IR	
12.	Yard Hydrants							
	 Total number of hydrants 	NA			Provided Provided		JA ,	
	Hose Box	NA					NA	
			i.					

13.	Pumpi	ing Arrangements:			1	
	•	Ground Level				
	•	Discharge of main	NA	NA		NA
		pump				
	>	Head of main pump	NA	NA		NA
	>	Number of main	NA	NA		NA
		pumps				
	>		NA	NA		NA
	>	V 1 1	NA	NA		NA
	>	a time of a time part	NA	NA		NA
	>	,	NA	NA		NA
	>	Auto Staring/Manual stopping	NA	NA		NA
	>	Pump House Access	NA	NA		NA
	•	Terrace level	11/1	TALI		1.1/1
	>	Discharge of pump	450 lpm &180	lnm	Provided	MR
	>	Head of the pump	40Mtr	Provi		MR
	>	Power supply	Required	Provi		MR
	>	Auto starting of pump	Required	Provi		MR
14.	Cantiv	ve water Storage for fire f		11011	uou	14117
11.	Captiv	Under ground tank	NA	NA		NA
		capacity	117	1 42 k		1 17 1
	>	Draw off connection	NA	NA		NA
	>		NA	NA		NA
	>	Access to tank	NA	NA		NA
	•	Overhead Tank	10,000Ltr		0 ltr provided	MR
		capacity) as as y as as assessment			
						- x
15	Exit S	ignage	Required	Provi	ded	MR
16.	Provis	ion of Lifts			2 N	
	>	Pressurization of Lift	NA	NA		NA
		Shaft				
	>	Pressurization of lift	NA	NA	•	NA
		lobby	NA	NA	_	NA
	>	Communication in lift	NA	NA	1	NA
		Car			, , Y	
	>	Fireman's Grounding	NA	NA		NA
		Switch				
1.77		Lift Signage	27.4	27.4		27.4
17.		by power supply	NA	NA		NA
18.	Refuge		NIA	214		27.4
		Total area	NA	NA		NA
10		Location	NA	NA		NA
19.		ontrol room	NIA	NT A		DIA
	A	Detector system panel	NA	NA		NA
		Flow Switch Panel	NA	NA		NA
	8	PA System Panel	NA	NA		NA
	197	Battery backup	NA	NA		NA
1 1		Building Floor Plans	NA	NA		NA

20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA	
	The fire protection sys found functional at the time of in the last of the deemed of the safety as required un F6/DFS/MS/2015/WZ/774 Dat Service Rules 2010 is recommendated by Signature of the Inspecting Off Name	nspection. compliance of m der the rules ed- 15-05-2015 inded.	inimum standards o the NOC issue renewal under rule	n fire preventiced vide letter	on and r no: ni Fire
	Designation ADO/WF		Designation		
à	- Dofla /ma	11/6/W			
	M	ett to	p5		
	AnolaP Sir	A1 15	Her 13	pol up	gra po
	Ple ?	12 s/6/10	Ž		
	Ple .7 (8/16/14				
	M				A DECEMBER OF THE PROPERTY OF