GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1436

Dated: 20 06 2018

FIRE SAFETY CERTIFICATE

Certified that M/s. Pitrashish Premium Guest House (A unit of Pitrashish Aashrya Pvt. Ltd.) located at 59/36,New Rohtak Road, Karol Bagh, New Delhi- 110005 comprised of basement, stilt, ground plus three upper floors, using basement as hall/storage, stilt floor as parking & reception, ground floor as 06 guest rooms & 01 store room, first, second & third floor each having 06 guest rooms respectively (total 24 guest rooms) was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/NDZ/971 dated 09.06.2015. The premises was re-inspected by the officer concerned of this department on 12/06/2018 in presence of Sh. Dinesh, manager and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 2006 2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 20 06 2018 at New Delhi by.

19/6, (VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. The Manager, M/s. Pitrashish Premium Guest House (A unit of Pitrashish Aashrya Pvt. Ltd.), 59/36, New Rohtak Road, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhi.govt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT 1. Name & address of the building : M/s. Pitrashish Premium Guest House (A unit of Pitrashish Aashrya Pvt. Ltd.), 59/36, New Rohtak Road, Karol Bagh, New Delhi- 110005. 2. Type of Occupancy : Lodging House 3. Type of Case : Renewal 4. Details of previous NOC : F6/DFS/MS/GH/2015/NDZ/971 dated 09.06.2015 5. Fire Safety directives letter No : Nil 6. Date of inspection : 12.06.2018 7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West) 8. Name and designation of officers from the building side : Sh. Dinesh Meena, manager 9. Year of Construction : Jan 2010 10. Applicant's letter No. : Form 'J' dated nil The said guest house is comprised of basement, stilt, ground plus three upper floors. S. Minimum Standards on fire Fire safety Remarks Provided at site No. arrangements as per prevention and fire safety U/R 33 MR/NMR letter dt. 09.06.2015

1	Acces	s to building						
	•	Road width	06 mts	Provided	MR			
	•	Gate width	4.5 mts	Provided	MR			
	•	Width of internal road	N/A	N/A	N/A			
2	Numb	er, Width, Type & Arrangeme	nt of Exits	•				
	a. Nun	nber of staircases	-		-			
	•	Upper Floors	01	01	MR			
	•	Basements	01	01	MR being old case			
	b. Wid	th of staircases	-		-			
	•	Upper Floors	1.25 mts	1.50 mts	MR			
	•	Basements	1.25 mts	1.50 mts	MR			
	c. Protection of exits		-		_			
	•	Fire check door	N/A	N/A	N/A			
	• ,	Pressurization	N/A	N/A	N/A			
	e. No. c	of continuous staircases to terrace	01	01	MR			
	g. Wid	th of Corridor	1.0 mt	1.28 mts.	MR			
	h. Door	Size	Old case	0.86 mts	MR being old case			
3	Compa	artmentation.						
	•	Fire check door	N/A	N/A	N/A			
	•	Sealing of electrical shafts	N/A	N/A	N/A			
	•	Fire Rating of shaft door	N/A	N/A	N/A			
	•	Water Curtain	N/A	N/A	N/A			
	•	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.							
	•	Basements	30 a/c per hour	Exhaust fan provided	MR			
	•	Upper floors	12 a/c per hour	Natural Ventilation	MR			

3	Fire Extinguishers		***						
	 Total numbers 	15	Provided	MR					
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR					
	IS marking	ISI marked	Provided	MR					
6	First-Aid Hose Reels.								
	 Total numbers on each floor 	01	Provided	MR					
	 Length of hose reel hose 	30 m	Provided	MR					
	Nozzle diameter	5 mm	Provided	MR					
7	Automatic fire detection and alarming								
	Type of detectors	N/A	N/A 🌭	N/A					
	Location of Main Panel	N/A	N/A	N/A					
	Location of Repeater Panel	N/A	N/A	N/A					
	Alternate source of power	Required	Provided	MR					
	Hooters' Location	N/A	N/A	N/A					
8	MOEFA	Required	Provided	MR					
9	Public Address System.	Required	Provided	MR					
10	Automatic Sprinkler System.								
	Basement	N/A	Provided	Area less than 200 sq. mts.					
	Upper Floor	N/A	N/A	N/A					
	Sprinkler above false ceiling	N/A	N/A	N/A					
11	Internal Hydrants								
	Size of riser/down-comer	N/A	N/A	N/A					
	Number of hydrants per floor	N/A	N/A	N/A					
	Hose Box	N/A	N/A	N/A					
12	Yard Hydrants.								
12	Total number of hydrants	N/A	N/A	N/A					
	Hose Box	N/A	N/A	N/A					
13	Pumping Arrangements.								
	Ground Level								
	> Discharge of main Pump	N/A	N/A	N/A					
	➤ Head of Main pump	N/A	N/A	N/A					
	> Number of main pumps	N/A	N/A	N/A					
	> Jockey Pump out put	N/A	N/A	N/A					
	Jockey pump head	N/A	N/A	N/A					
	Standby Pump out put	N/A	N/A	N/A					
	Standby Pump Head	N/A	N/A	N/A					
	> Auto Starting/ Manual stopp	oing N/A	N/A	N/A					
	Pump House Access	N/A	N/A	N/A					
	• Terrace level								
	Discharge of numn		ACO I DIA	MD					

		Head of the pump	T	30 mts	30 mts each	MR	
	Power Supply		-	Required	Provided	MR	
	7	Auto Starting of pump		Required	Provided	MR	
14	Captive Water Storage for fire fighting.						
	•	Underground tank capacity		N/A	N/A	N/A	
	>	Draw-off connection	N/A		N/A	N/A	
		Fire service inlet		N/A	N/A	N/A	
	>	> Access to tank		N/A	N/A	N/A	
	•	Overhead Tank capacity			5,000 lts	MR, old case	
15	Exit Si	gnage.	Re	quired	Provided	MR	
16							
3	•	Pressurization of Lift Shaft	, , ,	N/A	N/A	N/A	
	•	Pressurization of Lift lobby		N/A	N/A	N/A	
_	•	Communication In lift Car	Re	quired	Provided	MR	
	•	Fireman's Grounding Switch	Re	quired	Provided	MR	
	•	Lift Signage		quired	Provided	MR	
17	Standl	y power supply	Re	quired	Provided	MR	
18	Refuge Area.						
	>	Total Area		N/A	N/A	N/A	
	>	Location		N/A	N/A	N/A	
19	Fire C	ontrol Room					
RESE	RAICE	Detector System Panel		N/A	N/A	N/A	
	(Em)	Flow Switch Panel		N/A	N/A	N/A	
STATI	8 2	PA System Panel		N/A	N/A	N/A	
1026	43/	Battery backup		N/A	N/A	N/A	
Fire	•	Building Floor Plans		N/A	N/A	N/A	
20		Fire Protection Systems for on of special Risks, if any:		N/A	N/A	N/A	

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/NDZ/971 dated 09.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

14.06.18

DCFQ(SZ)

Name M.K.CHATTOPADHYAY
Div. Officer (South West)