## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS; DELHI FIRE SERVICE, NEW DELHI-110001.

No.F6/DFS/MS/Hospital/2018/ SZ

Dated: 08/06//8

## FIRE SAFETY CERTIFICATE

(Vipin Kental) Chief Fire Officer

Copy to:-

1. The Authorized Signatory, M/s. Aakash Healthcare Super Specialty Hospital, Sector-3, Dwarka, New Delhi.

2. The Jt. Director (L&I), DDA, Vikas Sadan, INA, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. 06 mts. wide access road all around the building shall be kept free at all the time for fire tender movement in case of any emergency.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. Basement shall be used as per the building bye laws.
- 8. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 10. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

ADO Durka

	<u> </u>	NSPECTION REPO	ORT			
1	Name & address of the building		or Aakash Healthcare Pv	/t. Ltd.		
2	Type of Occupancy		3, Dwarka, New Delhi.			
			asements + Ground + s	ervice floor		
3	Type of case	+ seven upper Flo				
4 5	Details of previous NOC  Fire safety directives letter No	Nil F6/DES/MS/RD/H	ospital/2017/279 dated 1	0.0.2017		
6	Date of inspection	07.06.2018	ospital/2017/219 dated 1	9.9.2017		
7	Name of the inspecting Officers :	M K Chattopadhyay DO (SW) & Satpal Bhardwaj ADO (Dwarka)				
8	Name and designation of officers from the building side	Sharma (Chief Eng	a (Admn.Manager) Sh. F gineer)	Rajinder		
9	Year of construction	2017				
10	Applicant's letter No.	AHPL/Admin./Lette	er/2018/041 dated 28-05	-2018		
		seven upper Flo		ce floor +		
. NO.	Minimum Standards on fire prevention and fire safety U/R 33	Requirements As per NBC/recommenda		Remarks MR / NM		
1	Access to building		T			
	1) Road width	12 Meters	provided	MR		
	2) Gate width	4.5 Mtrs.	6 Mtrs.	MR		
	3) Width of internal road	6 Mtrs.	Provided	MR		
2	Number, width Type & arrangema. Number of staircases	ent of exits		T		
	Upper floors	5 Nos.	Provided	MR		
	2. basements b. Width of staircase	6 Nos. + 1 Ramp	Provided	MR		
	1. Upper floors	2 Mtrs. each	2 Mtrs. Each	MR		
	2. basements	2 Mtrs. each & Ramp	2 Mtrs. each + Ramp	MR		
	c. Protection of exits					
	1. Fire check door	Required	Provided	MR		
	2. Pressurization	Required	Provided	M/R		
	d. No. of continuous staircase to terrace	6 Nos.	Provided	MR		
	e. Width of corridor	2.40 Mtrs.	Provided	MR		
	f. Door size	patient rooms:1.25, 1.50, & 2 Mtrs.	Provided	MR		
3	Compartmentation.  1. Fire check door	Description		1		
		Required	Provided	MR		
	2. Sealing of electrical shafts	Required	Sealed	MR		
	3. Fire Rating of shaft door	2 Hours rating	Provided	MR		
	4. water curtain	Required in basement	Provided	MR		
	5. Fire dampers	Required	Provided	MR		
4	Smoke Management system.	00.40.01				
	basement	30 AC Change 12 AC Change	Provided Provided	MR		
5	upper floors Fire Extinguishers		Tovided	MR		
	total numbers	As per IS	52 Nos.	MR		
	Types	CO2 & ABC	Provided	MR		
	ISI marking					
6		Required	Provided	MR		
	First-Aid Hose Reels.					
	Total numbers on each floor	2 Nos.	Provided	MR		
	Length of Hose reel hose	30 M	Provided	MR		
	Length of Hose reel flose	30 W	1 TOVIGOU	IVII		

4125

	7			MIN				
-	7	Automatic fire detection an	nd alar	ming system				
		Type of detectors		Smoke / Heat		Provided		MR
		location of Main Panel		Basement Floo	or-1	Provided		MR
		location of Repeater panel		Required		All Levels		MR
		Alternate source of power		Required		Provided		MR
	0	hooter's location		Appropriate Plac	ces	Near stairs at each f	loor	-
	•	MOEFA		Required		Provided		MR
		Public Address System.		Required		Provided		MR
1		Automatic Sprinkler System						
	- 1	pasement		Required		Provided		MR
		upper floors	I	Required		Provided		MR
1		sprinkler above false ceiling	F	Required		Provided		MR
-	- 1	nternal Hydrants						
	- 1	Size of riser/down-corner	1	50 mm		Provided		MR
	1	lumber of Hydrants per floor	2	No.		2 No.		MR
12		ose Box	2	No.	2	2 No.		MR
12	1	ard Hydrants.						
	- 1	tal number of hydrants	6	Nos.	6	Nos.		MR
40		ose box	6	Nos.	6	Nos.		MR
13	-	umping arrangements						1
		Ground level					T	
	1	Discharge of main Pump	28	350 LPM	Р	rovided		MR
	1	Head of main pump	70	Mtrs.	Р	rovided		ИR
	1	Number of main pumps	2	Nos.	Р	rovided		/IR
	d.j	ockey pump out put	18	30 LPM (2 Nos	.) Pi	rovided		/IR
	e.j	ockey pump head		Mtrs.		ovided		1R
	f. S	Standby Pump output	Cur	tain pump 900		ovided		1R
		Stanby Pump head		Mtrs.	D	o vielent	+	
	1	outo Starting/Manual stopping		quired		ovided	1	IR
	1	ump house access		quired		ovided		IR
	1	errace level	110	quireu	IPI	ovided	M	R
	a. E	Discharge of pump	N/A	\	N/A	A	N/	/A
- 1		ead of the pump	N/A	1	N/A	1	N/	
		ower supply	N/A		N/A		N/	
	d. A	uto starting of pump	N/A		N/A		N/	
14	Cap	tive water storage for fire					1.4/	
		nderground tank capacity	2 00	0000 Ltrs.	Dre	vido d	1	
	1	raw-off connection				vided	MF	
	b. fir	e service inlet				vided	MF	
	c.Ac	cess to tank					MF	
	Over	head tank Capacity				vided	MR	
5	1	Signage.	Requ			vided	MR	
6		ision of lifts.	1.1041	СС	-10/	rided	MR	
		essurization of lift shaft	Requ	uired .	Dre	iida d		
		essurization of lift lobby	Requ			· · · · · · · · · · · · · · · · · · ·	MR	
		mmunication in lift car	Requ				MR	
- 1		eman's grounding switch					MR	
- 1		signage	Requ		Provi		MR	
		390	Requ	ired P	rovi	ded	ИR	

17				T
	Standby power supply	Required	DG Set 500 KVA	MR
18	Refuge Area.			
	total area	Required	105 m2 (approx).	MR
	location	5th floor	Provided	MR
19	Fire control room			
	a. Detector system Panel	Required	Provided	MR
	b. Flow switch Panel	Required	Provided	MR
	c. PA system Panel	Required	Provided	MR
	d. Battery backup	Required	Provided	MR
	e. Building floor plans	Required	Provided	MR
20	Special Fire Protection System for Protection of special Risks,	Required	CO2 Flooding System in HT & LT Panels	MR

ire protection systems provided in the building were checked/Tested and found functional at the time of inspection. The shortcomings issued vide letters dated 6.2.2018, 31.05.2018 found rectified Keeping in view compliance of the minimum standarards on fire prevention & fire safety requirements under the rules, grant of Fire Safety Certificate is recommended under Rule 35 of the Delhi Fire Service Act 2007 &

Accordingly DFA is put up for approval and signature please.

M K Chattopadhyay Divisonal officer (SW)

335/00/SW

DCFo (SZ

Sir, f. T. letter is pud-op for your Kind and sognetive pleans

miscell legto

1481)c(20182 - C. G.O (SZ) /