## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. P6 OF5 ms 2018/W2/1234
FIRE SAFETY CERTIFICATE

Dated: 2// /2018

Certified that M/s Zeenat ( A unity of AAA Hospitality) located at Kh. No. 73/15, 72/11, 72/12, 72/13, Village Alipur, Main G.T.K. Road, Delhi-110036 comprised of Basement, Ground & one upper floor owned / occupied by M/s Zeenat ( A unity of AAA Hospitality) was issued fire safety certificate vide Letter no. F6/DFS/MS/Motel/2015/WZ/246 Dated 20/02/2015. The premise was reinspected by the officer concerned of this department on 15.05.2018 in the presence of Sh. Abhinav Seth and observed that all the fire prevention and fire safety arrangements as provided in the premise found in good working condition. The premise have therefore deemed complied with the requirements under rule 33 of the Delhi Fire Service Rules, 2010 and the building premise is fit for occupancy under "Class Residential and Assembly Buildings" with effect from ....... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010,

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.
- 9. This FSC is valid for exiting pucca structure /building as earlier approved by this department.

Issued on .... 25/5/18..... at New Delhi by

Chief Fire Officer Ph-011-23414250

Copy to:

- 1. The Joint Commissioner of Police (Lic), 1<sup>st</sup> floor, Police station, Defense Colony, New Delhi for
- 2. M/s Zeenat ( A unity of AAA Hospitality) Kh. No. 73/15, Main G T Karnal Road, Delhi-110036

## **INSPECTION REPORT**

Name & address of the building :M/s Zeenat Motel Building, Kh. No. 73/15, 72/11, 72/12, 72/13,

Village Alipur, Main G.T.K. Road, Delhi-110036.

2 Type of Occupancy :As

:Assembly (Residential ) Basement, Ground & One upper floor : Renewal

3 Type of Case : Renewa

4 Details of previous NOC : F6/DFS/MS/Motel/2015/WZ/246 dated 20/02/2015

5 Fire Safety directives letter No : F6/MS/DFS/BP/GH/2006/3693 dated 19/12/2006

6 Date of inspection :16.05.2018

7 Name of the Inspecting Officers : ADO (RN)

8 Name and designation of officers

from the building side : Sh. Abhinav Seth

9. Year of Construction : 2006

10. Applicant's letter No. : Dairy No. 5904 dated 12.04.2018

Minim	num Standards on fire prevention and fire safety U/R 33	NBC/ BBL Requirement	Provided at site	Remarks MR/NMR	
Access	to building		·		
•	Road width	06m	09m	MR	
•	Gate width	05m	05m	MR	
•	Width of internal road	NA	NA	NA	
Number, Width, Type & Arrangement of Exits					
a. Number of staircases					
	Upper Floors	- 03	04	MR	
•	Basements	05	03	Meeting travel Distance requirement as per NBC-part-4	
b. Widt	h of staircases		· · · · · · · · · · · · · · · · · · ·	40 001 1100 0	
•	Upper Floors	1.25 m each	1.25m each	MR	
•	Basements	1.25 m each	1.25m each	MR	
c. Prote	ection of exits	1.25 m each	1.23111 cdc11	1,111	
•	Fire check door	Required	Provided	MR	
•	Pressurization	NA	NA	NA	
d. No.	of continuous staircases to terrace	NA	NA	NA	
e. Widt	th of Corridor	NA	NA	NA	
f. Door		1.0m for guest room Banquet- 2.00 m each	Provided	MR	

	Fire check door	~		A		
		Required	Provided	MR		
	Sealing of electrical shafts	Required	Provided	MR		
	• Fire Rating of shaft door	Required	Provided	MR		
	<ul><li>Water Curtain</li><li>Fire Dampers</li></ul>	NA	NA	NA		
		NA	NA	NA		
4	Smoke Management System.					
	• Basements	30 a/c per hour	Exhaust fan	MR		
	• Upper floors	12 a/c per hour	Natural Ventilated	MR		
5	Fire Extinguishers					
	Total numbers	32nos	32 nos	MR		
	• Types	ABC & Co2	ABC/W.Co2	MR		
	ISI marking	Yes	Yes	MR		
5	First-Aid Hose Reels.					
	Total numbers on each floor	02	02	MR		
	• Length of hose reel hose	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	Smoke /Heat	Provided	MR		
	Location of Main Panel	G.F.	Provided	MR		
	Location of Repeater Panel	NA	NA	NA		
	Alternate source of power	Required	Provided	MR		
	Hooters' Location	Required	Provided	MR		
	MOEFA	Required	Provided	MR		
)	Public Address System.  Automatic Sprinkler System.	Required	Provided	MR		
	• Basement	Required	Provided	MR		
	• Upper Floor	Required	Provided	MR		
	<ul> <li>Sprinkler above false ceiling</li> </ul>	NA		1		

•	Size of riser/down-comer	150mm	Provided	MR		
•	Number of hydrants per floor	02	Provided	MR		
•	Hose Box	02	Provided	MR		
Yard H	Yard Hydrants.					
•	Total number of hydrants	06	Provided	MR		
•	Hose Box	06	Provided	MR		
Pumpi	ng Arrangements.					
•	Ground Level			18		
	> Discharge of main Pump	1620 lpm	2280 lpm	MR		
	<ul><li>Head of Main pump</li></ul>	40m	Provided	MR		
	Number of main pumps	2	Provided	MR		
	<ul><li>Jockey Pump out put</li><li>Jockey pump head</li></ul>	180 lpm	Provided	MR		
	Standby Pump out put	40 m	Provided	MR		
	Standby Pump Head	1620 lpm	2280 lpm	MR		
	<ul><li>Auto Starting/ Manual stopping</li><li>Pump House Access</li></ul>	Required	Provided	MR		
	Terrace level	Required	Provided	MR		
	<ul><li>Discharge of pump</li></ul>		5			
	Head of the pump	NA	900 lpm	NA		
	> Power Supply	NA	NA	NA		
	> Auto Starting of pump	NA	NA	NA		
		NA	NA	NA		
Captive Water Storage for fire fighting.						
•	Underground tank capacity	1,00,000 ltr.	Provided	MR		
->		Required	Provided	MR		
>		Required	Provided	MR		
7		Required	Provided	MR		
	Overhead Tank capacity	10,000 ltr	10,000 ltr.	MR		
Exit	Signage.	Required	Provided	MR		
Provision of Lifts.						
1100		Required	Provided	MR		
•	Pressurization of Lift Shaft Pressurization of Lift lobby	Required	Provided	MR		



	<ul> <li>Communication In lift Car</li> </ul>	D		
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
		Required	Provided	1
17	Standby power supply	Required	Provided	MR
18	Refuge Area.		- To vided	MR
	> Total Area			4.
	Location	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
1)	The Control Room			
	Detector System Panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel     Batter backup	NA	NA	NA
	Butter backup	NA	NA	
	Building Floor Plans		N. S. (1997)	NA
0.	Special Fire Protection Systems for	NA	NA	NA
	Protection of special Risks, if any:	NA	NA	NA
	Protection of special Risks, if any:	NA	NA	N/

The fire protection systems provided in the building were tested/ checked randomly and found in good working conditions. The observations/ shortcomings issued and communicated vide this department letter of even no. 1054 dated 14.03.2018 have been compiled by the management.

Keeping in view of the satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. 246 dated 20.02.2015 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name: - Rajesh Kumar

Designation:- ADO/RN

As approved, F.T. letter in but for your signature Pl 1/4