GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001 NO. F6/DFS/MS/CNG/2018/SZ/ 1225

Dated: 24/5/18

FIRE SAFETY CERTIFICATE

Certified that the CNG Filling Station (IGL) at Sector-09, Dwarka, New Delhi-110075, comprised of ground floor only was issued fire safety certificate by this department vide letter no. F6/DFS/MS/CNG/2015/SZ/343 dated 13.03.2015. The said premises was re-inspected by the officer concerned of this department on 04.05.2018 in presence of Sh. Pushpendra Sharma (Addl. Manager- Fire & Safety) & Sh. Dalip Kumar Station Manager and found that the premises have deemed complied with fire prevention & fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules 2010 and that the building is fit for occupancy of CNG Filling Station with effect from ... Tyl 518 ... for a period of three years, subject to compliance of the conditions printed overleaf.

Issued on 24/5/18 at New Delhi by

(Vipin Kental)

Copy to:-

1. Sh. Alok Sharma, Chief General Manager Fire & Safety IGL Bhawan, Plot No.4, Community Centre, R K Puram, Sector-9, New Delhi.

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT						
1	Name & address of the building M/s CNG Station (IGL) Sector-20, Dwarka, New Delhi.					
2	Type of Occupancy	Group J: Hazardous (CNG Filling Station)				
3	Type of case	Renewal				
4	Details of previous NOC	F6/DFS/MS/CNG/2015/SZ/412 dated 20.03.2015				
5	Fire safety directives letter No	OISD-179/ letter dated 24.9.2007				
6	Date of inspection	04.05.2018				
7	Name of the inspecting Officers	ADO S.P Bhardwaj (Dwarka)				
8	Name and designation of officers	Sh. Pushpendra Sharma (Addl. Manager-F&S) and				
Commence	from the building side	Sh. Pradeep (Station Manager)				
9	Year of construction	2007				
10	Applicant's letter No.	IGL/F&S/2018/15/75/ 01 dated 07.02.2018	Ground & First Floor			
S. NO.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement/ OISD-179/ Letter Dated 24.9.2007	Provided at site	Remarks MR / NMR		
1	Access to building	0.11	CO Mtro	MR		
	1) Road width	9 Mtr	60 Mtrs.			
	2) Gate width	4.5 Mtrs.	Direct accessible from road	MR		
The Control of the Co	3) Width of internal road	N/A	N/A	N/A		
2	Number, width Type & arrangeme	nt of exits				
and the state of t	a. Number of staircases					
	1. Upper floors	Required	1 Nos.	MR		
	2. basements	N/A	N/A	N/A		
1	b. Width of staircase					
	1. Upper floors	.98 Mtr.	1.25 Mtrs.	MR		
	2. basements	N/A	N/A	MR		
	c. Protection of exits		N1/0	N/A		
	1. Fire check door	N/A	N/A N/A	N/A		
	2. Pressurization	N/A				
	d. No. of continuous staircase to	Required	Provided as per plan	MR		
200	e. Width of corridor	N/A	N/A	N/A		
	f. Door size	1 Mtr	1.25 Mtrs.	MR		
3	Compartmentation.		N1/A	N/A		
	1. Fire check door	N/A	N/A N/A	N/A		
	2. Sealing of electrical shafts	N/A N/A	N/A N/A	N/A		
	3. Fire Rating of shaft door	N/A N/A	N/A	N/A		
	4. water curtain 5. Fire dampers	N/A	N/A	N/A		
4	Smoke Management system.		•			
	basement		N/A	N/A		
react) pro-		12 a/c per hour	7	147		
-	upper floors		Natural Ventilation	MR		
5	Fire Extinguishers	14 Nos.	37 Nos.	MR		
	total numbers	14 1105.	0, 1100.			
de constante de la constante d	Types	Co2, DCP	Co2 4.5 Kg. (8Nos.) DCP Trolly of 75 Kgs.(11Nos.), DCP10 Kgs.(18 Nos.)	MR		
			Provided	MR		
	ISI marking	Required	Provided	IVIIX		

		N19	il faith	
6	First-Aid Hose Reels.		NI/A	N/A
	total numbers on each floor	N/A	N/A	
and the same of th	Length of Hose reel hose	N/A	N/A	N/A
	Nozzle Diameter	N/A	N/A	N/A
7	Automatic fire detection and alarm	ning system		
a a		Gas and Flame	Provided in Compressor	MR
and man more and	Type of detectors	Detectors	Package	
demand and	location of Main Panel	N/A	N/A	N/A
•		N/A	N/A	N/A
C. Carlotte	location of Repeater panel	N/A	N/A	N/A
and the second	Alternate source of power	N/A	N/A	N/A
The second second	hooter's location	Required	Provided	MR
8	MOEFA Public Address System	N/A	N/A	N/A
9	Public Address System.	TWE		The second secon
10	Automatic Sprinkler System. basement	N/A	N/A	N/A
	upper floors	N/A	N/A	N/A
-	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-corner	N/A	N/A	N/A
a way and a man	Number of Hydrants per floor	N/A	N/A	N/A
		N/A	N/A	N/A
	Hose Box	IWA		
12	Yard Hydrants. Total number of hydrants	N/A	N/A	N/A
	Hose box	N/A	N/A	N/A
13				
10	1. Ground level/			
-	a. Discharge of main Pump	N/A	N/A	N/A
	b.Head of main pump	N/A	N/A	N/A
and an arrange of the second	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/A	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A N/A
	g.Stanby Pump head	N/A	N/A N/A	N/A N/A
	h.Auto Starting/Manual stopping	N/A N/A	N/A N/A	N/A
	pump house access	IV/A	IVIFY	
	2.Terrace level	NI/A	N/A	N/A
	a. Discharge of pump	N/A	N/A	N/A
	b. head of the pump	N/A	N/A N/A	N/A
Tana Para San San San San San San San San San Sa	c. Power supply	N/A		N/A
	d. Auto starting of pump	N/A	N/A	1477
14	Captive water storage for fire			
17	fighting	N1/A	N/A	N/A
	1. Underground tank capacity	N/A	N/A N/A	N/A
	a. Draw-off connection	N/A	N/A N/A	N/A
	b. fire service inlet	N/A	N/A N/A	N/A
	c.Access to tank	N/A	N/A	N/A
-	Over head tank Capacity	N/A		
15	Exit Signage.	Required No smoking boards	Provided	MR
16	Provision of lifts.		N1/A	N/A
	a. Pressurization of lift shaft	N/A	N/A	
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	N/A	N/A	N/A
	d. Fireman's grounding switch	N/A	N/A	N/A
and the state of t		N/A	N/A	N/A
The same	e. Lift signage			

d. Fireman's grounding switch
e. Lift signage

NIC							
17	Standby power supply	Required	GG Set (25 KVA)	MR			
18	Refuge Area.		Not Required				
	total area	N/A	N/A	N/A			
	location	N/A	N/A	N/A			
19	Fire control room						
19	a. Detector system Panel	N/A	N/A	N/A			
	b. Flow switch Panel	· N/A	N/A	N/A			
		N/A	N/A	N/A			
	c. PA system Panel		N/A	N/A			
	d. Batter backup	N/A					
	e. Building floor plans	N/A	N/A	N/A			
20	Special Fire Protection systems CNG cascade protection and Auto 02 nos. of Water mist cum foam tr	actuated CO2 flooding sycolley in dispenser area for	ystem for CNG compressor pr r fire fighting is provided.	MR			
The fire protection systems provided in the building were checked and found functional at the time of inspection. Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety requirement as per OISD-179, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/CNG/2015/SZ/412 dated 20.3.2015 is recommended.							
1		p for approval and signat	ure please.				
	Accordingly DFA is put of	p for approval and signat	S.P Bhardwaj ADO (DWARKA	12118			
201 DOCED 15/5/18 201 DOCED 15/05/18							
2	Deta(s2) Land La	ell the 1875 is put up of miscell le 23	er Stanatu plu. Smr 18	21/8-			