GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ /22/

Dated: 24/5/18

FIRE SAFETY CERTIFICATE

Issued on 2415/18 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Jagiri Lal (Owner), M/s. Hotel De-Gold, 3505/6, Bank Street, Karol Bagh, New Delhi- 05.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

: M/s. Hotel De-Gold, 3505/6, Bank Street, Karol Bagh, New Delhi- 05.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2014/SZ/1532 dated 09.12.2014

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 21.05.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Murari Tiwari, manager

9. Year of Construction

: Before 2008

10. Applicant's letter No.

: 1337/Addl C.P/Lic(H) dated New Delhi the 23.02.2018

The said guest house is comprised of basement, ground plus three upper floors.

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | Fire safety arrangements as per letter dt. 09.12.2014 | Provided at site | Remarks MR/NMR | | | |
|-----------|---|--|----------------------|-------------------|--|--|--|
| 1 | Access to building | | | | | | |
| | Road width | 06 mts | Provided | MR | | | |
| | Gate width | 4.5 mts | Provided | MR | | | |
| | Width of internal road | N/A | N/A | N/A | | | |
| 2 | Number, Width, Type & Arrangement of Exits | | | | | | |
| | a. Number of staircases | _ | - . | | | | |
| | Upper Floors | 01 | 01 | MR | | | |
| | Basements | 01 | 01 | MR being old case | | | |
| | b. Width of staircases | - | - | | | | |
| | Upper Floors | Old Case | 1.23-1.25 mts | MR being old case | | | |
| | Basements | Old Case | 1.10 mts | MR being old case | | | |
| | c. Protection of exits | - | - N | - | | | |
| | • Fire check door | N/A | N/A | N/A | | | |
| | Pressurization | N/A | N/A | N/A | | | |
| | e. No. of continuous staircases to terrace | 01 | 01 | MR | | | |
| | g. Width of Corridor | 1.0 mt. | 1.45 mts. | MR | | | |
| | h. Door Size | Old case | 0.88 mts | MR being old case | | | |
| 3 | Compartmentation. | 5 | | | | | |
| | Fire check door | N/A | N/A | N/A | | | |
| | Sealing of electrical shafts | N/A | Sealed | | | | |
| | Fire Rating of shaft door | N/A | N/A | N/A | | | |
| | Water Curtain | N/A | N/A | N/A | | | |
| | Fire Dampers | N/A | N/A | N/A | | | |
| 4 | Smoke Management System. | | | | | | |
| × | Basements | 30 a/c per hour | Exhaust fan provided | MR | | | |

| | • Opper Hoors | 12 a/c per nour | Natural Ventilation | MR | |
|----|---|---|---------------------|-----|--|
| 5 | Fire Extinguishers | | | | |
| | Total numbers | 15 | Provided | MR | |
| | • Types | CO ₂ , ABC, WCO ₂ | Provided | MR | |
| | IS marking | ISI marked | Provided | MR | |
| 6 | First-Aid Hose Reels. | | 9 | | |
| | Total numbers on each floor | 01 | Provided | MR | |
| | Length of hose reel hose | 30 m | Provided | MR | |
| | Nozzle diameter | 5 mm | Provided | MR | |
| 7 | Automatic fire detection and alarming system. | | | | |
| | Type of detectors | N/A | N/A | N/A | |
| | Location of Main Panel | N/A | N/A | N/A | |
| | Location of Repeater Panel | N/A | N/A | N/A | |
| | Alternate source of power | Required | D.G. set 25 KVA | MR | |
| | Hooters' Location | N/A | N/A | N/A | |
| 8 | MOEFA | Required | Provided | MR | |
| 9 | Public Address System. | Required | Provided | MR | |
| 8 | Automatic Sprinkler System. | | | | |
| | Basement | Required | Provided | MR | |
| 7. | Upper Floor | N/A | N/A | N/A | |
| | Sprinkler above false ceiling | N/A | N/A | N/A | |
| 11 | Internal Hydrants | | | | |
| | Size of riser/down-comer | N/A | N/A | N/A | |
| | Number of hydrants per floor | N/A | N/A | N/A | |
| | Hose Box | N/A | N/A | N/A | |
| 12 | Yard Hydrants. | | | | |
| | Total number of hydrants | N/A | N/A | N/A | |
| | Hose Box | N/A | N/A | N/A | |
| 13 | Pumping Arrangements. | | | | |
| | Ground Level | | | | |
| | Discharge of main Pump | N/A | N/A | N/A | |
| | Head of Main pump | N/A | N/A | N/A | |
| | Number of main pumps | N/A | N/A | N/A | |
| | Jockey Pump out put | N/A | N/A | N/A | |
| | Jockey pump head | N/A | N/A | N/A | |
| | Standby Pump out put | N/A | N/A | N/A | |
| | Standby Pump Head | N/A | N/A | N/A | |
| | Auto Starting/ Manual stopping | g N/A | N/A | N/A | |
| | Pump House Access | N/A | N/A | N/A | |

| 1 | Terrace level | 450 LPM | 450 LPM | MR |
|------|--|----------|-------------|--------------|
| | Discharge of pump | 30 mts | 30 mts each | MR |
| | Head of the pump | Required | Provided | MR |
| | Power SupplyAuto Starting of pump | Required | Provided | MR |
| 4 (| Captive Water Storage for fire fightin | g. | | |
| | Underground tank capacity | N/A | N/A | N/A |
| | > Draw-off connection | N/A | N/A | N/A |
| | Fire service inlet | N/A | N/A | N/A |
| | Access to tank | N/A | N/A | N/A |
| | Overhead Tank capacity | Old Case | 5,000 lts | MR, old case |
| 15 | Exit Signage. | Required | Provided | MR |
| | Provision of Lifts. | | | |
| | Pressurization of Lift Shaft | N/A | N/A | N/A |
| | Pressurization of Lift lobby | N/A | N/A | N/A |
| | Communication In lift Car | Required | Provided | MR |
| 1 | Fireman's Grounding Switch | Required | Provided | MR |
| | Lift Signage | Required | Provided | MR |
| 17 | Standby power supply | Required | Provided | MR |
| 18 | Refuge Area. | | | |
| | Total Area | N/A | N/A | N/A |
| | Location | N/A | N/A | N/A |
| 19 | Fire Control Room | | 8 | |
| | Day of Gartana Damal | N/A | N/A | N/A |
| SERV | Flow Switch Panel | N/A | N/A | N/A |
| 1 | PA System Panel | N/A | N/A | N/A |
| 718 | Battery backup | Required | Provided | MR |
| | Building Floor Plans | N/A | N/A | N/A |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | N/A | N/A | N/A |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/SZ/1532 dated 09.12.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

310/20/80

Name M.K.CHATTOPADHYAY
Div. Officer (South West)