

No. F6/DFS/MS/GH/SZ/2018/ /187

Dated:

23/5/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Good Times located at 8/7, WEA, Karol Bagh, New Delhi110005 is comprised of basement, ground plus four upper floors, using basement as hall/storage, ground floor as reception, lobby & 06 guest rooms, first, second & third floor each having 09 guest rooms respectively (total 33 guest rooms) and a pantry for staff with office on fourth floor, was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2015/SZ/522 dated 13.04.2015. The premises was re-inspected by the officer concerned of this department on 14.05.2018 in presence of Sh. Ravinder Singh (General Manager), and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23 of sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 23/5/18 at New Delhi by.

(VIPEN KENTAL)
CHIEF FIRE OFFICER
92-451

Copy to:-

- 1. Sh. Ravinder Singh (General Manager), M/s. Hotel Good Times, 8/7, WEA, Karol Bagh, New Delhi- 110005.
- 2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s Hotel Good Times, 8/7, WEA, Karol Bagh, New Delhi. 2. Type of Occupancy

: Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2015/SZ/522 dated 13.04.2015

5. Fire Safety directives letter No : N/A.

6. Date of inspection : 14.05.2018

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

from the building side : Sh. Ravinder Singh, General Manager

9. Year of Construction : Before 2003

Applicant's letter No.	: Before 2003		
The said guest house is comprised of base	: nil dated 24.04.	2018	
No. prevention and fire safety U/R 3	dan cille	No	Remarks
1 Access to building	2		MR/NMR
Road width	06 mts	Provided	
Gate width	4.5 mts		MR
Width of internal road	N/A	Breetly accessi	ble MR
Number, Width, Type & Arrange	ment of Evita	N/A	N/A
a. Number of staircases	Exits		
Upper Floors	01	Dravid 101	-
Basements	01	Provided(01)	MR
b. Width of staircases	-	Provided(02)	MR
 Upper Floors 	1.25 mts	1.32 mts.	_
• Basements	Old Case	1.26mts, 0.75 mt.	MR
c. Protection of exits	_	- 1.20mts, 0.75 mt.	MR being old case
• Fire check door	N/A	NI/A	_
• Pressurization	N/A	N/A N/A	N/A
e. No. of continuous staircases to	0 01	01	N/A
g. Width of Corridor		01	MR
h. Door Size	Old Case	1.15 mts	MR being all
Compartmentation.	1.0 mt.	Provided (0.89 mt.)	MR being old case MR being old case
		,	omg old case
The check door	N/A	N/A	NI/A
seaming of electrical shafts	N/A	N/A	N/A
Fire Rating of shaft doorWater Curtain	N/A		N/A
• Fire Dampers	N/A	N/A	N/A
	N/A	N/A N/A	N/A
Smoke Management System.		IWA	N/A
Basements	30 a/c per hour	Exhaust fan Provided	
Upper floors	12 a/c per hour	Natural ventilation	
Fire Extinguishers			MR

	 Total numbers 	12	Tiovided						
	• Types	CO ₂ , ABC type	Provided	MR					
	• IS marking ISI marked Provided		MR						
6	First-Aid Hose Reels.								
	Total numbers on each floor	01	Provided	MR					
	 Length of hose reel hose 	30 m	Provided	MR					
	 Nozzle diameter 	5 mm	Provided	MR					
7	Automatic fire detection and alarming system.								
7		N/A	N/A	N/A					
	Type of detectorsLocation of Main Panel	N/A	N/A	N/A					
		N/A	N/A	N/A					
	Location of Repeater Panel	N/A	N/A	N/A					
	Alternate source of powerHooters' Location	N/A	N/A	N/A					
			Provided	MR					
8	MOEFA	Required	Provided	MR					
9	Public Address System.	Required	Flovided	IVIIC					
10	Automatic Sprinkler System.		D '1-1	MR					
	Basement	Required	Provided	IVIK					
	Upper Floor	N/A	N/A	N/A					
	Sprinkler above false ceiling	N/A	N/A	N/A					
11	Internal Hydrants	*							
11	Size of riser/down-comer	N/A	N/A	N/A					
	 Number of hydrants per floor 	N/A	N/A	N/A					
	Hose Box	N/A	N/A	N/A					
12									
12	Yard Hydrants.Total number of hydrants	N/A	N/A	N/A					
	Hose Box	N/A	N/A	N/A					
13	Pumping Arrangements.	١							
13	Ground Level								
	Discharge of main Pump	N/A	N/A	N/A					
		N/A	N/A	N/A					
	Head of Main pumpNumber of main pumps	N/A	N/A	N/A					
	Jockey Pump out put	N/A	N/A	N/A					
	Jockey pump head	N/A	N/A	N/A					
	Standby Pump out put	N/A	N/A	N/A					
	Standby Pump Head	N/A	N/A	N/A					
	> Auto Starting/ Manual stopping	N/A	N/A	N/A					
	> Pump House Access	N/A	N/A	N/A					
	Terrace level								
	Discharge of pump	450 LPM	Provided	MR					

		► Head of the pump	30 mts	Provided	MR			
4		Power Supply	Required	Provided	MR			
		> Auto Starting of pump	Required	Provided	MR			
14	Capti	ve Water Storage for fire fightin	ıg.	_				
	•	Underground tank capacity	N/A	N/A	N/A			
	>	Draw-off connection	N/A	N/A	N/A			
	>	Fire service inlet	N/A	N/A	N/A			
	>	Access to tank	N/A	N/A	N/A			
	•	Overhead Tank capacity	5000 lts	Provided	MR			
15	Exit	Signage.	Required	Provided	MR			
16	Provision of Lifts.							
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
_	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	Required	Provided	MR			
	•	Fireman's Grounding Switch	Required	Provided	MR			
	•	Lift Signage	Required	Provided	MR			
17	Stand	by power supply	Required	Provided	MR			
18	Refug	Refuge Area.						
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19	Fire C	ontrol Room						
DE SEA		Detector System Panel	N/A	N/A	N/A			
	(m).	Flow Switch Panel	N/A	N/A	N/A			
3-5-18) *J.	PA System Panel	N/A	N/A	N/A			
19	\J	Battery backup	Required	Provided	MR			
of Fire S	•	Building Floor Plans	N/A	N/A	N/A			
20	_	I Fire Protection Systems for tion of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/522 dated 13.04.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

390/DOCAO) OU-15/05/18

danf

M.K. CHATTOPADHYAY Divisional Officer (South West)

100-1