## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1182

Dated: 23/5/(8

## FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Harjas Palace located at 5/43, W.E.A, Karol Bagh, New Delhi110005 comprised of basement, ground plus two upper floors, using basement as hall/storage & bank locker, ground floor as reception, offices & bank branch, first & second floor each having 10 guest rooms respectively (total 20 guest rooms) and one staff room with one store on terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/416 dated 23.03.2015. The premises was re-inspected by the officer concerned of this department on 14.05.2018 in presence of Sh. Lovender Pal Singh, manager of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 22 18 18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23 star at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

P

1. The Manager, M/s. Hotel Harjas Palace, 5/43, W.E.A, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

## Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building

: M/s. Hotel Harjas Palace, 5/43, W.E.A, Karol Bagh,

New Delhi- 05

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2015/SZ/416 dated 23.03.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 14-05-2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Lovender Pal Singh, manger

9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 259/Addl. C.P./Lic (H) dated New Delhi the 22.02.2018

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt.	Provided at site	Remarks MR/NMR
1	_	23.03.2015		
1	Access to building	06 mts	Provided	MR
	Road width	4.5 mts	Provided	MR
	Gate width Width of internal road	N/A	N/A	N/A
2			IV/A	1771
2	Number, Width, Type & Arrangemen	It Of Exits		
	a. Number of staircases	01	01	MR, Old Case
	• Upper Floors	01	01	MR, Old Case
	Basements	01	_	
	b. Width of staircases	-	1.13 mts.	MR being old case
	• Upper Floors	Old case	1.20 mts.	MR being old case
	Basements	Old case	-	
	c. Protection of exits	N/A	>T/A	N/A
	• Fire check door		N/A	905 d 1000000 9000
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	Old Case	1.42 mts	MR
	h. Door Size	Old case	0.77 mts	MR being old case
3	Compartmentation.			
	Fire check door	N/A	N/A	N/A
	Sealing of electrical shafts	N/A	Sealed	
	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A
4	Smoke Management System.			
	D	20 a/a per hour	Exhaust fan provided	MR

	• Total numbers	12	Provided	Mĸ
	Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.			IVIIC
	Total numbers on each floor	01	Provided	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarmin	g system.	-	
	Type of detectors	N/A	N/A	N/A
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A
	Alternate source of power	Required	D.G. set 15 KVA	MR
	Hooters' Location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	• Basement	Required	Provided	MR
	• Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.	IVA	IN/A	11///
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stopping	N/A	N/A	N/A
	<ul><li>Pump House Access</li></ul>	N/A	N/A	N/A
- No.	Terrace level			
	Discharge of pump	450 LPM	Provided	MR
	► Head of the pump	30 mts	Provided	MR

1							
10	Power Supply	Required	Provided	MR			
B	Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	➤ Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	Old Case	5,000 lts	MR being old case			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19 Fire Control Room							
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/416 dated 23.03.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

M.K. CHATTOPADHYAY Divisional Officer (South West)

290/DOCSIO) CH. 15/05/18