GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1185

Dated: 23/5/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Karat- 87 Inn located at 18/19, WEA, Karol Bagh, New Delhi110005 is comprised of basement, ground plus three upper floors, using basement as hall, ground floor as reception, offices & 04 guest rooms, first & second floor each having 09 guest rooms respectively, third floor having 07 guest rooms (total 29 guest rooms), was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2015/SZ/862 dated 28.05.2015. The premises was re-inspected by the officer concerned of this department on 14.05.2018 in presence of Sh. Ussain (Manager), and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23/5/18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 23/5/8 at New Delhi by.

(VIPEN KENTAL)
CHIEF FIRE OFFICER

Copy to:-

- 1. Sh. Vijay Kumar (owner), M/s. Hotel Karat- 87 Inn, 18/19, WEA, Karol Bagh, New Delhi-110005.
- 2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: M/s Hotel Karat-87 Inn, 18/19, WEA, Karol Bagh, New Delhi.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2015/SZ/862 dated 28.05.2015

5. Fire Safety directives letter No : N/A.

6. Date of inspection

: 14.05.2018

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

from the building side

: Sh. Ussain, Manager

9. Year of Construction

: Before 2009

10. Applicant's letter No.

: 1586/Addl. C.P./Lic (H) dated New Delhi the 21.03.2018

S. No.		inimum Standards on fire ention and fire safety U/R 33	Requirement as per letter No 28.05.2015	Provided at site	Remarks MR/NMR		
1	Access to building						
	•	Road width	06 mts	Provided	MR		
	•	Gate width	4.5 mts	Directly accessible	MR		
	•	Width of internal road	N/A	N/A	N/A		
2	Numl	oer, Width, Type & Arrangemo	ent of Exits		ē 0		
	a. Nu	mber of staircases	-	-	_		
	•	Upper Floors	01	Provided(01)	MR		
	•	Basements	01	Provided(01)	MR		
	b. Wi	dth of staircases	-	-	· _		
	•	Upper Floors	1.25 mts	1.25 mts.	MR		
	•	Basements	Old Case	1.19 mts	MR being old case		
	c. Pro	tection of exits	-	-	: A =		
	•	Fire check door	N/A	N/A	N/A		
	•	Pressurization	N/A	N/A	N/A		
	e. No.	of continuous staircases to terrace	01	01	MR		
	g. Wi	lth of Corridor	Old Case	1.33 mts	MR being old case		
	h. Do	or Size	1.0 mt.	Provided (0.89 mt.)	MR being old case		
3	Comp	partmentation.					
	•	Fire check door	N/A	N/A	N/A		
		Sealing of electrical shafts	N/A	Sealed			
	•	Fire Rating of shaft door	N/A	N/A	N/A		
	•	Water Curtain	N/A	N/A	N/A		
	•	Fire Dampers	N/A	N/A	N/A		
4	Smok	moke Management System.					
	•	Basements	30 a/c per hour	Exhaust fan Provide	d MR		
	•	Upper floors	12 a/c per hour	Natural ventilation	MR		
5	Fire F	xtinguishers					

	Total Hallious		11011404	MIC	
	• Types	CO ₂ , ABC type	Provided	MR 🤿	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	01	Provided	MR	
	 Length of hose reel hose 	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming	g system.			
	Type of detectors	N/A	N/A	N/A	
	 Location of Main Panel 	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	Required	Provided (125 KVA)	MR	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.				
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.	3			
	Ground Level				
	Discharge of main Pump	N/A	N/A	N/A	
	► Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	> Jockey Pump out put	N/A	N/A	N/A	
	> Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
	> Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level Disaberge of nump				
	> Discharge of pump	450 LPM	Provided	MR	

	► Head of the pump	30 mts	Provided	MR			
	> Power Supply	Required	Provided	MR			
	➤ Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	• Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	5000 lts	Provided	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	• Lift Signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	Total Area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room						
The state of the s	Detector System Panel	N/A	N/A	N/A			
T	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
5-18	Battery backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/862 dated 28.05.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

285/DOCEW) 15/05/2018

100

FIM.

M.K. CHATTOPADHYAY Divisional Officer (South West)