GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 183

Dated: 23/5/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Marble Arch located at 8/6, W.E.A, Pusa Lane, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus two upper floors, using basement as hall, ground floor as reception, pantry, offices & 05 rooms for personal use, first & second floor each having 11 guest rooms respectively (total 22 guest rooms) was granted FSC by this department vide letter No. F6/DFS/MS/GH/2014/SZ/1064 dated 22.08.2014. The premises was re-inspected by the officer concerned of this department on 14.05.2018 in presence of Sh. Dashrath Goswami, manager of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23/5/8 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23/5/18 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

A

- 1. Mohd. Saalim Qureshi S/o Sh. Haji Mohd. Yusuf (owner), M/s. Hotel Marble Arch, 8/6, W.E.A, Pusa Lane, Karol Bagh, New Delhi- 110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Marble Arch, 8/6, W.E.A, Pusa Lane, Karol

Bagh, New Delhi- 05

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2014/SZ/1064 dated 22.08.2014

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 14-05-2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Dashrath Goswami, manger

9. Year of Construction

: 2009-10

10. Applicant's letter No.

: nil dated 27.03.2018

The said guest house is comprised of basement, ground plus two upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 22.08.2014	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06 mts	Provided	MR			
	Gate width		Directly accessible	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	-	-,	-			
	Upper Floors	02	02	MR			
	Basements	02	02	MR			
	b. Width of staircases	-	-	- 1			
	Upper Floors	Old case	1.48, 0.90 mts.	MR being old case			
	Basements	Old case	1.48, 1.60 mts.	MR being old case			
	c. Protection of exits	-	-, -	_			
	Fire check door	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A	N/A			
	e. No. of continuous staircases to	01	02	MR			
	g. Width of Corridor	N/A	N/A	N/A			
	h. Door Size	Old case	0.80 mts	MR being old case			
3	Compartmentation.						
	• Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	Sealed				
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						

	Dubements	1	provided				
	Upper floors	12 a/c per hour	Natural Ventilation	MR			
5	Fire Extinguishers	-					
	Total numbers	20	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	Heat & Smoke				
	Location of Main Panel	N/A	Staircase				
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	D.G. set 200 KVA	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box			20 00 0000			
		N/A	N/A	N/A			
12	Yard Hydrants.			27/4			
	• Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps Lookey Pump out put	N/A	N/A	N/A			
	Jockey Pump out putJockey pump head	N/A	N/A	N/A			
	Standby Pump out put	N/A	N/A	N/A			
	Standby Pump Head	N/A	N/A	N/A			
	Standoy I unip Head	N/A	N/A	N/A			

= gr	>	Auto Starting/ Manual stopping	N/A	N/A	N/A		
	>		N/A	N/A	N/A		
	•	Terrace level					
)	Discharge of pump	900 LPM	Provided	MR		
	-)	Head of the pump	30 mts	Provided	MR		
)	Power Supply	Required	Provided	MR		
)	Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for fire fighting.						
	•	Underground tank capacity	N/A	N/A	N/A		
	>	Draw-off connection	N/A	N/A	N/A		
	>	Fire service inlet	N/A	N/A	N/A		
	>	Access to tank	N/A	N/A	N/A		
	•	Overhead Tank capacity	10,000 lts	10,000 lts	MR		
15	Exit S	ignage.	Required	Provided	MR		
16	Provision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A		
	•	Pressurization of Lift lobby	N/A	N/A	N/A		
	•	Communication In lift Car	Required	Provided	MR		
	•	Fireman's Grounding Switch	Required	Provided	MR		
	•	Lift Signage	Required	Provided	MR		
17	Stand	by power supply	Required	Provided	MR		
18	Refuge Area.						
	>	Total Area	N/A	N/A	N/A		
	>	Location	N/A	N/A	N/A		
19	Fire Control Room						
E GA		Detector System Panel	N/A	N/A	N/A		
		Flow Switch Panel	N/A	N/A	N/A		
(-1)	*	PA System Panel	N/A	N/A	N/A		
19	9.	Battery backup	Required	Provided	MR		
Tira C		Building Floor Plans	N/A	N/A	N/A		
20		Il Fire Protection Systems for tion of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/1064 dated 22.08.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Note: - All the shortcomings issued by this department vide letter no. F.6/DFS/MS/SZ/2018/162 dated

12.01.2018 have been complied with by the management.

DFA is put up for approval & signature please.

MK CHATTOPADHYAY