FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

Possesses schoolsnown/ 1161

Dated: 22/5/18

FIRE SAFETY CERTIFICATE

Certified that the building of Blooming Buds Public School Located at 1st & 2nd Floor, B-Block, New Moti Nagar, New Delhi - 110027 in a building comprised {One Block = Ground (Religious function) + 03 Upper Floors, owned and occupied by Blooming Buds Public School have complied with the fire prevention and fire safety requirements in accordance with the Circular No-F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by the Director of Education/ NBC Part IV and verified by the officers concerned of Fire Service on 30-05-2014 in the presence of Miss. Rashmi Gandhi (Principal) and that the building / premises is fit for the occupancy class "Educational" Group B Sub Division B – 1 with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. Issued on251.5.118..... at New Delhi.

Chief Fire officer Delhi Fire Service.

Copy to:-

- 1. The Principal, Blooming Buds Public School, B- Block, New Moti Nagar, New Delhi 110027.
- 2. Director of Education, Old Secretariat, Delhi-110054

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per building bye laws.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 9. 3rd floor shall not be used for any purpose.

INSPECTION REPORT

1. Name & address of the building: Blooming Buds Public School, Located at, 1st & 2nd Floor, B- Block, New Moti Nagar, New Delhi – 110027.

2. Type of Occupancy: Educational {One Block = Ground (Religious function), 1st & 2nd Floors(For School) }

Type of Case

: New

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-11

6. Date of inspection

: 01-05-2018

Area of School -4250 sqf

7. Name of the Inspecting Officer: Udai vir Singh, ADO (WP)

Covered Area -4250sqf

Class Rooms - 14

8. Name and designation of Officer

Total Students - 409

from the building side

: Miss. Rashmi Gandhi (Principal)

9. Year of Construction

1967

10. Applicant's letter No. : BBPS/B-37/JAN./2018/2011dated 20-03-2018

0	1 1 1 6	DOE 20	200	Provided at	Remar	1
S	Minimum standards on fi	ACCEPTAGE OF THE PARTY OF THE P	298- ated 1-3-	site	MR/N	
No	prevention and fire safety	11	iled 1-3-	Site	IVIROINI	VIK
1.	Access of building	11		4		
1.	Road width	Accessi	ihle	7 m Provided MR		
	Gate width	Accessi		On Road	MR	
			ibic	NA	NA	
	Width of internal	Toda .		INA	IVA	4 1
2.	Number, width, Type & A	Arrangements of	exits			
	a. Number of stairca	ses		*		The second
	 Upper floors 	1		Provided	MR	li .
	 Basements 	NA		NA	NA	
	b. Width of staircase	es				
	 Upper floors 	1.5m,		cm (Up to 3rd F		MR
				5cm(Up to 1 st F)		
				8cm(1 st to 2 nd F)	
	 Basements 	NA	NA	, "		NA
	c. Protection of exits	5				
	 Fire check door 	NA		NA	NA	
	 Pressurization 	NA		NA	NA	
	d. No of continuous staircase to terrace	Require	ed	Provided	MR	
	e. Width Of Corrido	r 1.5 m		160cm	MR	
	f. Door Size	1 m		101cmProvide	d MR	
				_		
	>					

3.	Compartmentation			
	Fire check door	NA	NA	NA
	 Sealing of electrical shafts 	NA	NA	NA
	 Fire Rating of shaft door 	NA	NA	NA
	 Water Curtain 	NA	NA	NA
	 Fire Dampers 	NA	NA	NA
4.	Smoke managements System			
	Basements	NA	· NA	NA
	 Upper floors 	NA	NA	NA
5.	Fire Extinguishers			9
	Total numbers	7 nos.	8 Provided	MR
	 Types 	ABC, CO_2	Provided	MR
	 IS marking 	ISI marked	Provided	MR
6.	First – Aid Hose Reels		1	
	 Total numbers on each floor 	1	Provided	MR
	 Length of hose reel hose 	30m	Provided	MR
	 Nozzle diameter 	5mm	Provided	MR
7.	Automatic fire detection and alar	ming system		
	 Type of detectors 	NA	NA	NA
	 Location of Main Panel 	NA	NA	NA
	 Location of Repeater Panel 	NA	NA .	NA
	 Alternate source of power 	NA	NA	NA
	 Hooters' Location 	NA	NA	NA
8.	MOEFA	NA	NA	NA
9.	Public Address System	NA	NA	NA
10.	Automatic Sprinkler System			
	Basements	NA	NA	NA
	 Upper Floor 	NA	NA	NA
	 Sprinkler above false ceiling 	NA	NA	NA
11.	Internal Hydrants:	1		
	Size of riser/down- comer	100 inm	Provided	NA
	 Number of hydrants per floor 	· MA	Provided	NA
	Hose Box	RequiredMA	provided	NA
12.	Yard Hydrants			
	Total number of hydrants	NA	NA	NA
	Hose Box	NA	NA	NA

13.	Pump	Pumping Arrangements:							
	Ground Level								
	•	Discharge of main	NA			NA NA			
		pump	NA	A		NA	NA		
	>		NA			NA	NA		
	>					No. Sec. Str.	1 17 1		
	>	1 1	NA	NA		NA	NA		
	>	 Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual stopping Pump House Access 		NA NA NA NA		NA	NA NA NA		
	>					NA			
	>					NA			
	>					NA NA			
							1 1/1 1		
,	>					NA NA			
3	•	Terrace level					1 12 2		
1	>	Discharge of pump	450) lpm	Pro	vided		MR	
)	>	Head of the pump	40			vided		MR	
	>	Power supply		quired	_	vided		MR	
		Auto starting of pump		quired	Provided			MR	
14.	Captiv	ve water Storage for fire fig						1411	
	Under ground tank			NA NA		NA	NA		
Name of Street		capacity					INA		
	>	Draw off connection	NA	NA		NA NA			
	>	Fire service inlet	NA NA		NA	NA NA			
	>	Access to tank			NA				
	•	Overhead Tank capacity		00 Litres	. 4	5,000 litres	MR		
		- · · · · · · · · · · · · · · · · · · ·	,,,,	oo Eme	,	Provided	IVIIC		
15	Exit S	ignage	Required			Provided	MR		
16.	Provis	ion of Lifts		1		TTOVIGUE	IVIIC		
		 Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage 		y NA ar NA		NA	NA	2	
						NA	NA NA NA		
						NA			
						NA			
						NA NA			
17.		y power supply		NA		NA	NA		
18.		e Area							
		Total area		NA	e	NA	NA		
		Location		NA		NA	NA		
19.	Fire co	ontrol room					28		
		Detector system panel	NA			NA	NA		
		Flow Switch Panel	NA			NA	NA		
		PA System Panel	NA			NA	NA		
				NA		NA	NA		
		Building Floor Plans	NA			NA	NA		
						**	1471		
		y .							
		*							

O. Special Fire Protection Systems for Protection of special Risks, if any;		NA	NA
The fire protection syst	nspection. ostantial com- pired under the	pliance of the mi	nimum standards on fire ommended to grant Fire crvice Rules 2010/issue serial numbers
Signature of the Inspecting Office	cer	Signature	of the Inspecting Officer
Name Udas Vir Designation ADO/Wf	Boluly	Name	
Designation ADO WF		Designat	ion
CAO WEST MISIK		1/8	
MONTH SIT	FP 1	etter i	s fulupdum
CFQ /A	9/2/18		