## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ / | 42

Dated: 181518

## **FIRE SAFETY CERTIFICATE**

Certified that the P.G. International Guest House located at 3990-3989-91, 3219, School Wali Gali, Sangatrashan, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + lobby), 1st floor to 3rd floor (09 guest rooms at each floor), total 27 guest rooms owned/occupied by P.G. International Guest House was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/735 dated 12/05/15. The premise was re-inspected by the officer concerned of this department on 03/05/18 in the presence of Sh. Sunil (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 27 guest rooms only with effect from -1-8/-5/18-----for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1624/Addl./C.P./Lic. (H) dated 03/04/18.
- 2. The Manager,

P.G. International Guest House at 3990-3989-91, 3219, School Wali Gali, Sangatrashan, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		-	-	-	
INSP	ECTI	ON	RF	PO	RT

1. Name & address of the building

P.G. International Guest House at 3990-3989-91, 3219, School Wali Gali,

Sangatrashan, Pahar Ganj, New Delhi.

2. Type of occupancy:-

Residential, Sub Division-A-1 Gr. + 03 Upper floors (total 27 Guest rooms)

Ground floor (Reception + lobby), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (09 guest rooms at each floor)

3. Type of case:-

4. Details of previous FSC:-

Renewal No. F6/DFS/MS/EH/2015/NDZ/735 dated 12/05/15.

5. Fire safety directives No.-

6. Date of inspection:-

03/05/18 7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10 Applicant's letter No

N/A

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Sunil (Manager)

2007

_ 10.	Applicant's letter No:-	1624/Addl.	C.P./Lic. (H) date	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Old Case Remarks MR/NMR
i.	Access to Building			
	1) Road width	N/A	06 mtr.	N/A
	2) Gate width	N/A	N/A	N/A
	3) Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Ar	rangement of Ex	rits	IVA
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			1 1/71
	1. Upper floors	0.80 mtr.	1.15 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	01 mtr.	01 mtr.	MR
3.	Compartmentation		or mu.	IVIIX
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) hire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
<b>-</b> ↓.	Smoke Management System	-		14/74
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural	MR
5.	Fire Extinguishers			1.117
	1) Total numbers	08 Nos.	08 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR

6.	First-Aid Hose Reel			MD
	1) Total number of eachfloor	01	01	MR MR
	2) Length of hose reel hose	30	30	MR
	3) Nozzle diameter	5 mm	5 mm	IVIK
7.	Automatic Fire Detection &	Alarming Syst	tem	N/A
THE RESERVE OF THE PERSON NAMED IN COLUMN TWO	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	MR
8.	MOEFA	Required	Provided	
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			NI/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants	-1	27/4	N/A
	1) Size of riser/down-comer	N/A	N/A	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TWO
	2) Number of hydrants per	N/A	N/A	N/A
	floor		27/4	N/A
	3) Hose box	N/A	N/A	IN/A
12.	Yard Hydrants		21/4	N/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	IN/A
13.	Pumping Arrangement		27/4	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	IN/A
	pump	27/4	N/A	N/A
	b) Head of main pump	N/A	N/A N/A	N/A
	e) Number of main pum			N/A
	d) Jockey pump out put	N/A	N/A N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu		N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manua	I N/A	IN/A	
	stopping			)
	2) Terrace level	220 LPM	220 LPM	MR
	a) Discharge of pump	30 mtr.	30 mtr.	MR
	b) Head of pump	Required	Provided	MR
	e) Power supply			MR
	d) Auto starting of pum			V12
14.	Captive Water Storage for	N/A	N/A	N/A
	1) Under ground tank	18/7	1 3/1 8	
	capacity	n N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	e) Access to tank	1 1 / / 1	1 1/1 1	

331

	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	e) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
~	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
2().	Special Fire Protection Syst Risk, if any:	tem for Protec	ction of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2015/NDZ/735 dated 12/05/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO(NDZ)

F.O - miscel

F7/81.

FJ. littes

is pull up.

69 M

a CalNDA) mscell 1475