GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/

Dated :-- 16 /05/17

FIRE SAFETY CERTIFICATE

Issued -- 16 05 // at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Ashwani Lodge Guest House at 8696-99, D.B.G. Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Ashwani Lodge Guest House at 8696-99, D.B.G. Road, Pahar Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

B+Gr. + 04 Upper floors (total 15 Guest rooms)
Basement (Storage), Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (04 guest rooms + 01 store room at each floor) and 4th floor (01 guest room

+ 01 manager room + 01 staff room)

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer from the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Renewal No. F6/DFS/MS/EH/2015/NDZ/675 dated

01/05/15.

N/A 09/05/18

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Vinod (Manager)

1983

Nil dated 25/04/2018.

10.	Applicant's letter No:-	Nil dated 23	5/04/2018.	Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	18 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arra	angement of E	xits			
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	01 Nos.	01 Nos.	MR		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.35 mtr.	MR		
	2. Basements	0.80 mtr.	0.80 mtr.	MR		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	01 mtr.	01 mtr.	MR		
3.	Compartmentation			5		
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		

Fire Extinguishers 1) Total numbers 2) Types 3) ISI marking	12 Nos. ABC & CO2	12 Nos. ABC & CO2	MR		
2) Types 3) ISI marking	100 W W 17 W				
3) ISI marking		ADC & COZ	MR		
	Required	Provided	MR		
First-Aid Hose Reel	1				
1) Total number of eachfloor	01	01	MR		
2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
3) Nozzle diameter	05 mm	05 mm	MR		
1) Type of detectors	N/A	N/A	N/A		
2) Location of main panel	N/A	N/A	N/A		
3) Location of repeater panel	N/A	N/A	N/A		
4) Alternate source of power	N/A	N/A	N/A		
5) Hooter's Location	N/A	N/A	N/A		
MOEFA	Required	Provided	MR		
		Provided	MR		
	1				
1) Basement	Required	Provided	MR		
,	N/A	N/A	N/A		
	N/A	N/A	N/A		
		V V			
1) Size of riser/down-comer	N/A	N/A	N/A		
2) Number of hydrants per	N/A	N/A	N/A		
floor		¥	2		
3) Hose box	N/A	N/A	N/A		
1) Total number of hydrants	N/A	N/A	N/A		
2) Hose box	N/A	N/A	N/A		
Pumping Arrangement					
1) Ground level	N/A	N/A	N/A		
a) Discharge of main	N/A	N/A	N/A		
pump		- 8			
b) Head of main pump	N/A	N/A	N/A		
c) Number of main pump	N/A	N/A	N/A		
d) Jockey pump out put	N/A	N/A	N/A		
e) Jockey pump head	N/A	N/A	N/A		
f) Stand by pump output	N/A	N/A	N/A		
g) Stand by pump head	N/A	N/A	N/A		
h) Auto starting/Manual	N/A	N/A	N/A		
stopping					
2) Terrace level			Proceedings		
a) Discharge of pump	225 LPM •	225 LPM	MR		
b) Head of pump	30 mtr.	30 mtr.	MR		
c) Power supply	Required	Provided	MR		
d) Auto starting of pump	Required	Provided	MR		
	1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump out put e) Jockey pump head f) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location N/A MOEFA Required Public Address System Required Automatic Sprinkler System 1) Basement 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer Altoward Hydrants 1) Size of riser/down-comer 3) Hose box N/A Yard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level A) Discharge of main pump b) Head of main pump Location N/A N/A Pumping Arrangement A) Jockey pump out put C) Number of main pump A) N/A A) Jockey pump out put A) Jockey pump head A) Jockey pump head A) Auto starting/Manual stopping A) Terrace level A) Discharge of pump A) Head of pump B) Head of pump B) Head of pump A) Required	2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location N/A		

m

14.	Captive Water Storage for	Fire Fighting		
× .	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	27/4
-	b) Fire service inlet	N/A	N/A N/A	N/A
	c) Access to tank	N/A	N/A N/A	N/A
	d) Over head tank	5000 ltr.		N/A
	capacity	3000 itr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1	11011464	IVIIC
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2015/NDZ/675 dated 01/05/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO(NDZ)

C. F.O. m. sight Witts.

F.T. Letter is put up-