GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F.6/DFS/MS/School/2018/NDZ/

Dated:/6/5/18

FIRE SAFETY CERTIFICATE

Issued on.....at New Delhi by

(Vipin Kental) Chief Fire Officer

of

To.

The Manager
M/s Green Vales School,
3.5 Pusta, Main Road,
Delhi -53.

Copy to:-

The Dy. Director of Education, B–Block, Yamuna Vihar, Delhi-110053.

- Conditions -

- 1 All the means of escape shall be kept free of all type of obstruction all the time.
- 2 All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. "The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry"

1. Name & address of the building: Green Vales School, 3.5 Pusta, Main Road, D-53.

2. Building is comprised of

Ground plus one upper floor only

3. Type of Occupancy

Educational

4. Type of Case

: Renewal

5. Details of Previous FSC letter

: F.6/DFS/MS/2009/3221 Dated 04/11/09 Old requirement (Circular No. 262-362 dated17/01/05)

6. Fire Safety circular No

: 11/04/18

7. Date of Inspection 8. Name of the Inspecting officers : ADO Omprakesh

9. Name and designation of Officer

: Sh. Sanjeev Garg (Manager)

from the building side 10. Year of Construction

: 1981

: Nil Dated - 03/04/2018

| NO. | Minimum Standards of the | Requirement as per D.O.E | Provided at Site | Remark MR/NMR | | | |
|-----|---|--------------------------|-----------------------------------|------------------|--|--|--|
| 1 | Access to building | 06 Mtrs | 06 Mtrs | MR | | | |
| | Road width | | N/A | N/A | | | |
| | Gate width | N/A | N/A | N/A | | | |
| | Width of internal road | N/A | 1477 | | | | |
| 2 | Number, Width, Type and Arrangement of Exits | | | | | | |
| | a. Number of Staircases Upper Floor | 01 no. | 05 no. | MR | | | |
| | | N/A | N/A | N/A | | | |
| | Basement | N/A N/A | N/A | N/A | | | |
| | b. Width of StaircasesUpper Floor | 1.50 mtr | (1.10 m x3), (1.20 m & 1.45 m) | MR | | | |
| | | N/A | N/A | N/A | | | |
| | Basement | 1477 | | | | | |
| | c. Protection of exits | N/A | N/A | N/A | | | |
| | Fire check door | N/A | N/A | N/A | | | |
| | Pressurization d. No. of continuous staircases | 01 no. | 02 no. | MR | | | |
| | to terrace | 1.5 m | 1.5 m | MR | | | |
| | e. Width of Corridor | 1.0 m | 1.0 m | MR | | | |
| | f. Door Size | | | | | | |
| 3 | Compartmentation. | N/A | N/A | N/A | | | |
| | Fire check door | N1/A | N/A | N/A | | | |
| | Sealing of electrical shafts | N/A | N/A | N/A | | | |
| | Fire rating of shaft door | N/A | N/A | N/A | | | |
| | Water curtain | N/A | N/A | N/A | | | |
| | • Fire Dampers | | | | | | |
| 4 | Smoke Management System. | N/A | N/A | N/A | | | |
| | BasementUpper floor | N/A | N/A | N/A | | | |
| 5 | | | 08 nos. | MR | | | |
| 3 | Total numbers | 04 nos. | | MR | | | |
| | • types | ABC & Co | 1.01 | MR | | | |
| | ISI marking | ISI market | ı lormanod | 3 4 | | | |

M/4

| 6 | First-aid-Hose Reels. | 1 1 | | | | | |
|----|--|-----------|--------------|-----|--|--|--|
| | Total numbers of each floor | 1 no. | 2 no. | MR | | | |
| | Length of hose reel hose | 30 m | 30 m | MR | | | |
| | Nozzle diameter | 5 mm | 5 mm | MR | | | |
| 7 | Automatic fire detection and alarming system. | | | | | | |
| | T | N/A | N/A | N/A | | | |
| | Type of detectorsLocation of main panel | N/A | N/A | N/A | | | |
| | t C Guarantermonol | N/A | N/A | N/A | | | |
| | Location of repeater panelAlternate source of power | N/A | N/A | N/A | | | |
| | Hooter's location | N/A | N/A | N/A | | | |
| 8 | MOEFA | N/A | N/A | N/A | | | |
| 9 | Public address System. | N/A | N/A | N/A | | | |
| 10 | Automatic Sprinkler System. | | | | | | |
| 10 | Basement | N/A | N/A | N/A | | | |
| | upper floor | N/A | N/A | N/A | | | |
| | sprinkler above false ceiling | N/A | N/A | N/A | | | |
| 11 | Internal Hydrants | | | | | | |
| • | size of riser/down-comer | N/A | N/A | N/A | | | |
| | Number of hydrants per floor | N/A | N/A | N/A | | | |
| | Hose Box | N/A | N/A | N/A | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | |
| | Hose Box | N/A | N/A | N/A | | | |
| 13 | Pumping Arrangements. | | | | | | |
| | Ground Level | N/A | N/A | N/A | | | |
| | Discharge of main Pump | N/A | N/A | N/A | | | |
| | ➢ Head of Main Pump | N/A | N/A | N/A | | | |
| | Number of main pumps | N/A | N/A | N/A | | | |
| | Jockey pump out put | N/A | N/A | N/A | | | |
| | Jockey pump head | N/A | N/A | N/A | | | |
| | Standby pump out put | N/A | N/A | N/A | | | |
| | Standby pump Head | N/A | N/A | N/A | | | |
| | > Auto Starting /Manual | N/A | N/A | N/A | | | |
| | stopping > Pump House Access | N/A | N/A | N/A | | | |
| | Fullip House Access | | | | | | |
| | Terrace LevelDischarge of pump | 220 LPM | 220 LPM | MR | | | |
| | Head of the Pump | 40 m | 40 m | MR | | | |
| | > Power supply | Required | Required | MR | | | |
| | > Auto Starting of pump | N/A | N/A | N/A | | | |
| 14 | Captive Water Storage for Fire Fighti | 0.000000 | - NO. 12 100 | | | | |
| 14 | Underground tank capacity | N/A | N/A | N/A | | | |
| | > Draw-off connection | N/A | N/A | N/A | | | |
| | Fire service inlet | N/A | N/A | N/A | | | |
| | > Access to tank | N/A | N/A | N/A | | | |
| | Overhead Tank capacity | 2500 Ltrs | 2500 Ltrs | MR | | | |
| | - (Norhood Lank canacily | | | | | | |

| 16 | Provision of Lifts. | | | | | |
|----|--|-----|-----|------|--|--|
| | Pressurization of Lift Shaft | N/A | N/A | N/A | | |
| | Pressurization of Lift lobby | N/A | N/A | N/A | | |
| | Communication in lift car | N/A | N/A | N/A | | |
| | Firemen's grounding switch | N/A | N/A | N/A | | |
| | Lift Signage | N/A | N/A | N/A | | |
| 17 | Standby power supply | N/A | N/A | N/A | | |
| 18 | Refuge Area. | - | | 14// | | |
| | Total area | N/A | N/A | N/A | | |
| | Location | N/A | N/A | N/A | | |
| 19 | Fire Control Room | | | | | |
| | Detector system panel | N/A | N/A | N/A | | |
| | Flow switch panel | N/A | N/A | N/A | | |
| | PA system panel | N/A | N/A | N/A | | |
| | Battery backup | N/A | N/A | N/A | | |
| | Building Floor Plans | N/A | N/A | N/A | | |
| 20 | Special Fire Protection systems for protection of special Risks, if any: | N/A | N/A | N/A | | |

The Fire protection systems provided in the building were Tested / Checked and found functional, at the time of inspection.

Keeping in view, of the deemed compliance, of the minimum standards on Fire prevention and Fire safety measures as required under the rules.

The Fire safety Certificate issued vide letter no. F.6/DFS/MS/2009/3221 Dated 04/11/09 has grant under circular No. 262-362 dated 17/01/2005 is recommended to renewal under rule 37 of the Delhi Fire Service Rule 2010.

Ombala 23 4 18

Signature of the Inspecting Officer

Name

: - Om Prakash

Designation: - ADO (Shahdara)

DO (East)

DO (East) Sir, f.T. Letter is but up far your kind signatur Please. CFO (MDZ)/ MSCELL FT/A.