GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/FH/2018/WZ/ 1123

Dated: 17/5/18

FIRE SAFETY CERTIFICATE

Certified that the Shrishti Vatika located at Hiran kudna Road, Ghevra, Delhi-110041. comprised of Basement + Ground Floor only owned / occupied by Shrishti Vatika has already been issued Fire Safety Certificate Vide letter No. F6/DFS/MS/FH/2014/WZ/330 dated 10/03/2014. The premises was re-inspected by the officer concerned of Fire Service on 02.05.2018 in the presence of Mr. Brijesh (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with NBC (Part-IV) and that the building / premises is fit for occupancy class Assembly (Group-D) Building excluding basement with effect from 17 / 7 / 2018 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

(AT UL GARG) CHIEF FIRE OFFICER.

Altho/c

Copy to :-

1. The Manager, Shrishti Vatika located at Hiran kudna Road, Ghevra, Delhi-110041.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <u>WWW.dfs.Delhigovt.nic.in</u>

INSPECTION REPORT

Basement + Ground Floor

1. Name & address of the building: Shrishti Vatika, Hiran kudna Road, Ghevra, Delhi-110041.

2. Type of Occupancy : Assembly3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/FH/2014/WZ/330 dated 10/03/2014

5. Fire Safety directives Letter No.: NBC (Part-IV)6. Date of inspection : 02/05/2018

7. Name of the Inspecting Officer: A. K.-Jaiswal (ADO JWP)

8. Name and designation of Officer

from the building side : Mr. Brijesh (Manager)

9. Year of Construction : 2004 10. Applicant's letter No. : - Nil

S	Minimum standards on fire	NBC (Part-IV)	Provided at	Remarks		
No	prevention and fire safety U/R 33	Requirements site		MR/NMR		
1.	Access of building					
	 Road width 	6 mtr	6 mtr	MR		
	• Gate width	4.5 mtr	4.5 mtr	MR		
	 Width of internal road 	6 mtr	6 mtr	MR		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases					
	 Upper floors 	1	1	MR		
	Basements	N/A	N/A	N/A		
	b. Width of staircases	2				
	 Upper floors 	N/A	N/A	N/A		
	Basements	1.25 mtr	1.25 mtr	MR		
	c. Protection of exits					
	Fire check door	N/A N/A		N/A		
	Pressurization	N/A	N/A	N/A		
	d. No of continuous	N/A	N/A	N/A		
	staircase to terrace	NI/A		N/A		
	e. Width Of Corridor	N/A	N/A It is an op	en farm House		
2	f. Door Size	N/A	N/A It is all op	T Tarri Tiouse		
3.	Compartmentation	N/A	N/A	N/A		
	Fire check door					
	• Sealing of electrical shafts	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers		=			
4.	Smoke managements System	20				
	Basements	Exhaust Fan	Exhaust Fan	MR		
	Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers			4		
	Total numbers	4	8	M/R		
	• Types	ISI marked ABC/CO ₂	Provided	M/R		
	IS marking	Required	Provided	M/R		
	• 15 marking	Required	Frovided	IVI/ IX		

	6.	First – Aid Hose Reels				
	0.	Total numbers on	1		4	
		each floor	1	1	MR	
			20		1	
		 Length of hose reel hose 	30mtr	30mtr	MR	
		Nozzle diameter	5 mm			
-	7.	Automatic fire detection and		5 mm	MR	
	•	Type of detector	N/A			
		Location of Main		N/A-	N/A	
		Panel	N/A	N/A	N/A	
		Location of Repeater	N/A	DI/A		
		Panel	IV/A	N/A	N/A	
*		Alternate source of	N/A	DI / A		
		power	IN/A	N/A	N/A	
		Hooters' Location	N/A	2.7		
8		MOEFA		N/A	N/A	
9		Public Address System	Required	Provided	MR	
-	0.	Automatic Sprinkler System	N/A	N/A	N/A	
		Basements	N/A	DI/A		
		Upper Floor	N/A	N/A	N/A	
		• Sprinkler above false		N/A	N/A	
		ceiling	N/A	N/A	N/A	
1		Internal Hydrants				
		• Size of riser/down-	100 mm	100		
		comer	100 11111	100 mm	MR	
		 Number of hydrants 	1	1	NAD.	
		per floor		1	MR	
		Hose Box	1	1		
12		Yard Hydrants		1	MR	
		• Total number of	N/A	10.7		
		hydrants	IN/A	N/A	N/A	
		Hose Box	N/A	DI/O		
13		Pumping Arrangements	N/A	N/A	N/A	
	•	Ground Level	N/A			
		Discharge of main pump	N/A	DI/A		
	>	Head of main pump	N/A	N/A	3	
	>	Number of main pumps	N/A	N/A	N/A	
	>	Jockey pump out put	N/A	N/A	N/A	
	>	Jockey pump head	N/A	N/A N/A	N/A	
	>	Standby Pump out put	N/A	N/A	N/A	
	>	Standby Pump Head	N/A	N/A	N/A	
	>	Auto Staring/Manual	N/A	N/A	N/A N/A	
		stopping		14/7	N/A	
	>	Pump House Access	N/A	N/A	N/A	
	•	Terrace level				
	1	Discharge of pump	900 LPM	900 LPM	MR	
	>	Head of the pump	40 MH	40 MH		
	>	Power supply	Required	Provided	MR	
		Auto starting of pump	Required	Provided	MR	
14.			•	riovided	MR	
The solider for the lighting						
		 Underground tank capacity 	N/A	N/A	N/A	
		> Draw of connection	NI/A			
		Fire service inlet	N/A	N/A	N/A	
			N/A N/A	N/A	N/A	
		Overhead Tank	15 000 Ltr	N/A	N/A	
		- CALLOUND I CHILL				

				S		
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of lift lobby	N/A	N/A	N/A		
	Communication in lift	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	➤ Lift Signage	N/A	N/A	N/A		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A			
	> Total area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19.	Fire control room					
	Detector system panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	➤ PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20.	Special Fire Protection	N/A	N/A	N/A		
	Systems for Protection of special Risks, if any;	,				

Note:- Sprinkler system in basement is not required as area of the basement is only 94m² which is less than 200m².

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/FH/2014/WZ/330 dated 10/03/2014 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name

: Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

T. is added for signaturefl.