FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F-6/DFS/MS/SCHOOL/2018/WZ/ / O S

Dated: 6 /05/2018

FIRE SAFETY CERTIFICATE

Certified that the **Spring Field Middle School** located at **FD Block, Madhuban Chowk Pitam pura, Delhi** – **110034** comprised of Ground + one Upper Floor was issued FSC vide Letter No. F-6/DFS/MS/SCHOOL/2015/WZ/79 dated- 15/01/2015. The premises was re inspected by the officer concerned of this department on **01-05-2018** in the presence of **Sh. Jagdish Gandhi (Manager)** and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance F-6/DFS/MS/BP/96/888 dated 26/7/96 and that the premises is fit for occupancy class "Educational" Group B with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Atul Garg) Chief Fire Officer, Delhi Fire Service.

Copy to:

A

 The Principal, Spring Field Middle School FD Block, Madhuban Chowk Pitam pura, Delhi – 110034.

2. Directorate Of Education Old Secretariat Delhi – 110054.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Spring Field Middle School Located at, FD Block, Madhuban Chowk Pitam pura, Delhi – 110034.

2. Type of Occupancy

: Educational (Ground + 1 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC: F-6/DFS/MS/SCHOOL/2015/WZ/79 dated- 15/01/15

5. Fire Safety directives Letter No.: F-6/DFS/MS/BP/96/888 dated 26/7/96

6. Date of inspection

: 01-05-2018

7. Name of the Inspecting Officer: Udai vir singh, ADO (WP)

No. of Students=120 No. of class rooms=8 Plot area=782 m² Covered area=260 m²

8. Name and designation of Officer

from the building side

:Sh.Jagdish Gandhi(Manager)

9. Year of Construction

: 1997

10. Applicant's letter No.

:SFS dated -06/04/2018

| S No | Minimum standards on fire prevention and fire safety U/R 33 | NBC/Directive issued | I I O I I GO O O O O O | Remarks MR/NMR |
|---------|--|--------------------------|-------------------------------------|-------------------|
| 1. | Access of building | | 1 | |
| 1. | Road widthGate widthWidth of internal road | Accessible Accessible NA | 06mProvided 338cm Provided NA | MR MR NA |
| 2. | Number, width, Type & Arrang a. Number of staircases | gements of exits | | |
| | a. Number of staffcasesUpper floorsBasements | 1 NA | 2 Provided NA | MR NA |
| N. | b. Width of staircasesUpper floors | 1.5m | 153cm &75cm | MR |
| | Basementsc. Protection of exitsFire check door | NA | NA | NA |
| | Pressurization | NA | NA | NA |
| | d. No of continuous | NA | NA | NA |
| | staircase to terrace e. Width Of Corridor | 1 | Provided | MR |
| | f. Door Size | 1.5m | 166cm | MR |
| | 1. 2001 | 1 mtr | -90cm | MR (Old case) |
| | | | | |

| 3. | Compartmentation | | | | | |
|-----|---|-----------------------|------------|--------|--|--|
| | Fire check door | NA | NA | NA | | |
| | Sealing of electrical shaft | t NA | NA | NA | | |
| | Fire Rating of shaft door | | NA | NA | | |
| | Water Curtain | NA | NA | NA | | |
| | Fire Dampers | NA · | NA | NA | | |
| 4. | Smoke managements System | | | | | |
| | Basements | NA | NA | NA | | |
| | Upper floors | NA | NA | NA | | |
| 5. | Fire Extinguishers | | | r | | |
| | Total numbers | 04nos. | 4 Provided | MR | | |
| | Types | ABC & CO ₂ | Provided | MR | | |
| | IS marking | ISI marked | Provided | MR | | |
| 5. | First – Aid Hose Reels | | | | | |
| | Total numbers on each floor | NA | Provided | NA | | |
| | Length of hose reel hose | NA | Provided | NA | | |
| | Nozzle diameter | NA | Provided | NA | | |
| 7. | Automatic fire detection and alarming system | | | | | |
| | Type of detectors | NA | NA | NA | | |
| | Location of Main Panel | NA | NA | NA | | |
| | Location of Repeater Panel | NA | NA | NA | | |
| | Alternate source of power | NA | NA | NA | | |
| | Hooters' Location | NA | NA | NA | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | Required | Provided | MR | | |
| 10. | Automatic Sprinkler System Required Provided NR | | | | | |
| | Basements | NA | NA | NA | | |
| , | Upper Floor | NA | NA | NA | | |
| | Opper FloorSprinkler above false | NA | NA NA | NA | | |
| | ceiling | | | | | |
| 11. | Internal Hydrants: | | | | | |
| 11. | Size of riser/down- | NA | NA | NA | | |
| | comer | | | | | |
| | Number of hydrants per | NA | NA | NA | | |
| | floor | <u></u> | | | | |
| | Hose Box | NA | NA | NA | | |
| 12. | Yard Hydrants | | | | | |
| | Total number of | NA | NA | NA | | |
| | hydrants | | | 1.11.2 | | |
| | | | | * | | |

| 3. I | Pumping Arrangements: | | | | |
|--|--|----------|--------------|----------|--|
| | Ground Level Ground Level | NA | NA | NA | |
| | Discharge of main | INA | | | |
| | pumpHead of main pump | | | | |
| | Number of main pumps | NA | NA | NA | |
| | > Jockey pump out put | NA | NA | NA | |
| | > Jockey pump head | NA | NA | NA | |
| | Standby Pump out put | NA | NA | NA | |
| | Standby Pump Head | NA | NA | NA | |
| | Auto Staring/Manual | NA | NA | NA | |
| | stopping | NA | NA | NA | |
| | Pump House Access | | 37.4 | DIA | |
| | Terrace level | NA | NA | NA | |
| | Discharge of pump | | 450 1 D | vided NA | |
| | > Head of the pump | NA | 450 lpm Prov | NA NA | |
| | Power supply | NA | Provided | NA NA | |
| | Auto starting of pump | NA | NA | NA NA | |
| | | NA | NA | INA | |
| 14. | Captive water Storage for fire fighting: | | | | |
| | Under ground tank | ·NA | NA | NA | |
| | capacity > Draw off connection | NA | NA | NA | |
| | Fire service inlet | NA | NA | NA | |
| | > Access to tank | NA | NA | NA | |
| | Overhead Tank | 5000Ltrs | Provided | MR | |
| Canada and | capacity | 3000243 | | | |
| 15 | Exit Signage | NA | NA | NA | |
| 16. | Provision of Lifts | | • | | |
| 10. | 1 TOVISION OF EATE | | | | |
| | > Pressurization of Lift | NA | NA | NA | |
| | Shaft Pressurization of lift | NA | NA | NA | |
| | lobby | | | | |
| | Communication in lift | NA | NA | NA | |
| | Car | NA | NA | NA | |
| | Fireman's Grounding | | | 5 | |
| The state of the s | Switch | NA | NA | NA | |
| | Lift Signage | | | 7 A | |
| 17. | Standby power supply | NA | NA | NA | |
| 18. | Refuge Area | | 27.4 | NIA | |
| | > Total area | NA | NA | NA | |
| | > Location | NA | NA | NA | |
| | | | | | |
| | | | | | |
| | | | | | |

| 19. | Fire control room | | | | |
|-----|----------------------------------|----|------|----|--|
| | Detector system panel | NA | NA | NA | |
| | > Flow Switch Panel | NA | NA | NA | |
| | > PA System Panel | NA | NA | NA | |
| | Battery backup | NA | . NA | NA | |
| | Building Floor Plans | NA | NA | NA | |
| 20. | Special Fire Protection | NA | NA | NA | |
| | Systems for Protection of | | | | |
| | special Risks, if any; | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F-6/DFS/MS/SCHOOL/2015/WZ/79 dated- 15/01/2015 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name

Name

Name

Designation Designation

Dy sto (2) multi nops 2

Sola March March 18/15/18

Sir FF letter popol up